UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

U0P30174

7.2K Capacity Flat Deck - Tilt, TVH

GENERAL

- GVWR: 9,990 Lbs.
- GAWR: 5,080 Lbs. (*per axle*)
- Estimated Empty Weight: 2,700 Lbs.
- Total Capacity: 7,290 Lbs.
- Hitch: 3" Towing Lunette Eye, Adjustable, Two Bolt Attachment
- Safety Chains: (2) 5/16" Grade 70 with Slip Hook Ends

OVERALL DIMENSIONS

- 23' 6" L x 96" W x 34" H
- Deck Dimension: 18'



RUNNING GEAR

- Tires: (5) Goodyear 225/75R 15 "D" (*8ply rating*) 2,450 Lbs. per Tire
- Wheels: 15" x 6" Steel Wheels
- Brakes: Dexter 12" x 2" Electric
- Axles: (2) Dexter 5,200 Lbs. Rated

FRAME

- Frame Rails: C7 Channel
- Cross Members: H Frame Design Specific to Trailer

DECK

- Material: 3.0# Expanded Steel Mesh in Track Area (*32" Wide*) Open Center Section
- Loading Angle: 11*

ELECTRICAL

- Wire Harness: Color Coded Sealed Modular System
- Breakaway System: 12 Volt Sealed Lead Battery in Protective Case, Charge Level Indicator, Located on Tongue
- Electrical Connection: 6 Pole Round or 7 Way RV Wired to SAE Standard
- Lighting / Conspicuity: Shock Mounted Sealed LED Lights with Smooth Top Reflectors, White Reflective Markings for Higher Visibility in White Out Conditions

FINISH

- Galvanized

OTHER

- Tongue Jack: 7K Lbs. Top Crank Drop Leg with Integral Sand Foot
- Wheel Chock Holders for Customer Supplied Wheel Chocks
- Registration Holder: Sealed & Located in Tongue Area

SPECIAL FEATURES

Tilt Deck Holder Down (1) Tipper Latches with Cam Over Positive Transport Lock

Tilt Cushion Cylinder: 2" x 18" Hydraulic Cushion Cylinder

Spare Tire Carrier: Located Under Tongue

Mud Flaps: (2) 10" x 22" Anti-Sail

D-Ring Tie Down: (2) side ½" Forged D-Rings & on Rear Deck Rail

Front Tie Downs: (2) ea. ½" D-Rings Located on Side of Hitch

Cargo Control: (4) ea. Ratchet Assemblies, Adjustable Angle Snap Hook Ends, Winch Bar

Tool Storage: Located in Tongue with lockable Cover, slip Resistant Tread Plate Surface