UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

U0P30201

11.5K Capacity Equipment

GENERAL

- GVWR: 16,000 Lbs.
- GAWR: 8,000 Lbs. (*per axle*)
- Estimated Empty Weight: 4,450 Lbs.
- Total Capacity: 11,550 Lbs.
- Hitch: 3" Towing Eye, Adjustable, 20K Gross Trailer Weight
- Safety Chains: 3/8" Grade 70 Chain with Clevis Hooks & Safety Latches



OVERALL DIMENSIONS

- 333 9/16" L x 95 ½" W x 101 9/16" H
- Deck Dimension: 216" with 36" Beaver Tail L x 91 5/16" W x 32 3/32" H

RUNNING GEAR

- Tires: ST235/85R16 LRE
- Wheels: Galvanized 16" 6K with 8 Bolts on a 6.5" Bolt Circle
- Brakes: Electric
- Axles: (2) 8,000 Lbs. Underslung Type Galvanized Finish

FRAME

- Frame Rails: W8 x 10 I-Beam ASTM A36
- Cross Members: 11 GA HR Sheet ASTM A569

DECK

- Material: 2 x 6 Treated Pine Board

RAMP

- Dimensions: (2) 72" L x 19" W, Vertical Store, Ladder Style

ELECTRICAL

- Wire Harness: No Internal Splices, enclosed in Protective Loom
- Breakaway System: To Federal DOT Standards
- Electrical Connection: 7 Way Plug
- Lighting / Conspicuity: To Federal DOT Standards, Conspicuity Tape Where Practicable

FINISH

- Hot Dipped Galvanizing: Entire Trailer & Ramps Hot Dipped Galvanized
- Non-Galvanized Areas
  - Preparation: Iron Phosphate Conversion Treatment, Chromium-Free Post Treatment
  - Primer: Epoxy Ester High Solids Primer
  - Topcoat: Polyurethane Two Component High-Solids Enamel

OTHER

- Tongue Jack: 7K Capacity, Drop Foot, Top Wind
- Registration Holder: Water Resistant

SPECIAL FEATURES

- Tool Bin in tongue Area (*expanded metal floor, steel lid with hasp)*
- Below Deck Ramp Deck Spring Assist