UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

U0P30251

11.8K Capacity Beaver Tail Fixed
For Tucker Sno-Cat® style vehicles

GENERAL

- GVWR: 16,100 Lbs.
- GAWR: 14,000 Lbs.
- Estimated Empty Weight: 4,250 Lbs.
-
- Total Capacity: 11,850 Lbs.
- Hitch: 3" Lunette Eye, 60K, Adjustable
- Safety Chains: 3/8" G70 with G70 Clevis Mount Slip Hook



DIMENSIONS

- Overall: 26' 4" L x 96" W x 34 1/2" H
- Deck Dimension: 20'
- Beavertail: 2' L
- Ramps: 6' Stand Up Cleat Style
- Tongue Length: 48" (*to hitch plate*)

DECK

- #4 Expanded Steel Grating Entire Deck
- D-ring Tie Downs: (3) Each Side, 2 Rear 5/8" forged D-Rings
- Front Tie Downs: (2) Each 5/8" Forged D-Rings
- Splash Guards: Located Over Tires

RUNNING GEAR

- Tires: ST235/80R16 "E" 8 Ply Rating
- Wheels: 16" x 6" Steel Wheels, 8 on 6.5" Bolt Pattern
- Brakes: Dexter 12" x 2", Self-Adjusting, Electric
- Axles: Dexter Straight Axles, Beam Rating of 7K Each
- Spare Tire Carrier: Located Under Tongue
- Suspension: Multi-Leaf Slipper Spring, 7K Rated

FRAME

- Frame Rails: (2) Each 6" Tall HD Center Guide Rails, Transitioning Down Beavertail, Set at 26" Apart Outside to Outside Measurement for Prinoth Trooper HD
- Traction Assist: (4) Each bolt on Inverted Channel Traction Cleats Attached to Beavertail

ELECTRICAL

- Wire Harness: Color Coded Sealed Modular System
- Breakaway System: 12V Sealed Lead Battery in Protective Case, Mounted
- Breakaway Battery Charger: Diode Protected Charge Circuit with Charge Indicator Light
- Electrical Connection: 7 Way J560 Plug End
- Lighting / Conspicuity: DOT Approved LED Sealed Lights & Reflectors, Red / White Reflective Markings for Higher Visibility

FINISH

- Hot Dipped Galvanizing

OTHER

- Tongue Jack: 10K Capacity, Side Crank, Drop Leg with Integral Sand Foot
- Registration Holder: Located in Tongue Area

SPECIAL FEATURES

- Mud Flaps: (2) 10" x 22" Anti-Sail