UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

UTL110

5K Capacity Stick Pipe Hauler

GENERAL

- GVWR: 10,000 Lbs.
- GAWR: 5,000 Lbs. (*per axle*)
- Estimated Empty Weight: 1,900 Lbs.
- Total Capacity: 5,000 Lbs.
- Hitch: 3" Towing Eye, Adjustable, 12K Lbs. Gross Trailer Weight

OVERALL DIMENSIONS

- 45' 1" L x 86 3/16" W x 75" H
- Deck Dimensions: 39' 11" L x 62" W x 31 ¼" H

RUNNING GEAR

- Tires: LT225/75R x 15 LRD
- Wheels: 15" x 6" 6 Bolts on a 5.5" Bolt Circle
- Brakes: Electric
- Axles: (2) 5,000 Lbs. Underslung Type

FRAME

- Frame Rails: C8 x 11.5 Structural Channel ASTM A36
- Cross Members: 7 Gauge HR Sheet ASTM A569, 4" x 2" x 3/16" Wall Steel tube ASTM A500B, C8 x 11.5 Channel

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway system: To Federal DOT Standards
- Electrical Connection: 6 Pin Plug
- Lighting / Conspicuity: Lighting to Federal DOT Standards, Conspicuity Tape Where Practicable

FINISH

- Preparation: Iron Phosphate Conversion Treatment, Chromium-Free Post Treatment
- Primer: Epoxy Ester High Solids Primer
- Topcoat: Polyurethane Two Component High-Solids Enamel

Special Features:

- Removable Wood Side Posts for Easy Loading

