UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

UOP30093

16.8K Capacity Beaver Tail

GENERAL

- GVWR: 22,000 Lbs.
- GAWR: 9,610 Lbs. *each axle*
- Estimated Empty Weight: 5,200 Lbs.
- Total Capacity: 16,800 Lbs.



DIMENSIONS

- Overall: 288.5" L x 96" W x 36.25" Deck H
- Deck: 215.5" L x 96" W x 36.25" H
- Hitch: 3" Towing Eye, Galvanized, 4 Bolt 60K Capacity
- Safety Chains: 3/8" G70 with G70 Clevis Mount Slip Hook

DECK

- Material: C7 x 9.8 Structural Channel ASTM A36 Bed Frame, C6 x 8.2 Crossmember
- Beaver Tail: 36"
- Pull Out Light Brackets: 6 Total, 3 Each Side
- Deck Tilt: Hydraulic Cushion Cylinder. Deck stays in position when tilted.
- Center Guide Rails: 8" H x 45° Slope Inward @2" from Base of Deck
  30° Inward Taper Starting 36" from Rear Transition to Center
- Vehicle Stop: Bolt On / Adjustable
- Access: Bolt on Handrail on tongue & Street Side Flexible Grip Strut Step

RUNNING GEAR

- Tires: 215/75R17.5 LRH 4805 lb. Capacity Each
- Wheels: 17.5" x 6.75" 8 Lug on a 6.5" Center White PC
- Brakes: 12.25" x 4" Air Brakes with 4S, 1M ABS System, Spring Brakes & Slack Adjusters on Both Axles
- Axles: 10,000 Lbs. Dexter HD Oil Bath Hubs
- Suspension: 3" Rubber Bushed Springs with Rubber Bushed EQ

FRAME

- Frame Rails: C10 x 20 Structural Channel ASTM A36
- Cross Members: C4 x 5.4 Structural Channel ASTM A36

ELECTRICAL

- Wire Harness: Sealed Modular Harness
- Electrical Connection: 7-Way J560 Spec Plug (*4 taillight compatible*)
- Lighting / Conspicuity: LED Lighting to DOT with 6 Slide Out Markers

FINISH

- Hot Dipped Galvanized Finish
- Preparation: Phosphate Wash **non-galvanized item*
- Topcoat: Polyurethane – Spectrum Gray **non-galvanized item*

OTHER

- Tongue Jack: 10K Drop Foot, Top Wind
- Registration Holder: MGS#16001 (Truck-Lite Watertight)
- Tongue Mount Toolbox
- Spare Tire & Wheel Mounted Under Tongue
- Mud Flaps (2)
- Splash Guards Located Over Tires