UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

EPT20321

28.6K Capacity Telescopic Pole Trailer 70ft

GENERAL

- GVWR: 34,800 Lbs.
- GAWR: 15,000 Lbs.
- Estimated Empty Weight: 6,280 Lbs.
- Total Capacity: 28,520 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, Adjustable, 60K Lbs. Gross Trailer Weight
- Safety Chains: 1/2" Grade 70 Chain with G70 Clevis Hook & Safety Latch

OVERALL DIMENSIONS

- Retracted - 30' L x 90" W
- Extended – 47'L

RUNNING GEAR



- Tires: 215/75R 17.5 LRH
- Wheels: Galvanized, 17.5" x 6.75" 8 Bolts on 275mm" Bolt Circle
- Brakes: Electric
- Axles: 15,000 Lb. Dexter Sprung Axles

FRAME

- Frame Rails: 4' x 8"x 1/4" Wall Structural Tube ASTM A500B
- Tongue: 8" x 8" x ¼" Wall Structural Tube ASTM A500B.
- Tongue Socket: 10" x 10" x ¼" ASTM A36 –
- 72" Long Formed Tongue Socket with Adjustable Sintered Bronze Bushings At Both Ends
- Cross Members: Formed ¼" Plate And 2" X 2" X 3/16" Tubing

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom. Internal Tongue Wiring Enclosed In Cat Track.
- Socket On Tongue Accepts Standard 12' Coiled Cord (Supplied)
- Breakaway system: To Federal DOT Standards with Solar Maintainer
- Electrical Connection: Coiled Cord Wired to J560 Spec
- Lighting / Conspicuity: LED to DOT

FINISH

- Hot Dipped Galvanizing
- Non-Galvanized Parts – Preparation: Iron Phosphate Conversion Treatment, Chromium-Free Post Treatment
- Primer: Epoxy Ester High Solids Primer
- Topcoat: Polyurethane Two Component High-Solids Enamel

OTHER

- Jack: (2) -10,000 Lb. Trunnion Mount. One On "A" Frame And One On Tongue
- Registration Holder: Truck Lite

Special Features:

- Bronze Bushings On Tongue Receiver
- Integral Light Bar with Ratchet Strap And 25' Cord
- Flexible Cable Carrier to Protect Tongue Wiring
- (3) Pole Bolsters (Two on Chassis, One on Extendable Tongue)
- (4) Adjustable Pole Stanchions on Rear Bolsters
- (2) Pole Chocks on Front Bolster
- (6) 4" Pole Binders (Ratchet Type) With Heavy Duty 5,000 Lb. Winches (2) Per Bolster, (1) Winch Handle,
- Manual Holder