

Product Description

Shingle-Seal- A waterborne rejuvenating spray-on sealer is made with a blend of resins engineered to create a sealer with excellent durability and adhesion to all asphalt-based roofing shingles and rolled roofing. This sealer penetrates the surface forming a durable film protecting the surface from moisture and weathering. Shingle-Seal improves the adhesion of the granules to the shingle and therefore restoring and extending the life of the roofing shingle. Stain blocking resins allow application over aged tar and worn shingles. Shingle-Seal rejuvenates old and weathered shingles making them resistant to UV degradation, high winds, and hail, while also rejuvenating the colors/appearance and flexibility of the shingles.

Uses

- Shingles
- Roofing Tiles
- Rolled Roofing
- Bond Extra Granules

Advantages

- Excellent UV Resistance
- Re-Apply 5 Years
- Low-Cost vs. New Roof
- Low V.O.C.
- Provides wind protection (flexibility)
- Excellent Weathering
- Abrasion Resistant (hail)
- Time Savings w/ No Mess
- Chalk Resistant
- Clean & 'Green'-No messy, intrusive tear out, Keeping old shingles out of the landfills

Packaging	5-gallon plastic pails. (Makes 10 gallons).
Coverage	200 - 500 ft ² / gallon @ 2mils.
Dry Time	(77°F & 50% Rel. Humidity.) 1 hour to touch.
Preparation	Surfaces should be free of defects, dirt, and contamination.
Application	Spray apply or can be brushed or rolled on. Thin 50/50 with tap water. Do not apply coating system below 45 °F. Best results are obtained when surface and air temperatures are above 60°F and below 100°F.
Clean-Up	Clean brushes, roller-covers, and spray rigs with ordinary tap water until the wash water is clear. Clean up overspray with a mild soap and water solution. (Do not wait longer than 15 minutes).