



Stormtite®

SYNTHETIC UNDERLayment



Synthetic underlayment replaces 15-lb roofing felt.

Stormtite®

SYNTHETIC UNDERLayment



PRODUCT SPECIFICATIONS

Length	250 ft (76.2 m)
Width	48" (1,219 mm)
Roll Contents	1000 sq ft (92.9 m ²)

Note: All values shown are approximate.

Synthetic underlayment that will totally rock the way you roll

IKO Stormtite synthetic underlayment is engineered to be used under asphalt shingles. And it has qualified as an IKO Proformax Integrated Roofing Accessories. It is a cost-effective alternative to traditional #15 asphalt saturated felt.

Here's why it rocks.

- ✓ Stronger than felt. **Stormtite** is more resistant to tearing and shredding when installers walk on it. Plus it's coated top and bottom with tough polyolefin for superior weather resistance.
- ✓ More flexible, even in cold weather. **Stormtite** is easy to install around vents, dormers, skylights and other typical roof structures. It lays flat without curling and is super durable.
- ✓ Synthetic, non-breathable material. **Stormtite** effectively sheds water that gets behind shingles and it's engineered to be a vapor-retarder.
- ✓ Lighter than felt. A single roll of **Stormtite** contains 1000 square feet.
- ✓ Each roll is printed with dashed lines every 2-inches from the center and bold dots at the recommended fastener areas for easier and improved application.

Ready to Roll with Stormtite?

PROFORMAX™

INTEGRATED ROOFING ACCESSORIES

Shingles alone are usually not enough to protect your home. IKO has developed superior multilayered roofing components incorporating our industry-leading products. A complete roofing system ensures your roof's optimum performance.

1 DECK PROTECTION. IKO StormShield® Ice & Water Protectors and IKO GoldSeam™ Roof Sealing Tape.

2 SYNTHETIC UNDERLAYMENT. Stormtite®.

3 ROOF STARTERS. Leading Edge Plus™ or EdgeSeal®.

4 CAPPING SHINGLES. Hip & Ridge 12™ or UltraHP/UltraHP IR™.

