

BUILT TO MEET
Grade™

**SCAFFOLDING
AND DRYWALL
TRADES**



METALTECH®

**BUILT TOUGH FOR
SAFETY**

6' BUILDMAN[®] DRYWALL BAKER SCAFFOLD

NEW WITH
SAFECLIMB[™]
PLATFORM



SAFECLIMB TRAPDOOR
AND ANTI-SLIP DECK



EACH END CAN ADJUST
SEPARATELY TO BE USED
ON BOTH LEVEL SURFACES
AND STAIRWAYS



SAFECLIMB RUNG STEP



QUICK AND EASY HEIGHT
ADJUSTMENT



TECHNICAL FEATURES

ASSEMBLED DIMENSIONS (WxDxH)	75 3/4 X 31 X 76 IN. (192.4 X 78.7 X 193 CM)
WEIGHT	165 LB (74.8 KG)
LOAD CAPACITY	1,500 LB (680 KG) COMBINED WEIGHT OF USER + MATERIALS
WORKING HEIGHTS	FROM 29 TO 71 1/2 IN. (73.7 TO 181.6 CM). 2 IN. (5 CM) INCREMENT ADJUSTABLE HEIGHTS
REACH	12 FT (3.7 M). STACKABLE UP TO 3 UNITS HIGH FOR 24 FT (7.4 M) REACH
DECK (WxD)	29 X 67 IN. (73.7 X 170.2 CM) PLATFORM WITH TRAPDOOR. 19/32 IN. (15 MM) PLYWOOD, SLIP-RESISTANT
BRACE	DOUBLE LOCKING STEM MECHANISMS WITH TIGHTENING KNOBS TO PREVENT LOOSENESS IN THE STRUCTURE
CASTERS	6 IN. (15 CM) DOUBLE LOCKING HEAVY DUTY, NON-MARKING
MODEL	I-BMSS
UPC	778300100057

* All trademarks and registered trademarks listed above are the property of their respective owners.

12' REACH

1,500 lb

LOAD
CAPACITY



ANTI-SLIP
DECK



TRAPDOOR
ACCESS



NON-
MARKING



STACKABLE

OSHA
ANSI
CSA

ACCESSORIES

FOR 6' BUILDMAN® DRYWALL BAKER SCAFFOLD



**CLIMB-N-GO
MOTORIZED SYSTEM
FOR BAKER TYPE
SCAFFOLD**

MODEL: I-CNG
UPC: 778300006083



GUARDRAILS SYSTEM

MODEL: I-BMSGRJP
UPC: 778300001828



**SET OF 14 IN.
OUTRIGGERS
WITH CASTERS
FOR 2 UNITS HIGH**

MODEL: I-BMS04
UPC: 778300100262



**SET OF 46 IN.
OUTRIGGERS
WITH CASTERS
FOR 3 UNITS HIGH**

MODEL: I-BMS04TT
UPC: 778300003792



39 IN. HIGH EXTENSION

MODEL: I-BMSSEK
UPC: 778300001323



SCAFFL@CK

SAFETY BRAKES

MODEL: I-ISL
UPC: 778300001552



**SET OF 4
LEVELING JACKS**

MODEL: I-IBSJP12H4
UPC: 778300001644



**SET OF 4
BASE PLATES**

MODEL: I-IBBF4
UPC: 778300001699

**GUARDRAILS
SYSTEM**

**3 UNITS
TOWER
24 FT
REACH**

17.5'

**46 IN.
OUTRIGGERS**



JOBSITE SERIES PERRY STYLE™

- 100% fully compatible with Nu-Wave Perry Model 660
- 1,000 Lb load capacity
- Quick and easy height adjustment
- 5/8" Anti-slip deck
- Double locking 5" casters
- Meets OSHA and ANSI

METALTECH®



**NO TOOLS
REQUIRED**



**ANTI-SLIP
DECK**

**OSHA
ANSI**

MEETS



**NU-WAVE
PERRY 660*
COMPATIBLE**

1,000 lb

LOAD CAPACITY


**BUILT TOUGH FOR
SAFETY**

* Nu-Wave Model 660 is a trademark owned by Nu-Wave Manufacturing, LLC.

JOBSITE SERIES PERRY STYLE™

GUARDRAILS SYSTEM

Use for added safety or when stacking units



TOOL TRAY

Safer organized clutter free work area,
installs at any rung height



SET OF 14" OUTRIGGERS WITH CASTER

Use when stacking 2 units



SET OF 46" OUTRIGGERS WITH CASTER

Use when stacking 3 units



**CLIMB-N-GO
MOTORIZED SYSTEM**



**SCAFFLOCK™
SAFETY BRAKES**



**SET OF
BASE PLATES**



**ADD-ON STORAGE
SHELF**



40" HIGH EXTENSION



**SET OF FOUR 5" HEAVY
DUTY CASTERS**



	PERRY STYLE™
ASSEMBLED DIMENSIONS (WDXH)	73.75 X 29.25 X 79 IN.
PACKAGE DIMENSIONS (WDXH)	75.25 X 30 X 5.25 IN.
WEIGHT	125 LB
COMPATIBLE WITH	NU-WAVE PERRY MODEL 660*
LOAD CAPACITY	1,000 LB (454 KG). COMBINED WEIGHT OF USER + MATERIALS
WORKING HEIGHTS	FROM 28.5 TO 78.75 IN. / 2 IN. INCREMENT ADJUSTABLE HEIGHTS
REACH	12 FT / STACKABLE UP TO 3 UNITS HIGH FOR 24 FT REACH
FINISH	POWDER COATED
PLATFORM	5/8 IN. PLYWOOD THICK WITH PROTECTIVE STEEL EDGE BANDING. ANTI-SLIP
STRUCTURE	1.5 IN. SQUARE TUBE. 16 GAUGE STEEL
CASTERS	5 IN. DOUBLE LOCKING HEAVY DUTY
STANDARDS	ANSI AND OSHA
MODEL	I-CISCPY
UPC	778300200115

* Nu-Wave Model 660 is a trademark owned by Nu-Wave Manufacturing, LLC.

METALTECH®

WWW.METALTECH.CO

1 800 363-7587

Metaltech is a registered trademark of Metaltech-Omega inc. | www.metaltech-omega.com | NOTE: Pictures and descriptions in this brochure may differ from actual product. S-CISCPY-NA-EN12