



USAG GLADIATOR

A4.0 6x6

TECHNICAL SPECS

PART	NIJ0108.01 Level III	EN1063 BR6	STANAG4569 Level 2
Roof	✓	✓	✓
Dome	✓	✓	✓
Sides	✓	✓	✓
Doors	✓	✓	✓
Floor	✓	✓	✓
Engine	✓	✓	✓
Windows	✓	✓	✓
Radiator Grill	✓	✓	✓
Tires	✓	✓	✓
Bullet Slits	✓	✓	✓

ACCESSORIES

Seats	23 occupants, longitudinal configuration; upholstered in flame-retardant fabric; shock absorbing system.
A/C Unit	Yes
Gas Extractor	Yes
Lighting System	Internal and External LED
Intercom/Siren	High-powered Military-grade
Drone Platform	Yes
CCTV	Yes; 17" Monitor
Anti-barricade Shovel	Optional
Anti-explosive Deflector (V-Shape)	On the Bottom of the Vehicle
Communication Rack	Yes
Drawers and Compartments	For Supplies

Engine

Engine	13000 cm³ turbo-charged
Number of cylinders	6L
Power (hp)	500 hp Euro 6
Torque (lb-ft @ rpm)	2500 @ 925-1340
Fuel	Diesel
Emissions level	Euro VI

Transmission

Gearbox	Automatic 8 speeds
Maximum performance modes	Economy mode, Power mode, Off-road mode
Traction	6x6

Chassis

Direction	Hydraulic
Front suspension	Semi-elliptical leaf spring
Rear suspension	Semi-elliptical leaf spring
Brake system - type	100% air
ke system - ABS	Yes
Tire measurements - front	385/70 R22.5
Tire measurements - rear	295/80 R22.5

Weights and capacities

Vacuum weight	67100 lb
Fuel tank	93gl

Electrical system

Electrical system voltage	24V
Battery	12V 120 Ah
Battery amount	2 - series
Alternator	24V-250 Amp

Dimensions

WB (distance between axes) (ft)	20.83
OL (total length) (ft)	31.92
OH (total height) (ft)	10.5
OW (total width) (ft)	8.06

*Technical specifications are subject to modification and adjustment in accordance with customer requirements.