



USAG GLADIATOR

V2.0 4x4

TECHNICAL SPECS

	NIJ0108.01 Level III	EN1063 BR6	STANAG4569 Level 1
Roof	✓	✓	✓
Dome	✓	✓	✓
Sides	✓	✓	✓
Doors	✓	✓	✓
Floor	✓	✓	✓
Engine	✓	✓	✓
Windows	✓	✓	✓
Radiator grille	✓	✓	✓
Tires	✓	✓	✓
Bullet slits	✓	✓	✓

Accessories	
Seats	10 occupants, longitudinal configuration; upholstered in flame-retardant fabric; shock-absorbing system
AC unit	Yes
Gas extractor	Yes
Lighting system	Internal and external LED
Intercom/siren	High-powered military-grade
Drone platform	Yes
CCTV	Yes; 17" monitor
Anti-barricade shovel	Optional
Anti-explosive deflector (V-shape)	On the bottom of the vehicle
Communications rack	Yes
Drawers and compartments	For supplies

Engine	
Engine	13000 cm³ turbo-charged
Number of cylinders	6 L
Power (hp)	370 hp Euro 6
Torque (lb-ft @ rpm)	2350 @ 925-1340
Fuel	Diesel
Emissions level	Euro VI

Transmission	
Gearbox	Automatic 8 speeds
Maximum performance modes	Economy mode, Power mode, Off-road mode
Traction	4x4

Chassis	
Direction	Hydraulic
Front suspension	Semi-elliptical leaf spring
Rear suspension	Semi-elliptical leaf spring
Brake system – type	100% air
Brake system – ABS	Yes
Traction control	Yes
Tire measurements – front	385/65 R22.5
Tire measurements – rear	295/80 R22.5
Frame	Ladder type

Weights and capacities	
Vacuum weight	40120 lb
Fuel tank	70 gl

Electrical system	
Electrical system voltage	24V
Battery	12V 180 Ah
Battery amount	2 – series
Alternator	24V-60 Amp

Dimensions	
WB (distance between axes) (in)	170
OL (total length) (in)	244
OH (total height) (in)	126
OW (total width) (in)	96.7

*Technical specifications are subject to modification and adjustment in accordance with customer requirements.