



# Product Guide

---

2025 V 1.0

# CONTENTS

Our Story . . . . .	2
X Series . . . . .	8
X Series Cylinders . . . . .	18
M Series Residential . . . . .	24
M Series Multiples . . . . .	40
M Series Commercial . . . . .	42
M Series Cylinder . . . . .	52
C Series . . . . .	58
C Series Cylinder . . . . .	62
H Series . . . . .	64
H Series Cylinder . . . . .	68
A Series . . . . .	72
S Series . . . . .	74
Downlight Comparison . . . . .	80





# Brilliance, Engineered

DMF is a modular, architectural lighting manufacturer of industry-leading luminaires known for flexibility, performance, and quality. With more than 150 patents, our team continues to innovate and invest heavily in R&D to provide you with performance lighting solutions that address common challenges to specification, installation, and maintenance.

Our product families are designed to give you recessed, surface mount, pendant, sconce, and signage solutions at varying price points and feature offerings that will meet a multitude of budgets and installation needs across all space types while maintaining aesthetic continuity.

Unique, patented embedded driver technology is built into our modules rather than above the ceiling and equipped with quick connects for plug-and-play capability expediting installation and overall serviceability.

**Construction projects are complex,  
but with DMF your LED lighting solutions  
should never be.**



## Designed in California

Founded by an electrical engineer in Southern California, it is only natural that innovation and sustainability are deeply ingrained in the ethos of our brand. Our solutions based modular designs are intended to get product in your hands quickly and address common issues and needs experienced by our customers in a meticulously designed and highly reliable fixture package.





Downlights  
Made

Functional.  
Flexible.  
Fast.

**DMF offers you a plug-and-play solution designed for the ever-changing needs of mixed-use spaces.**

X Series, M Series, C Series and H Series are our recessed fixture offerings designed with a variety of apertures and features as well as complementing cylinder solutions, the perfect solution for varying budgets and installation needs.

You can outfit a space with multiple DMF families, all with aesthetic continuity across the application.



Sunday Pilates, Las Vegas

Products: M Series Residential & S Series | Architect: Taylor Bosari Inc  
Lighting Design: The Cosine | Photography Credit: Katie Lynn Photography



X Series

Performance, small aperture collection of modular 2-inch downlights and 3-inch cylinders with field-changeable trims, modules and optics for exceptional versatility. Universal housing allow this series ultimate flexibility but addresses installation and serviceability issues common with small aperture fixtures like driver replacement and over-cutting.

<b>Product Type:</b>	Recessed, Cylinders
<b>Aperture:</b>	2"
<b>Price Range:</b>	\$\$\$
<b>Lumens:</b>	500 – 1500 lm
<b>Dimming/Controls:</b>	0-10V (1%), TRIAC/ELV (1%), DALI-2 (0.1%)
<b>Voltage:</b>	120V – 277V
<b>Housing Type:</b>	New Construction IC, Spray Foam IC, Remodel Non-IC, Chicago Plenum, Millwork
<b>Application:</b>	Hospitality, Retail, Commercial Office, Multi-family Residential, Single Family Residential



M Series

Our most versatile 4-inch product family, comprised of Residential IC rated options, Commercial high lumen offerings, Multiples, and complementing Cylinders. This product family ensures you have a solution for every lighting layer throughout your space types while maintaining consistency in light quality.

<b>Product Type:</b>	Recessed, Multiples, Cylinders, Surface
<b>Aperture:</b>	4"
<b>Price Range:</b>	\$\$
<b>Lumens:</b>	750 – 3500 lm
<b>Dimming/Controls:</b>	0-10V (1%), TRIAC/ELV (1%), DALI-2 (0.1%), Lutron Athena Wireless Node
<b>Voltage:</b>	120V – 277V
<b>Housing Type:</b>	New Construction IC, New Construction Non-IC, Remodel IC, Remodel Non-IC, Fire Rated IC, Spray Foam IC, Chicago Plenum, Millwork, Low Profile, Concrete, Double Housing, J Box, Super Shallow <i>(Coming Soon)</i>


**Application:** Commercial Office, Healthcare, Higher Education, Hospitality, Retail, Multi-family Residential, Single Family Residential



C Series

Designed to be a perfect blend of performance and affordability, the C Series prioritizes efficiency throughout every stage of a construction project. Streamlined options allow for a simplified specification and an error-free ordering process. Contractor-friendly features facilitate easy installation and effortless maintenance.


<b>Product Type:</b>	Recessed, Cylinders
<b>Aperture:</b>	4", 6"
<b>Price Range:</b>	\$
<b>Lumens:</b>	1000 – 2000 lm
<b>Dimming/Controls:</b>	0-10V (5%)
<b>Voltage:</b>	120V – 277V
<b>Housing Type:</b>	Non-IC
<b>Application:</b>	Commercial Office, Healthcare, Higher Education, Retail, Multifamily, Hospitality



H Series

DMF's high value offering delivers a quality, sustainable and modular design with reliable performance at an affordable price point. A field selectable lumen switch allows for quick changes on the fly while simplicity of the product offering lends itself to a straightforward ordering process.

<b>Product Type:</b>	Recessed, Cylinders, Surface
<b>Aperture:</b>	3", 4"
<b>Price Range:</b>	\$
<b>Lumens:</b>	350 – 950 lm
<b>Dimming/Controls:</b>	TRIAC/ELV (5%)
<b>Voltage:</b>	120V
<b>Housing Type:</b>	J Box, New Construction IC, Remodel IC
<b>Application:</b>	Single Family Residential, Multi-family Residential, Hospitality




2” Aperture Lighting System

The X Series represents the next evolution of the DMF line, bringing you the industry's best small-aperture downlights. The trim, optics, and aiming options provide the highest quality of light possible. The result is 2" aperture downlight or adjustable solutions offering uncompromised performance, finishes, and serviceability.

The Key to Innovation

A true breakthrough in the category, our patent-pending Precision Lock Collar eliminates the need to jump the housing collar and the over-cutting and drywall repair that jumping often creates with other small aperture fixtures. The Precision Lock Collar provides depth adjustment and secure fit, making flush-to-ceiling installation easy to achieve.



Easy Installation & Serviceability

A universal housing designed to adapt for downlight, adjustable, or wall wash solutions, the X Series is designed to allow for quick modification as space needs change. Additional features like a unique trap door that provides post-install access to the splice boxes and dimming drivers integrated within the module rather than housing ensure you always have full serviceability and access of the fixture below the ceiling plane.

Lighting Quality in a Small Package

Lumen output from 500 to 1500 lumens and comparable performance to competing 3" and 4" fixtures in ceilings up to 10 feet. Tool-less field changeable optics allow for ultimate flexibility in aiming a project.





X Series

PRODUCT SPECS



2" Downlight  
XMD

INSTALLATION

Ceiling Thickness

New Construction: 1/2" up to 1 1/4"  
Remodel: 5/8" up to 1 1/4"  
Extension Collar: 1 1/4" up to 3"

Ceiling Material

Drywall, Millwork

TRIMS

Shape

Round, Square

Style

Standard: Micro Flange, Flangeless  
Wall Wash, Hyperbolic, Pinhole, Decorative

Finish

White, Black, Bronze, Clear Diffuse,  
Custom Color

LIGHT OUTPUT & DISTRIBUTION

Module

Downlight

Lumens (Power)

500 lm (9.5 W), 750 lm (9.5W), 1000 lm (12.5W), 1250 lm (14.3W), 1500 lm (14.3W)

Color Quality

93 CRI, 2-step SDCM

Color Temperature

- 2700K 3000K 3500K
- 4000K Warm Dim (3000K–1800K)
- Tunable White (4000K–1800K)
- Tunable White (6500K–2700K)

Beam Spread

- Ultra Narrow Spot (10°) Narrow Spot (20°)
- Spot (30°) Flood (40°)
- Wide Flood (50°) Linear Spread (50°x30°)

POWER & CONTROLS

Input Voltage

120 / 277V

Dimming

0-10V (1%), TRIAC/ELV (1%), DALI-2 (0.1%)

RATINGS & CERTIFICATIONS


- IC (Insulation Contact) Rated (New Construction Only)
- ASTM E283 Certified Air Tight
- Chicago Plenum
- UL Listed for Wet Location
- RoHS Compliant
- NSF Listed (White and Black Finish Only)
- Turtle & Wildlife Friendly Configurations Available




NOTE: For complete ordering information & product details, please reference individual product spec sheets.

Round 2" Downlight


HOUSINGS



**X2NCR**  
New Construction




**X2CPR**  
Chicago Plenum




**X2RMR**<sup>1</sup>  
Remodel

TRIMS & ACCESSORIES




**X2TRDSWHMF**<sup>1</sup>  
Standard Micro Flange

○ ● ● ● ● ●




**X2TRDSWHFL**<sup>2</sup>  
Standard Flangeless

○ ● ● ● ● ●




**X2TRDWWHMF**<sup>1</sup>  
Wall Wash Micro Flange

○ ● ● ● ● ●




**X2TRDWWHFL**<sup>2</sup>  
Wall Wash Flangeless

○ ● ● ● ●




**X2TRDHHH**<sup>1</sup>  
Hyperbolic

○ ● ● ● ●




**X2TRDHHFL**<sup>2</sup>  
Hyperbolic Flangeless

○ ● ● ● ●




**X2TRDPWH**<sup>1</sup>  
Pinhole

○ ● ● ● ●




**X2TRDPWHFL**<sup>2</sup>  
Pinhole Flangeless

○ ● ● ● ●




**X2TRDSWHDO**<sup>1</sup>  
Decorative Open

○




**X2TRDSWHDH**<sup>1</sup>  
Decorative Hyperbolic


○




**X2KRMUD**  
Flangeless Mud Kit




**X2KRWOOD**  
Wood Kit



**X2KRTEMPLATE**  
Router Template



**X2CREXT**  
Extension Collar



**X2KRWOODXL**  
Wood Extension Collar

FINISH OPTIONS

- White (**WH**)
- Black (**BK**)
- Bronze (**BZ**)
- Clear Diffuse, White Flange (**CW**)
- Custom Color (**CC**)

Square 2" Downlight

HOUSINGS



**X2NCS**  
New Construction




**X2CPS**  
Chicago Plenum




**X2RMS**<sup>1</sup>  
Remodel

TRIMS & ACCESSORIES




**X2TSDSWHMF**<sup>1</sup>  
Standard Micro Flange

○ ● ● ● ● ●




**X2TSDSWHFL**<sup>2</sup>  
Standard Flangeless

○ ● ● ● ● ●




**X2TSDWWHMF**<sup>1</sup>  
Wall Wash Micro Flange

○ ● ● ● ● ●




**X2TSDWWHFL**<sup>2</sup>  
Wall Wash Flangeless

○ ● ● ● ●




**X2TSDPWH**<sup>1</sup>  
Pinhole

○ ● ● ● ●




**X2TSDPWHFL**<sup>2</sup>  
Pinhole Flangeless

○ ● ● ● ●




**X2TSDSWHDO**<sup>1</sup>  
Decorative Open

○




**X2TSDSWHDF**<sup>1</sup>  
Decorative Float


○



**X2KSMUD**  
Flangeless Mud Kit



**X2KSWOOD**<sup>3</sup>  
Wood Kit



**X2KSTEMPLATE**  
Router Template

<sup>1</sup> Precision Lock Collar included  
<sup>2</sup> Flangeless Mud or Wood Kit required



X Series

PRODUCT SPECS



2" Adjustable

XMA

INSTALLATION

Ceiling Thickness

New Construction: 1/2" up to 1 1/4"  
Remodel: 5/8" up to 1 1/4"

Ceiling Material

Drywall, Millwork

TRIMS

Shape

Round, Square

Style

Standard: Micro Flange, Flangeless  
Pinhole

Finish

White, Black, Bronze, Clear Diffuse,  
Custom Color

SPECIALTY LENS

● Hexcell Louver

LIGHT OUTPUT & DISTRIBUTION

Module

Adjustable

Adjustment

360° directional aim, 35° tilt

Lumens (Power)

500 lm (9.5 W), 750 lm (9.5W), 1000 lm (12.5W)

Color Quality

93 CRI, 2-step SDCM

Color Temperature

- 2700K ● 3000K ● 3500K
- 4000K ● Warm Dim (3000K–1800K)
- Tunable White (4000K–1800K)
- Tunable White (6500K–2700K)

Beam Spread

- ▲ Ultra Narrow Spot (10°) ▲ Narrow Spot (20°)
- ▲ Spot (30°) ▲ Flood (40°)
- ▲ Wide Flood (50°) ▲ Linear Spread (50°x30°)

POWER & CONTROLS

Input Voltage

120 / 277V

Dimming

0-10V (1%), TRIAC/ELV (1%), DALI-2 (0.1%)

RATINGS & CERTIFICATIONS

- IC (Insulation Contact) Rated  
(New Construction Only)
- ASTM E283 Certified Air Tight
- CP Chicago Plenum
- UL Listed for Damp Location
- RoHS Compliant



Declare.




NOTE: For complete ordering information & product details, please reference individual product spec sheets.

Round 2" Adjustable

HOUSINGS



X2NCR  
New Construction



X2CPR  
Chicago Plenum



X2RMR<sup>1</sup>  
Remodel

TRIMS & ACCESSORIES



X2TRASWHMF<sup>1</sup>  
Standard Micro Flange



X2TRASWHFL<sup>2</sup>  
Standard Flangeless



X2TRAPWH<sup>1</sup>  
Pinhole



X2TRAPWHFL<sup>2</sup>  
Pinhole Flangeless



X2KRMUD  
Flangeless Mud Kit



X2KRWOOD  
Wood Kit



X2KRTEMPLATE  
Router Template

FINISH OPTIONS

- White (WH)
- Black (BK)
- Bronze (BZ)
- Clear Diffuse, White Flange (CW)
- Custom Color (CC)

<sup>1</sup> Precision Lock Collar included

<sup>2</sup> Flangeless Mud or Wood Kit required

Square 2" Adjustable

HOUSINGS



X2NCS  
New Construction



X2CPS  
Chicago Plenum



X2RMS<sup>1</sup>  
Remodel

TRIMS & ACCESSORIES




X2TSASWHMF<sup>1</sup>  
Standard Micro Flange



X2TSASWHFL<sup>2</sup>  
Standard Flangeless



X2TSAPWH<sup>1</sup>  
Pinhole



X2TSAPWHFL<sup>2</sup>  
Pinhole Flangeless



X2KSMUD  
Flangeless Mud Kit



X2KSWOOD  
Wood Kit



X2KSTEMPLATE  
Router Template

FINISH OPTIONS

- White (WH)
- Black (BK)
- Bronze (BZ)
- Clear Diffuse, White Flange (CW)
- Custom Color (CC)

<sup>1</sup> Precision Lock Collar included

<sup>2</sup> Flangeless Mud or Wood Kit required

<sup>3</sup> Not compatible with Remodel

# X Series Cylinder



## Small Aperture Cylinder

X Series Cylinders add pendant, surface mount, and wall mount solutions to your lighting toolkit. Field-changeable trims, decorative diffusers, snoot, and optics deliver uncompromised performance and serviceability with flexible distribution and aesthetics. X Series modules are consistent, so you can count on the same light quality, color, and output from each cylinder.

## Features

Options to fit almost any spec or application.



### Pendant Options

Cord or stem suspension options, and both are field-cuttable to exact requirements.



### ADA Compliant

The overall projection of the wall mount from the surface of the wall is less than 4.0" making it ADA compliant, when installed at the proper height.



### Uplight

Shadowless pendant uplight allows for direct and indirect lighting from a single cylinder.



### Decorative Trims

Three acrylic forms combine polished and frosted surfaces to produce an eye catching interplay of light.



### Wall Wash

Perfect for delivering consistent light across a wall surface.



### Decorative Shades *Coming Soon*

Offered in narrow, medium and wide, add a decorative element to your space.



### Wet Location Rated

Available moisture protection options are IP65 and UL Wet Listed, ideal when specifying product for outdoor use.



X Series Cylinder

PRODUCT SPECS



Pendant Mount  
XCP

CYLINDER

Mount

Cord, Stem

Size

Diameter: 3.5"  
Height: 6.5", 9"

Suspension Length

Standard: 24" or 48"  
Custom: Up to 156" (Cord) or 96" (Stem)

Canopy

Standard

Trims

Standard, Snoot, Wall Wash, Decorative

Shades *Coming Soon*

Narrow, Medium, Wide

Finish

White, Black, Brushed Aluminum,  
Bronze, Custom Color

LIGHT OUTPUT & DISTRIBUTION

Lumens (Power)

750 lm (9.5W), 1000 lm (12.5W),  
1250 lm (14.3W), 1500 lm (14.3W)

Color Quality

93 CRI, 2-step SDCM

Color Temperature

- 2700K 3000K 3500K
- 4000K Warm Dim (3000K–1800K)
- Tunable White (4000K–1800K)
- Tunable White (6500K–2700K)

Beam Spread

- Narrow Spot (20°) Spot (30°)
- Flood (40°) Wide Flood (50°)

Lighting Type

- Downlight Up and downlight Adjustable

POWER & CONTROLS

Input Voltage

120 / 277V

Dimming

0-10V (120/277V): 1%  
TRIAC/ELV (120V): 1%  
DALI-2 (120/277V): 0.1%

RATINGS & CERTIFICATIONS

- Wet Location / IP65 Rated Configurations Available
- NSF Listed *(White and Black Finish Only)*
- Turtle & Wildlife Friendly Configurations Available



NOTE: For complete ordering information & product details, please reference individual product spec sheets.




Surface Mount

XCS

CYLINDER
Mount
Surface
Size
Diameter: 3.5" Height: 6.5", 9"
Canopy
Standard, Flangeless
Trims
Standard, Snoot, Wall Wash, Decorative
Finish

White, Black, Brushed Aluminum,  
Bronze, Custom Color

LIGHT OUTPUT & DISTRIBUTION
Lumens (Power)
750 lm (9.5W), 1000 lm (12.5W), 1250 lm (14.3W), 1500 lm (14.3W)
Color Quality
93 CRI, 2-step SDCM
Color Temperature
<div><div></div>2700K</div> <div><div></div>3000K</div> <div><div></div>3500K</div> <div><div></div>4000K</div> <div><div></div>Warm Dim (3000K–1800K)</div> <div><div></div>Tunable White (4000K–1800K)</div> <div><div></div>Tunable White (6500K–2700K)</div>
Beam Spread
<div><div></div>Narrow Spot (20°)</div> <div><div></div>Spot (30°)</div> <div><div></div>Flood (40°)</div> <div><div></div>Wide Flood (50°)</div>
Lighting Type



POWER & CONTROLS
Input Voltage
120 / 277V
Dimming
0-10V (120/277V): 1% TRIAC/ELV (120V): 1% DALI-2 (120/277V): 0.1%
RATINGS & CERTIFICATIONS
<div><div></div>Wet Location / IP65 Rated Configurations Available</div> <div><div></div>NSF Listed <i>(White and Black Finish Only)</i></div> <div><div></div>Turtle &amp; Wildlife Friendly Configurations Available</div>





Wall Mount

XCW

CYLINDER
Mount
Wall
Size
Diameter: 3.5" Height: 6.5", 9"
Bracket
Standard (Wet), Slim (Damp)
Trims
Standard, Snoot, Wall Wash, Decorative
Finish


White, Black, Brushed Aluminum,  
Bronze, Custom Color

LIGHT OUTPUT & DISTRIBUTION
Lumens (Power)
750 lm (9.5W), 1000 lm (12.5W), 1250 lm (14.3W), 1500 lm (14.3W)
Color Quality
93 CRI, 2-step SDCM
Color Temperature
<div><div></div>2700K</div> <div><div></div>3000K</div> <div><div></div>3500K</div> <div><div></div>4000K</div> <div><div></div>Warm Dim (3000K–1800K)</div> <div><div></div>Tunable White (4000K–1800K)</div> <div><div></div>Tunable White (6500K–2700K)</div>
Beam Spread
<div><div></div>Narrow Spot (20°)</div> <div><div></div>Spot (30°)</div> <div><div></div>Flood (40°)</div> <div><div></div>Wide Flood (50°)</div>
Lighting Type




POWER & CONTROLS
Input Voltage
120 / 277V
Dimming
0-10V (120/277V): 1% TRIAC/ELV (120V): 1% DALI-2 (120/277V): 0.1%
RATINGS & CERTIFICATIONS
<div><div></div>Wet Location / IP65 Rated Configurations Available</div> <div><div></div>NSF Listed <i>(White and Black Finish Only)</i></div> <div><div></div>Turtle &amp; Wildlife Friendly Configurations Available</div>





Modular Downlighting System

DMF's upgraded modular downlighting system, is now more versatile than ever – fixed, adjustable or wall wash, round or square, 750 to 1500 lumens. Featuring DMF engineered embedded 0-10V, TRIAC/ELV and DALI-2 drivers for optimal performance and reliability, the M Series can keep up with the fast-paced and ever-changing nature of your projects and can be the solution you go to every day.



Flexible Housing

M Series 4" Round & Square Housings feature Standard, Fire-Rated, and Chicago Plenum, along with specialty options such as Low-Profile and Double Housing. The compact, 4" housing installs easily and precisely for optimal fixture placement in crowded plenum space, to accommodate ductwork, framing, and plumbing.



A Perfect Match

The materials, heft, and finish of our M Series trims set them apart. The precision-crafted aluminum trims meet the design aesthetic of any project – wall wash, pinhole, round, square, flangeless – all completely interchangeable and available in five standard finishes and a custom color option.



M Series Residential

PRODUCT SPECS



4" Downlight

DRD2M

INSTALLATION

Ceiling Thickness

New Construction: 1/2" up to 1 3/4"  
Remodel: 5/8" up to 1 1/4"  
Low Profile: 1/2" up to 1 1/4"  
Alt/EM: 1/2" up to 1 1/4"  
Extension Collar: 1 3/4" up to 3"  
Super Low Profile: 1/2" up to 1 1/2" *Coming Soon*

Ceiling Material

Drywall, Millwork, Concrete

TRIMS

Shape

Round, Square

Style

Standard, Flangeless, Wall Wash, Hyperbolic, Pinhole, Decorative, Marine Grade/IP66 *Coming Soon*

Finish

White, Black, Bronze, Clear Diffuse, Custom Color

LIGHT OUTPUT & DISTRIBUTION

Module

Downlight

Lumens (Power)

750 lm (9.5W), 1000 lm (12.5W), 1250 lm (14.3W), 1500 lm (14.3W)

Color Quality

93 CRI, 2-step SDCM

Color Temperature

- 2700K 3000K 3500K
- 4000K Warm Dim (3000K–1800K)
- Tunable White (4000K–1800K)
- Tunable White (6500K–2700K)

Beam Spread

- Narrow Spot (15°) Spot (25°)
- Flood (40°) Wide Flood (60°)
- General (90°+) Linear Spread (40°x20°)
- Soft Focus

POWER & CONTROLS

Input Voltage

120/277V

Dimming/Controls

0-10V (1%), TRIAC/ELV (1%), DALI-2 (0.1%), Lutron Athena Node *Coming Soon*

Emergency

Optional Emergency LED Driver for lighting up to 90 minutes in event of power failure

RATINGS & CERTIFICATIONS

- IC (Insulation Contact) Rated
- ASTM E283 Certified Air Tight
- Fire Rated *(For use in fire-rated assemblies up to a max of 2-hours)*
- STC/IIC Sound Rated
- Chicago Plenum
- RoHS Compliant
- UL Listed for Wet Location *(Flanged Trims Only)*
- NSF Listed *(White and Black Finish Only)*
- Turtle & Wildlife Friendly Configurations Available




Declare.




NOTE: For complete ordering information & product details, please reference individual product spec sheets.

Round 4" Downlight


HOUSINGS




**M4NCRS**  
New Construction  
Standard




**M4NCRF**  
New Construction  
Fire Rated




**M4CPRS**  
New Construction  
Chicago Plenum




**M4SFRS**  
New Construction  
Spray Foam Rated




**M4DHRS**  
Double Housing  
Standard




**M4LTRS**  
Low Profile  
Standard




**M4LTRF**  
Low Profile  
Fire Rated




**M4NSRS**  
Super Shallow  
Standard  
*Coming Soon*




**M4NCRS7OEM**  
Emergency  
Standard




**M4NCRF7OEM**  
Emergency  
Fire Rated



**M4RMRS**  
Remodel  
Standard




**M4RMRF**  
Remodel  
Fire Rated




**M4CC**  
Concrete  
Construction

Round 4" Downlight


TRIMS & ACCESSORIES




**M4TRSWH**  
Standard




**M4TRSWHFL\***  
Standard Flangeless




**M4TRLWH**  
Wall Wash/Sloped Ceiling




**M4TRLWHFL\***  
Wall Wash/Sloped Ceiling  
Flangeless




**M4TRHWH**  
Hyperbolic




**M4TRHWHFL\***  
Hyperbolic Flangeless




**M4TRPWH**  
Pinhole




**M4TRPWHFL\***  
Pinhole Flangeless




**M4TRSWHDOF**  
Decorative: Open,  
Frosted




**M4TRSWHDCF**  
Decorative: Closed,  
Frosted




**M4TRSWHDCC**  
Decorative: Closed,  
Clear, Frosted Side




**M4TRSWHDCCF**  
Decorative: Closed,  
Clear, Frosted Inside




**M4TRSWHEM**  
Emergency, Integrated  
Test Switch




**M4TRSWHDF**  
Non-Conductive  
Dead Front




**M4TRSWHIP**  
Marine Grade/IP66  
*Coming Soon*




**M4XRMUD**  
Flangeless Mudplate



**M4KRTEMPLATE**  
Router Template



**M4CREXT**  
Extension Collar



**M4KRRETRO6**  
Retrofit Kit - 6" to 4"  
Round Conversion


\*Flangeless Mudplate required for drywall ceiling installation;  
Router Template recommended for wood ceiling installation

FINISH OPTIONS

- White (WH)
- Black (BK)
- Bronze (BZ)
- Clear Diffuse, White Flange (CW)
- Custom Color (CC)

Square 4" Downlight


HOUSINGS




**M4NCSS**  
New Construction  
Standard




**M4NCSF**  
New Construction  
Fire Rated




**M4CPSS**  
New Construction  
Chicago Plenum




**M4SFSS**  
New Construction  
Spray Foam Rated




**M4LTSS**  
Low Profile  
Standard




**M4LTSF**  
Low Profile  
Fire Rated




**M4NSSS**  
Super Shallow  
Standard  
*Coming Soon*




**M4NCSS7OEM**  
Emergency  
Standard



**M4NCSF7OEM**  
Emergency  
Fire Rated




**M4RMSS**  
Remodel  
Standard




**M4RMSF**  
Remodel  
Fire Rated

Square 4" Downlight


TRIMS & ACCESSORIES




**M4TSSWH**  
Standard




**M4TSSWHFL\***  
Standard Flangeless




**M4TSQWH**  
Round on Square




**M4TSQWHFL\***  
Round on Square  
Flangeless




**M4TSSWWH**  
Wall Wash/Sloped Ceiling




**M4TSLWHFL\***  
Wall Wash/Sloped Ceiling  
Flangeless




**M4TSPWH**  
Pinhole




**M4TSPWHFL\***  
Pinhole Flangeless




**M4TSSWHDCF**  
Decorative: Closed,  
Frosted




**M4TSSWHDCCF**  
Decorative: Closed,  
Clear, Frosted Inside




**M4TSSWHEM**  
Emergency, Integrated  
Test Switch



**M4XSMUD**  
Flangeless Mudplate



**M4KSTEMPLATE**  
Router Template



**M4KSRETRO6**  
Retrofit Kit - 6" to 4"  
Square Conversion

\*Flangeless Mudplate required for drywall ceiling installation


FINISH OPTIONS

- White (WH)
- Black (BK)
- Bronze (BZ)
- Clear Diffuse, White Flange (CW)
- Custom Color (CC)

M Series Residential


Retrofit 4" Downlight

TRIMS




**DRD2TR4SWH**  
4" Smooth

☐ ☒




**DRD2TR4BWH**  
4" Baffle

☐




**DRD2TR5SWH**  
5" Smooth

☐ ☒




**DRD2TR5BWH**  
5" Baffle

☐



**DRD2TR6SWH**  
6" Smooth


☐ ☒




**DRD2TR6BWH**  
6" Baffle

☐


ADAPTERS




**DRD2X-QCM-ED**  
Edison Adapter



**DRD2X-QCM-M**  
Male IDEAL PowerPlug® Adapter



**DRD2X-QCM-GU**  
GU-24 Adapter




**DRD2X-QCM-HW\***  
Hardwire Adapter


*\*Included with M Series 4" Downlight module*

SurfaceFrame 4" Downlight

HOUSINGS & TRIMS



**F4NC**  
New Construction  
Fire Rated



**DRD2TRJSWH**  
Surface Mount

☐

FINISH OPTIONS

☐ White (**WH**)

☒ Black (**BK**)





M Series Residential

PRODUCT SPECS



4" Adjustable  
DRD4M

INSTALLATION

Ceiling Thickness

New Construction: 1/2" up to 1 3/4"  
Remodel: 5/8" up to 1 1/4"  
Low Profile: 1/2" up to 1 1/4"  
Alt/EM: 1/2" up to 1 1/4"  
Super Low Profile: 1/2" up to 1 1/2" *Coming Soon*

Ceiling Material

Drywall, Millwork, Concrete

TRIMS

Shape

Round, Square

Style

Standard, Hyperbolic, Pinhole, Flangeless

Finish

White, Black, Bronze, Clear Diffuse,  
Custom Color

SPECIALTY LENS

● Hexcell Louver

LIGHT OUTPUT & DISTRIBUTION

Module

Adjustable

Adjustment

360° directional aim, 45° tilt

Lumens (Power)

750 lm (9.5W), 1000 lm (12.5W)

Color Quality

93 CRI, 2-step SDCM

Color Temperature

- 2700K ● 3000K ● 3500K
- 4000K ● Warm Dim (3000K–1800K)
- Tunable White (4000K–1800K)
- Tunable White (6500K–2700K)

Beam Spread

- ▲ Narrow Spot (15°) ▲ Spot (25°)
- ▲ Flood (40°) ▲ Linear Spread (60° x 30°)
- ▲ Soft Focus

POWER & CONTROLS

Input Voltage

120 / 277V

Dimming/Controls

0-10V (1%), TRIAC/ELV (1%), DALI-2 (0.1%),  
Lutron Athena Node *Coming Soon*

Emergency

Optional Emergency LED Driver for lighting up  
to 90 minutes in event of power failure

RATINGS & CERTIFICATIONS

- IC (Insulation Contact) Rated
- ASTM E283 Certified Air Tight
- Fire Rated *(For use in fire-rated assemblies up to a max of 2-hours)*
- STC/IIC Sound Rated
- Chicago Plenum
- RoHS Compliant
- UL Listed for Damp Location




Declare.



NOTE: For complete ordering information & product details, please reference individual product spec sheets.

Round 4" Adjustable


HOUSINGS




**M4NCRS**  
New Construction  
Standard




**M4NCRF**  
New Construction  
Fire Rated




**M4CPRS**  
New Construction  
Chicago Plenum




**M4SFRS**  
New Construction  
Spray Foam Rated




**M4DHRS**  
Double  
Housing



**M4LTRS**  
Low Profile  
Standard



**M4LTRF**  
Low Profile  
Fire Rated




**M4NSRS**  
Super Shallow  
Standard  
*Coming Soon*



**M4NCRS7OEM**  
Emergency  
Standard




**M4NCRF7OEM**  
Emergency  
Fire Rated



**M4RMRS**  
Remodel  
Standard




**M4RMRF**  
Remodel  
Fire Rated




**M4CC**  
Concrete  
Construction

Round 4" Adjustable


TRIMS & ACCESSORIES




**M4TRSWH**  
Standard




**M4TRSWHFL\***  
Standard Flangeless




**M4TRHWH**  
Hyperbolic




**M4TRHWHFL\***  
Hyperbolic Flangeless




**M4TRPWH**  
Pinhole




**M4TRPWHFL\***  
Pinhole Flangeless




**M4TRSWHEM**  
Emergency



**M4XRMUD**  
Flangeless Mudplate




**M4KRTEMPLATE**  
Router Template




**M4KRRETRO6**  
Retrofit Kit - 6" to 4"  
Round Conversion

Retrofit 4" Adjustable


TRIMS




**DRD2TR4SWH**  
4" Smooth




**DRD2TR4BWH**  
4" Baffle




**DRD2TR5SWH**  
5" Smooth



**DRD2TR5BWH**  
5" Baffle




**DRD2TR6SWH**  
6" Smooth




**DRD2TR6BWH**  
6" Baffle


ADAPTERS




**DRD2X-QCM-ED**  
Edison Adapter



**DRD2X-QCM-M**  
Male IDEAL PowerPlug® Adapter



**DRD2X-QCM-GU**  
GU-24 Adapter



**DRD2X-QCM-HW\***  
Hardwire Adapter

\*Included with M Series 4" Adjustable module


FINISH OPTIONS

- White (WH)
- Black (BK)
- Bronze (BZ)
- Clear Diffuse, White Flange (CW)
- Custom Color (CC)


\*Flangeless Mudplate required for drywall ceiling installation; Router Template recommended for wood ceiling installation

Square 4" Adjustable


HOUSINGS




M4NCSS  
New Construction  
Standard



M4NCSF  
New Construction  
Fire Rated




M4CPSS  
New Construction  
Chicago Plenum




M4SFSS  
New Construction  
Spray Foam Rated




M4LTSS  
Low Profile  
Standard




M4LTSF  
Low Profile  
Fire Rated



M4NSSS  
Super Shallow  
Standard  
*Coming Soon*



M4NCSS7OEM  
Emergency  
Standard



M4NCSF7OEM  
Emergency  
Fire Rated




M4RMSS  
Remodel  
Standard



M4RMSF  
Remodel  
Fire Rated

Square 4" Adjustable

TRIMS & ACCESSORIES



M4TSQWH  
Round on Square



M4TSQWHFL\*  
Round on Square  
Flangeless



M4TSPWH  
Pinhole



M4TSPWHFL\*  
Pinhole Flangeless



M4XSMUD  
Flangeless Mudplate



M4KSTEMPLATE  
Router Template




M4KSRETRO6  
Retrofit Kit - 6" to 4"  
Square Conversion

\*Flangeless Mudplate required for drywall ceiling installation

FINISH OPTIONS

- White (WH)
- Black (BK)
- Bronze (BZ)
- Clear Diffuse, White Flange (CW)
- Custom Color (CC)

# M Series Multiples



- Rectangular Multiple options based around our 4" adjustable modules maintain clean lines in the ceiling while maximizing light output
- Multi-directional adjustment with 360 degree directional aim and 45 degree tilt give you the ability to precisely highlight focal points throughout the interior
- Diecast unibody trims integrate up to three lights into one fixture and provide industry leading flexibility in a seamless package
- Integrated driver options allow for individual module control and dimming options down to 0.1%

INSTALLATION
<b>Ceiling Thickness</b>
New Construction: 1/2" up to 1 3/4"
<b>Ceiling Material</b>
Drywall
TRIMS
<b>Shape</b>
Square (1-Head), Rectangular (2-Head, 3-Head)
<b>Style</b>
Standard, Flangeless
<b>Finish</b>
White, Black
SPECIALTY LENS
<div><div></div>Hexcell Louver</div>

LIGHT OUTPUT & DISTRIBUTION
<b>Module</b>
Adjustable
<b>Adjustment</b>
360° directional aim, 45° tilt
<b>Lumens (Power)</b>
Per Head: 750 lm (9.5W), 1000 lm (12.5W)
<b>Color Quality</b>
93 CRI, 2-step SDCM
<b>Color Temperature</b>
<div><div>2700K</div><div>3000K</div><div>3500K</div></div> <div><div>4000K</div><div>Warm Dim (3000K–1800K)</div></div> <div><div>Tunable White (4000K–1800K)</div><div>Tunable White (6500K–2700K)</div></div>
<b>Beam Spread</b>
<div><div><div>Narrow Spot (15°)</div><div>Spot (25°)</div></div><div><div>Flood (40°)</div><div>Linear Spread (60° x 30°)</div></div><div><div>Soft Focus</div></div></div>

POWER & CONTROLS
<b>Input Voltage</b>
120 / 277V
<b>Dimming</b>
0-10V (1%), TRIAC/ELV (1%), DALI-2 (0.1%)
RATINGS & CERTIFICATIONS
<div><div></div>IC (Insulation Contact) Rated</div> <div><div></div>ASTM E283 Certified Air Tight</div> <div><div></div>RoHS Compliant</div> <div><div></div>UL Listed for Damp Location</div>



NOTE: For complete ordering information & product details, please reference individual product spec sheets.

# M Series Multiples

COMPATIBLE HOUSINGS & TRIMS

## Multiples 4" Adjustable

### HOUSINGS



### TRIMS & ACCESSORIES

<div><div></div><div><b>M4T1SWH</b> 1-Head Standard</div><div><div></div><div></div></div></div>	<div><div></div><div><b>M4T1SWHFL<sup>1</sup></b> 1-Head Flangeless</div><div><div></div><div></div></div></div>	<div><div></div><div><b>M4XSMUD</b> 1-Head Flangeless Mudplate</div></div>
<div><div></div><div><b>M4T2SWH</b> 2-Head Standard</div><div><div></div><div></div></div></div>	<div><div></div><div><b>M4T2SWHFL<sup>1</sup></b> 2-Head Flangeless</div><div><div></div><div></div></div></div>	<div><div></div><div><b>M4XS2MUD</b> 2-Head Flangeless Mudplate</div></div>
<div><div></div><div><b>M4T3SWH</b> 3-Head Standard</div><div><div></div><div></div></div></div>	<div><div></div><div><b>M4T3SWHFL<sup>1</sup></b> 3-Head Flangeless</div><div><div></div><div></div></div></div>	<div><div></div><div><b>M4XS3MUD</b> 3-Head Flangeless Mudplate</div></div>

### FINISH OPTIONS

- White (**WH**)
- Black (**BK**)

<sup>1</sup> Flangeless Mudplate required

NOTE: For complete ordering information & product details, please reference individual product spec sheets.



All-New Higher-Lumen  
Downlighting System

The M Series Commercial family is a versatile lighting solution with built in universal features which radically simplify configuration in the field. Appropriate for most installation applications, this family delivers 750 lm to 3500 lm of 93 CRI lighting with our unique, patented, integrated and detachable driver solutions that dim to 1% and below and allow for full serviceability beneath the ceiling plane. Within the same housing, you can change modules, optics, and trims and seamlessly integrate with building lighting control systems for flexible dimming options.

Downlight Module

The M Series Commercial downlight module comes in a wide range of lumen packages, appropriate for varying ceiling heights and it's wet listing makes it suitable for both interior and exterior applications. Field changeable, folded optics and reflectors from 15 to 90 degrees help mitigate glare and a wide variety of interchangeable trims offer endless lighting customization allowing you to construct a comforting, design-forward, space that can evolve as space needs change.



Adjustable Module

The M Series Commercial adjustable module aims lighting exactly where you want it with 360° of rotation and up to 40° of tilt. Reflectors from 15 to 40 degrees minimize any distortion to the beam spread and are always field changeable. Never requiring the need for tools after the housing is installed, this module allows you to adapt quickly to design changes in a space.



M Series Commercial

PRODUCT SPECS

4" Downlight  
MD



750–1500 lm



2000 lm



2500–3500 lm  
High Lumen

INSTALLATION

Ceiling Thickness

New Construction: 1/2" up to 2"  
Remodel: 1/2" up to 1 1/4"

Ceiling Material

Drywall, Millwork

TRIMS

Shape

Round, Square

Style

Standard, Hyperbolic, Pinhole, Wall Wash,  
Flangeless, Decorative, Vandal Proof/IP66,  
Marine Grade/IP66 *Coming Soon*

Finish

White, Black, Bronze, Clear Diffuse,  
Custom Color

LIGHT OUTPUT & DISTRIBUTION

Module

Downlight

Lumens (Power)

**Standard Lumen:** 750 lm (9.5W), 1000 lm (12.5W ), 1250 lm (14.3W), 1500 lm (14.3W), 2000 lm (24.5W)

**High Lumen:** 2500 lm (27.5W), 3000 lm (34.0W), 3500 lm (40.5W)

Color Quality

93 CRI, 2-step SDCM

Color Temperature

- 2700K 3000K 3500K
- 4000K Warm Dim (3000K–1800K)
- Tunable White (6500K–2700K)

Beam Spread

- Narrow Spot (15°) Spot (25°)
- Flood (40°) Wide Flood (60°)
- General (90°+)

POWER & CONTROLS

Input Voltage

120 / 277V

Dimming

0-10V (1%), Lutron Athena Node (1%),  
DALI-2 (0.1%)

Emergency

Optional Emergency LED Driver for lighting up  
to 90 minutes in event of power failure

RATINGS & CERTIFICATIONS

- RoHS Compliant
- Wet Location / IP66 Rated  
Configurations Available (*Flanged trims only*)
- NSF Listed (*White and Black Finish Only*)




Declare.




NOTE: For complete ordering information & product details, please reference individual product spec sheets.

Round 4" Downlight


HOUSINGS




**M4NCRN**  
New Construction  
Standard



**M4NCRN07OAWN**  
New Construction  
Alternate/Athena




















**M4NCRN07OEM**  
New Construction  
Emergency



**M4RMRN**  
Remodel


TRIMS & ACCESSORIES

 <p><b>M4TRSWH</b> Standard</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TRSWHFL*</b> Standard Flangeless</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TRLWH</b> Wall Wash/Sloped Ceiling</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TRLWHFL*</b> Wall Wash/Sloped Ceiling Flangeless</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TRHWH</b> Hyperbolic</p> <p>○ ● ● ● ● ●</p>
 <p><b>M4TRHWHFL*</b> Hyperbolic Flangeless</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TRPWH</b> Pinhole</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TRPWHFL*</b> Pinhole Flangeless</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TRSWHDOF</b> Decorative: Open, Frosted</p> <p>○</p>	 <p><b>M4TRSWHDCF</b> Decorative: Closed, Frosted</p> <p>○</p>
 <p><b>M4TRSWHDCCF</b> Decorative: Closed, Clear, Frosted Side</p> <p>○</p>	 <p><b>M4TRSWHDCCF</b> Decorative: Closed, Clear, Frosted Inside</p> <p>○</p>	 <p><b>M4TRSWHEM</b> Emergency, Integrated Test Switch</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TRSWHVP</b> Vandal Proof/IP66 Anti-Microbial Finish</p> <p>○</p>	 <p><b>M4TRSWHIP</b> Marine Grade/IP66 <i>Coming Soon</i></p> <p>○ ●</p>
 <p><b>M4XRMUD</b> Flangeless Mudplate</p>	 <p><b>M4CREXT</b> Extension Collar</p>	<p>FINISH OPTIONS</p> <p>○ White (WH)</p> <p>● Black (BK)</p> <p>● Bronze (BZ)</p> <p>● Clear Diffuse, White Flange (CW)</p> <p>● Custom Color (CC)</p>		


\*Flangeless Mudplate required for drywall ceiling installation

Square 4" Downlight


HOUSINGS




**M4NCSN**  
New Construction  
Standard



**M4NCSN07OAWN**  
New Construction  
Alternate/Athena















**M4NCSN07OEM**  
New Construction  
Emergency



**M4RMSN**  
Remodel

TRIMS & ACCESSORIES

 <p><b>M4TSDWH</b> Standard</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TSDWHFL*</b> Standard Flangeless</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TSLWH</b> Wall Wash/Sloped Ceiling</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TSLWHFL*</b> Wall Wash/Sloped Ceiling Flangeless</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TSPWH</b> Pinhole</p> <p>○ ● ● ● ● ●</p>
 <p><b>M4TSPWHFL*</b> Pinhole Flangeless</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TSSWHDCF</b> Decorative: Closed, Frosted</p> <p>○</p>	 <p><b>M4TSSWHDCCF</b> Decorative: Closed, Clear, Frosted Inside</p> <p>○</p>	 <p><b>M4TSDWHEM</b> Emergency, Integrated Test Switch</p> <p>○ ● ● ● ● ●</p>	 <p><b>M4TSDWHVP</b> Vandal Proof/IP66 Anti-Microbial Finish</p> <p>○</p>
 <p><b>M4XSMUD</b> Flangeless Mudplate</p>	 <p><b>M4CSEXT</b> Extension Collar</p>	<p>FINISH OPTIONS</p> <p>○ White (WH)</p> <p>● Black (BK)</p> <p>● Clear Diffuse, White Flange (CW)</p> <p>● Custom Color (CC)</p>		

\*Flangeless Mudplate required for drywall ceiling installation



M Series Commercial

PRODUCT SPECS



4" Adjustable

MA

INSTALLATION

Ceiling Thickness

New Construction: 1/2" up to 2"  
Remodel: 1/2" up to 1 1/4"

Ceiling Material

Drywall, Millwork

TRIMS

Shape

Round, Square

Style

Standard, Pinhole, Flangeless, Hyperbolic

Finish

White, Black, Bronze, Clear Diffuse,  
Custom Color

SPECIALTY LENS

● Hexcell Louver

LIGHT OUTPUT & DISTRIBUTION

Module

Adjustable

Adjustment

360° directional aim, 40° tilt

Lumens (Power)

**Standard Lumen:** 750 lm (9.5W), 1000 lm (12.5W ), 1250 lm (14.3W), 1500 lm (14.3W), 2000 lm (24.5W)

**High Lumen:** 2500 lm (27.5W), 3000 lm (34.0W), 3500 lm (40.5W)

Color Quality

93 CRI, 2-step SDCM

Color Temperature

● 2700K ● 3000K ● 3500K  
● 4000K ● Warm Dim (3000K–1800K)  
● Tunable White (6500K–2700K)

Beam Spread

▲ Narrow Spot (15°)    ▲ Spot (25°)  
▲ Flood (40°)

POWER & CONTROLS

Input Voltage

120 / 277V

Dimming

0-10V (1%), Lutron Athena Node (1%),  
DALI-2 (0.1%)

Emergency

Optional Emergency LED Driver for lighting up to 90 minutes in event of power failure

RATINGS & CERTIFICATIONS


✓ RoHS Compliant  
● UL Listed for Damp Location




NOTE: For complete ordering information & product details, please reference individual product spec sheets.

Round 4" Adjustable


HOUSINGS




**M4NCRN**  
New Construction  
Standard



**M4NCRN07OAWN**  
New Construction  
Alternate/Athena




**M4NCRN07OEM**  
New Construction  
Emergency




**M4RMRN**  
Remodel

TRIMS & ACCESSORIES




**M4TRSWH**  
Standard

○ ● ● ● ● ●




**M4TRSWHFL\***  
Standard Flangeless

○ ● ● ● ● ●




**M4TRHWH**  
Hyperbolic

○ ● ● ●




**M4TRHWHFL\***  
Hyperbolic Flangeless

○ ● ● ●




**M4TRPWH**  
Pinhole

○ ● ● ●



**M4TRPWHFL\***  
Pinhole Flangeless

○ ● ● ●



**M4XRMUD**  
Flangeless Mudplate


FINISH OPTIONS

- White (**WH**)
- Black (**BK**)
- Bronze (**BZ**)
- Clear Diffuse, White Flange (**CW**)
- Custom Color (**CC**)


\*Flangeless Mudplate required for drywall ceiling installation

Square 4" Adjustable


HOUSINGS




**M4NCSN**  
New Construction  
Standard



**M4NCSN07OAWN**  
New Construction  
Alternate/Athena



**M4NCSN07OEM**  
New Construction  
Emergency



**M4RMSN**  
Remodel

TRIMS & ACCESSORIES



**M4TSAWH**  
Standard

○ ● ● ● ● ●



**M4TSAWHFL\***  
Standard Flangeless

○ ● ● ● ● ●



**M4TSPWH**  
Pinhole

○ ● ● ●



**M4TSPWHFL\***  
Pinhole Flangeless

○ ● ● ●



**M4XSMUD**  
Flangeless Mudplate

FINISH OPTIONS

- White (**WH**)
- Black (**BK**)
- Clear Diffuse, White Flange (**CW**)
- Custom Color (**CC**)

\*Flangeless Mudplate required for drywall ceiling installation

# M Series Cylinder




## Modern Cylinder System

By combining a suite of customizable features with our high performance LED modules, the M Series Cylinder (previously named DCC Cylinder) provides brilliant illumination and a beautiful design versatile enough for whatever your project needs.

## Options & Accessories

Shades, trims, specialty options, even the light engine can all be swapped out in the field, giving you control during and after the installation.




### Uplight

Enables light output at elevated levels, while providing glare-free ambiance and the ability to highlight architectural elements.



### Snoot

Channels light source and decreases visual cutoff angle to increase focus and mitigate glare.



### Wall Wash *Coming Soon*

Designed to direct light evenly across a wall, minimizing shadows and highlighting architectural features



### Decorative Trims

Finely crafted acrylic subtly fills your space with beautiful ambient light.



### Junction Box Cover

Completes the cylinder's look in open ceiling applications.



### Decorative Shades *Coming Soon*

Offered in narrow, medium and wide, add a decorative element to your space.




### Wet Location Rated

Available moisture protection options are IP65 and UL Wet Listed, ideal when specifying product for outdoor use.



M Series Cylinder



Pendant Mount

CYLINDER

Mount

Cord, Stem

Size

Diameter: 4"  
Height: Small (4"), Medium (8"), Large (12")

Suspension Length

Standard: 24" or 48"  
Custom: Up to 156" (Cord) or 96" (Stem)

Canopy

Standard

Trims

Standard, Snoot, Decorative,  
Wall Wash *Coming Soon*

Shades *Coming Soon*

Narrow, Medium, Wide

Finish

White, Black, Brushed Aluminum,  
Bronze, Custom Color

SPECIALTY LENS

● Hexcell Louver

LIGHT OUTPUT & DISTRIBUTION

Lumens (Power)

750 lm (9.5W), 1000 lm (12.5W), 1250 lm (14.3W), 1500 lm (14.3W), 2000 lm (24.5W), 2500 lm (27.5W), 3000 lm (34W)

Color Quality

93 CRI, 2-step SDCM

Color Temperature

- 2700K ● 3000K ● 3500K
- 4000K ● Warm Dim (3000K–1800K)
- Tunable White (4000K–1800K)
- Tunable White (6500K–2700K)

Beam Spread

- ▲ Narrow Spot (15°) ▲ Spot (25°)
- ▲ Flood (40°) ▲ Wide Flood (60°)
- ▲ General (90°+)

Lighting Type

- Downlight
- Up and downlight
- Adjustable

POWER & CONTROLS

Input Voltage

120 / 277V

Dimming

0-10V (120/277V): 1%  
TRIAC/ELV (120V): 1%  
DALI-2 (120/277V): 0.1%


Emergency

Optional Remote Inverter or Emergency LED Driver for lighting up to 90 minutes in event of power failure

RATINGS & CERTIFICATIONS

- Wet Location / IP65 Rated Configurations Available
- NSF Listed *(White and Black Finish Only)*
- Turtle & Wildlife Friendly Configurations Available

















Surface Mount



CYLINDER
Mount
Surface
Size
Diameter: 4" Height: Small (4"), Medium (8"), Large (12")
Canopy
Standard
Trims
Standard, Snoot, Decorative, Wall Wash <i>Coming Soon</i>
Finish
White, Black, Brushed Aluminum, Bronze, Custom Color

SPECIALTY LENS
 Hexcell Louver

LIGHT OUTPUT & DISTRIBUTION
Lumens (Power)
750 lm (9.5W), 1000 lm (12.5W), 1250 lm (14.3W), 1500 lm (14.3W), 2000 lm (24.5W), 2500 lm (27.5W), 3000 lm (34W)
Color Quality
93 CRI, 2-step SDCM
Color Temperature
 2700K  3000K  3500K
 4000K  Warm Dim (3000K–1800K)
 Tunable White (4000K–1800K)
 Tunable White (6500K–2700K)

Beam Spread
 Narrow Spot (15°)  Spot (25°)
 Flood (40°)  Wide Flood (60°)
 General (90°+)








Lighting Type
 Downlight  Adjustable











Wall Mount


CYLINDER
Mount
Wall
Size
Diameter: 4" Height: Medium (8"), Large (12")
Bracket
Standard (Damp Location), Wet Location
Trims
Standard, Snoot, Decorative, Wall Wash <i>Coming Soon</i>
Finish
White, Black, Brushed Aluminum, Bronze, Custom Color

SPECIALTY LENS
 Hexcell Louver

LIGHT OUTPUT & DISTRIBUTION
Lumens (Power)
750 lm (9.5W), 1000 lm (12.5W), 1250 lm (14.3W), 1500 lm (14.3W), 2000 lm (24.5W), 2500 lm (27.5W), 3000 lm (34W)
Color Quality
93 CRI, 2-step SDCM
Color Temperature
 2700K  3000K  3500K
 4000K  Warm Dim (3000K–1800K)
 Tunable White (4000K–1800K)
 Tunable White (6500K–2700K)

Beam Spread
 Narrow Spot (15°)  Spot (25°)
 Flood (40°)  Wide Flood (60°)
 General (90°+)

Lighting Type
 Downlight  Up and downlight  Adjustable






Commercial Downlighting

Designed to be a perfect blend of performance and affordability, the C Series prioritizes efficiency throughout every stage of a construction project. Streamlined options allow for a simplified specification and error-free ordering process. Contractor-friendly installation features facilitate easy installation and effortless maintenance. Most importantly, the vast majority of C Series products will ship within 72 hours or less, keeping your projects moving forward with speed and reliability.

Flexible Output

Our C Series module includes an adjustable integrated brightness switch option, allowing you to customize the light level to suit your needs. Installation and maintenance are a breeze with our embedded 0-10V drivers, all accessible from below the ceiling.



Universal Installation

Designed with contractor needs in mind, our C Series fixtures include pre-installed universal bar hangers and butterfly brackets, allowing for easy and adaptable installation across different ceiling types. This flexibility reduces installation errors and minimizes costly delays.



Downlight  
CM

INSTALLATION
<b>Ceiling Thickness</b>
New Construction: 5/8" up to 1 1/4"
<b>Ceiling Material</b>
Drywall, ACT
TRIMS
<b>Aperture</b>
4", 6"
<b>Shape</b>
Round
<b>Style</b>
Standard
<b>Finish</b>
White, Semi-Specular with White Flange

LIGHT OUTPUT & DISTRIBUTION
<b>Module</b>
Downlight
<b>Lumens (Power)</b>
Integrated Brightness Switch 1000 lm (13.6W), 1500 lm (17W), 2000 (24.5W)
<b>Color Quality</b>
80+ CRI, 3-step SDCM
<b>Color Temperature</b>
<div><div></div> 3000K</div> <div><div></div> 3500K</div> <div><div></div> 4000K</div>
<b>Beam Spread</b>
<div><div></div> General (90°+)</div>


POWER & CONTROLS
<b>Input Voltage</b>
120/227 V
<b>Dimming</b>
0-10V (5%)
RATINGS & CERTIFICATIONS
<div><div></div> RoHS Compliant</div> <div><div></div> UL Listed for Wet Location <i>(Under Covered Ceilings)</i></div> <div><div></div> NSF Listed <i>(White Finish Only)</i></div> <div><div></div> Non-Conductive Dead Front</div>



4" HOUSINGS



C4NCRN  
4" New Construction




C4NCRNOEMS  
4" New Construction  
Emergency

6" HOUSINGS



C6NCRN  
6" New Construction



C6NCRNOEMS  
6" New Construction  
Emergency

FINISH OPTIONS

- White (**WH**)
- Semi-Specular, White Flange (**SP**)

4" TRIMS



C4TRSWH  
4" Standard



6" TRIMS



C6TRSWH  
6" Standard



# C Series Cylinder



## Commercial Cylinder

C Series Cylinders offer an advantageous option for projects that can't accommodate a fully recessed downlight, such as those with open ceilings or retrofits. DMF's paramount modularity allows for our cylinder families to share the same performance and quality that you find in our downlights, and the C Series is no exception. C Series Cylinders is available as an 8" pendant with Stem and Cord mounting options, and by utilizing the same exact module you can get a consistent quality of light across your entire project when using mixed fixture types.

# C Series Cylinder



Pendant Mount  
CCP

### CYLINDER

#### Mount

Pendant

#### Size

Diameter: 4"  
Height: 8"

#### Suspension Length

Cord: 8' Field-Cuttable  
Stem: 2' or 4'

#### Canopy

Standard

#### Trims

Standard

#### Finish

White, Black

### LIGHT OUTPUT & DISTRIBUTION

#### Lumens (Power)

1000 lm (13.6W), 1500 lm (17W),  
2000 (24.5W)

#### Color Quality

80+ CRI, 3-step SDCM

#### Color Temperature

3000K 3500K 4000K

#### Beam Spread

General (90°+)

#### Lighting Type



Downlight

### POWER & CONTROLS

#### Input Voltage

120/227 V

#### Dimming

0-10V (5%)

#### Emergency *Coming Soon*

Optional Remote Inverter or Emergency LED Driver for lighting up to 90 minutes in event of power failure


### RATINGS & CERTIFICATIONS

NSF Listed



Declare.





DMF Performance  
at an Attainable Price

The H Series is a modular downlight system that brings the best of our award-winning design to your projects. With several trim options and high-quality finishes, the H Series is simple to select, order, install, and maintain for any new construction or remodel project.

Flexible Housing Applications

Strong, lightweight, and stackable to consolidated shelf space, the H Series Housings are designed to simplify installations. The housings feature bar hangers, wood joist mounting screws, or pop out springs to ensure a quick and accurate installation. Made from sustainable materials, the housings are recyclable and 100% manufactured in North America.



Brilliant Illumination

The Integrated Natural Warm Dim seamlessly transitions from comfortable white to warm light without losing color accuracy and the Brightness Switch enables field selectable light output, including ambient, standard, and higher ceiling environments.

H Series



Downlight

HM3C, HM2C

INSTALLATION
<b>Ceiling Thickness</b>
New Construction: 5/8" Remodel: 5/8" up to 1 1/4"
<b>Ceiling Material</b>
Drywall
TRIMS
<b>Aperture</b>
3", 4"
<b>Shape</b>
Round, Square
<b>Style</b>
Standard
<b>Finish</b>
White, Black








LIGHT OUTPUT & DISTRIBUTION
<b>Module</b>
Downlight
<b>Lumens (Power)</b>
Integrated Brightness Switch 350 lm (5W), 750 lm (9W), 950lm (12W)
<b>Color Quality</b>
90+ CRI, 3-step SDCM
<b>Color Temperature</b>
<div><div></div> Natural Warm Dim (3000K-2200K)</div> <div><div></div> Natural Warm Dim (2700K-1800K)</div>
<b>Beam Spread</b>
<div><div></div> General (90°+)</div>

POWER & CONTROLS
<b>Input Voltage</b>
120 V
<b>Dimming</b>
TRIAC/ELV (5%)
RATINGS & CERTIFICATIONS
<div><div></div> IC (Insulation Contact) Rated</div> <div><div></div> ASTM E283 Certified Air Tight</div> <div><div></div> Fire Rated <i>(For use in fire-rated assemblies up to a max of 2-hours)</i></div> <div><div></div> RoHS Compliant</div> <div><div></div> UL Listed for Wet Location</div> <div><div></div> NSF Listed</div>








H Series

COMPATIBLE HOUSINGS & TRIMS

4" HOUSINGS & TRIMS

			
<b>H4BH</b> 4" New Construction with Bar Hangers	<b>H4RM</b> 4" Remodel	<b>F4NC*</b> New Construction Fire Rated	
			
<b>H4TRSWH</b> 4" Round	<b>H4TRFWH</b> 4" Flush	<b>H4TSSWH</b> 4" Square	<b>H4TRAWH</b> 4" Adjustable
<input type="radio"/> <input checked="" type="radio"/>	<input type="radio"/> <input checked="" type="radio"/>	<input type="radio"/> <input checked="" type="radio"/>	<input type="radio"/> <input checked="" type="radio"/>

3" HOUSINGS & TRIMS

			
<b>H3BH</b> 3" New Construction with Bar Hangers	<b>H3RM</b> 3" Remodel	<b>H3FR*</b> New Construction Fire Rated	
			
<b>H3TRSWH</b> 3" Round	<b>H3TRFWH</b> 3" Flush	<b>H3TSSWH</b> 3" Square	<b>H3TRAWH</b> 3" Adjustable
<input type="radio"/> <input checked="" type="radio"/>	<input type="radio"/> <input checked="" type="radio"/>	<input type="radio"/> <input checked="" type="radio"/>	<input type="radio"/> <input checked="" type="radio"/>

ADAPTERS
<b>DRD2X-QCM-ED</b> Edison Adapter

FINISH OPTIONS
<div><div></div> White (<b>WH</b>)</div> <div><div></div> Black (<b>BK</b>)</div>

\*For usage with  
Flush trim only





Pendant Mount

The stylish pendant introduces a decorative element to your lighting environment. A built-in brightness control allows you to adjust the lumen output appropriate for the task at hand, while decorative trim allows for a soft diffusion of the light.



Wall Mount

Our ADA compliant Wall Mount pendant effortlessly installs while exposing no visible hardware - maintaining a minimalist appearance. An integrated lumen switch on the module allows you to adjust output based on the desired mounting height. IP65 rated, this cylinder is perfect for both exterior and interior applications including balconies and corridors.

H Series Cylinder



Pendant Mount

HCP3D

CYLINDER
Mount
Pendant
Size
Diameter: 3.5" Total Length: 8.5"
Suspension Length
48" Cord with 8" Partial Stem
Trims
5.5" Decorative Trim Only
Finish
White

LIGHT OUTPUT & DISTRIBUTION
Lumens (Power)
Integrated Brightness Switch 350 lm (5W), 750 lm (9W), 950lm (12W)
Color Quality
90+ CRI, 3-step SDCM
Color Temperature
<div><div></div> Natural Warm Dim (3000K–2200K)</div> <div><div></div> Natural Warm Dim (2700K-1800K)</div>
Beam Spread
<div><div></div> General (90°+)</div>
Lighting Type
<div><div></div></div> <div>Downlight</div>

POWER & CONTROLS
Input Voltage
120 V
Dimming
TRIAC/ELV (5%)
Mounting
Most 3O, 4O, 4R Junction boxes
RATINGS & CERTIFICATIONS
<div><div></div> UL Listed for Damp Location</div> <div><div></div> NSF Listed</div>



H Series Cylinder



Wall Mount

HCW6B

CYLINDER
Mount
Wall
Size
Diameter: 3.5" Height: 6.5"
Trims
Standard Trim Only
Finish
White, Black

LIGHT OUTPUT & DISTRIBUTION
Lumens (Power)
Integrated Brightness Switch 350 lm (5W), 750 lm (9W), 950lm (12W)
Color Quality
90+ CRI, 3-step SDCM
Color Temperature
<div><div></div> Natural Warm Dim (3000K–1800K)</div> <div><div></div> Natural Warm Dim (2700K-1800K)</div>
Beam Spread
<div><div></div> General (90°+)</div>
Lighting Type
<div><div></div></div> <div>Downlight</div>

POWER & CONTROLS
Input Voltage
120 V
Dimming
TRIAC/ELV (5%)
Mounting
2-Gang Switch Boxes Most 3O, 4O, 4R & 4S Junction boxes
RATINGS & CERTIFICATIONS
<div><div></div> Wet Location / IP65 Rated</div> <div><div></div> NSF Listed</div>



# A Series






## Illuminated Signage

The A Series illuminated signage is a completely customizable, solution perfect for multifamily and hospitality applications simultaneously fulfilling a need for signage and corridor illumination. This ADA compliant fixture mounts 0.5" from the surface onto most standard 4" round or octagonal junction boxes and our integrated driver allows for ease of installation and serviceability.

# A Series




Illuminated Room Sign  
ADR

PHYSICAL	LIGHT OUTPUT & DISTRIBUTION	POWER & CONTROLS
<b>Mount</b>	<b>Lighting Type</b>	<b>Input Voltage</b>
Wall	Indirect	120 / 277V
<b>Size</b>	<b>Lumens (Power)</b>	<b>Mounting</b>
4.5"x 7.25" x 0.5" (Rectangle)	~50 Lumens (3W) Delivered	4O Junction Box, 4R Junction Box
<b>Plate Finish</b>	<b>Color Quality</b>	<b>RATINGS &amp; CERTIFICATIONS</b>
Black, Custom Color	90+ CRI, 3-step SDCM	 Suitable for Damp Locations
	<b>Color Temperature</b>	
	 2700K  3000K	



Surface Mount Downlighting

The S Series redefines what’s possible for a surface mount downlight. Packed with technical breakthroughs, the ultra-thin fixture matches the elegance of a recessed downlight but offers the versatility to fit into more applications, even those with limited plenum space.




8" Round Surface Mount

This minimalist downlight takes everything that makes the original 4" exceptional, and expands on it. This area light can fill a room with inviting, accurate illumination. In addition, its SurfaceFrame compatibility simplifies installation and makes it interoperable with the rest of the S Series family.



4" Surface Mount

The S Series minimal design is available in multiple form factors, with the 4" Round and Square matching the appearance of recessed lights. These models also include optional Integrated EM Test Switch and Non-Conductive Dead Front variants.



18" Linear Surface Mount

This linear area light delivers 1500 lumens of 90+ CRI light in a unique form factor. Like our other downlights in this series, the linear version features a proprietary integrated driver and small footprint, making it a great choice for new construction or retrofit applications.





4" Round & Square  
DRD5S4

PHYSICAL	LIGHT OUTPUT & DISTRIBUTION	POWER & CONTROLS
<b>Application</b>	<b>Lumens (Power)</b>	<b>Input Voltage</b>
New Construction, Retrofit	750 lm (9.0W), 1000 lm (12.0W)	0-10V: 120/277V TRIAC/ELV: 120V
<b>Mount</b>	<b>Color Quality</b>	<b>Dimming</b>
Surface	90+ CRI, < 3-step SDCM	0-10V (1%) TRIAC/ELV (5%)
<b>Shape</b>	<b>Color Temperature</b>	<b>Emergency</b>
4" Round, 4" Square	<div><div>2700K</div><div>3000K</div><div>3500K</div></div>	Optional Remote Inverter or Emergency LED Driver for lighting up to 90 minutes in event of power failure
<b>Finish</b>		
White		
<b>RATINGS &amp; CERTIFICATIONS</b>		
<div><div></div>Wet Location</div>		



8" Round  
DRD5S8R

PHYSICAL	LIGHT OUTPUT & DISTRIBUTION	POWER & CONTROLS
<b>Application</b>	<b>Lumens (Power)</b>	<b>Input Voltage</b>
New Construction, Retrofit	1500 lm (17W)	0-10V: 120/277V TRIAC/ELV: 120V
<b>Mount</b>	<b>Color Quality</b>	<b>Dimming</b>
Surface	90+ CRI, < 3-step SDCM	0-10V (1%) TRIAC/ELV (5%)
<b>Shape</b>	<b>Color Temperature</b>	<b>Emergency</b>
8" Round	<div><div>2700K</div><div>3000K</div><div>3500K</div></div>	Optional Remote Inverter or Emergency LED Driver for lighting up to 90 minutes in event of power failure
<b>Finish</b>		
White		
<b>RATINGS &amp; CERTIFICATIONS</b>		
<div><div></div>Wet Location</div>		





18" Linear  
DRD5S4L

PHYSICAL

Application

New Construction, Retrofit

Mount

Surface

Shape

18" x 4" Rectangle

Finish

White

LIGHT OUTPUT & DISTRIBUTION

Lumens (Power)

1500 lm (17W)

Color Quality

90+ CRI, < 3-step SDCM

Color Temperature

2700K 3000K 3500K

POWER & CONTROLS

Input Voltage

0-10V: 120/277V  
TRIAC/ELV: 120V

Dimming

0-10V (1%)  
TRIAC/ELV (5%)

Emergency

Optional Remote Inverter or Emergency LED Driver for lighting up to 90 minutes in event of power failure


RATINGS & CERTIFICATIONS

Wet Location




SurfaceFrame

HOUSINGS



F4NC  
New Construction  
Fire Rated



F4NC7OEM  
Emergency  
Fire Rated

Retrofit

COMPATIBLE JUNCTION BOXES



JUNCTION BOX	MIN. DEPTH	MIN. VOLUME	THROUGH-WIRE RATING
4O Octagonal (metallic)	2 1⁄8"	21.5 in³	6 (three in, three out) #12 AWG
3O Round (non-metallic)	2 3⁄4"	18 in³	6 (three in, three out) #12 AWG
4O Round (non-metallic)	2 3⁄16"	20 in³	6 (three in, three out) #12 AWG

	X Series 2" Downlight	X Series 2" Adjustable	M Series Residential 4" Downlight	M Series Residential 4" Adjustable	M Series Commercial 4" Downlight	M Series Commercial 4" Adjustable	C Series 4" & 6" Downlight	H Series 3" & 4" Downlight
APPLICATION	New Construction, Remodel	New Construction, Remodel	New Construction, Remodel, Retrofit	New Construction, Remodel, Retrofit	New Construction, Remodel	New Construction, Remodel	New Construction	New Construction, Remodel, Retrofit
HOUSING	X Series, X Series Cylinder	X Series	M Series; SurfaceFrame; M Series Cylinder; 4", 5", 6" Retrofit, Multiples	M Series; M Series Cylinder; 4", 5", 6" Retrofit	M Series Commercial, M Series Cylinder	M Series Commercial	C Series, C Series Cylinder	H Series, H Series Cylinder
ADJUSTMENT	–	360° directional aim, 35° tilt	–	360° directional aim, 45° tilt	–	360° directional aim, 40° tilt	–	–
DELIVERED LUMENS	500 lm (9.5W), 750 lm (9.5W), 1000 lm (12.5W), 1250 lm (14.3W), 1500 lm (14.3W)	500 lm (9.5W), 750 lm (9.5W), 1000 lm (12.5W)	750 lm (9.5W), 1000 lm (12.5W), 1250 lm (14.3W), 1500 lm (14.3W)	750 lm (9.5W), 1000 lm (12.5W)	750 lm (9.5W), 1000 lm (12.5W), 1250lm (14.3W), 1500lm (14.3W), 2000 lm (24.5W), 2500 lm (27.5W), 3000 lm (34.0W), 3500 lm (40.5W)	750 lm (9.5W), 1000 lm (12.5W), 1250 lm (14.3W), 1500 lm (14.3W), 2000 lm (24.5W), 2500 lm (27.5W), 3000 lm (34.0W), 3500 lm (40.5W)	1000 lm (13.6W), 1500 lm (17W), 2000 lm (24.5W), Selectable Option 1000lm/1500lm/2000lm	Up to 950 lm - Selectable 350 lm (5W), 750 lm (9W), 950 lm (12W)
EFFICACY	53 lm/W, 79 lm/W, 80 lm/W, 87 lm/W, 105 lm/W	53 lm/W, 79 lm/W, 80 lm/W	79 lm/W, 80 lm/W, 87 lm/W, 105 lm/W	79 lm/W, 80 lm/W	79 lm/W, 80 lm/W, 87 lm/W, 105 lm/W, 82 lm/W 91 lm/W, 88 lm/W, 86 lm/W	79 lm/W, 80 lm/W, 87 lm/W, 105 lm/W, 82 lm/W, 86 lm/W	74 lm/W, 88 lm/W, 82 lm/W	70 lm/W, 83 lm/W, 79 lm/W
COLOR QUALITY	93 CRI, 2-step SDCM	93 CRI, 2-step SDCM	93 CRI, 2-step SDCM	93 CRI, 2-step SDCM	93 CRI, 2-step SDCM	93 CRI, 2-step SDCM	80+ CRI, 3-step SDCM	90+ CRI, 3-step SDCM
CCT	2700K, 3000K, 3500K, 4000K	2700K, 3000K, 3500K, 4000K	2700K, 3000K, 3500K, 4000K	2700K, 3000K, 3500K, 4000K	2700K, 3000K, 3500K, 4000K	2700K, 3000K, 3500K, 4000K	3000K, 3500K, 4000K	2700K, 3000K
WARM DIM	3000K–1800K	3000K–1800K	3000K–1800K	3000K–1800K	3000K–1800K	3000K–1800K	-	2700K-1800K, 3000K–2200K
TUNABLE WHITE	4000K-1800K, 6500K–2700K	4000K-1800K, 6500K–2700K	4000K-1800K, 6500K–2700K	4000K-1800K, 6500K–2700K	6500K–2700K	6500K–2700K	-	–
BEAM SPREAD	Ultra Narrow Spot (10°), Narrow Spot (20°), Spot (30°), Flood (40°), Wide Flood (50°)	Ultra Narrow Spot (10°), Narrow Spot (20°), Spot (30°), Flood (40°), Wide Flood (50°)	Narrow Spot (15°), Spot (25°), Flood (40°), Wide Flood (60°), General Ambient (90°+)	Narrow Spot (15°), Spot (25°), Flood (40°)	Narrow Spot (15°), Spot (25°), Flood (40°), Wide Flood (60°), General Ambient (90°+)	Narrow Spot (15°), Spot (25°), Flood (40°)	General Ambient (90°+)	General Ambient (90°+)
OPTIONS	Linear Spread, Hexell Louver	Linear Spread, Hexell Louver	Linear Spread, Soft Focus	Linear Spread, Soft Focus, Hexell Louver, Black or White Surround	–	Hexell Louver	–	–
INPUT VOLTAGE	120/277V	120/277V	120/277V	120/277V	120/277V	120V/277V	120V/277V	120V
DIMMING	0-10V 1%, TRIAC/ELV 1%, DALI-2 0.1%	0-10V 1%, TRIAC/ELV 1%, DALI-2 0.1%	0-10V 1%, TRIAC/ELV 1%, Lutron Athena Node 1%, DALI-2 0.1%	0-10V 1%, TRIAC/ELV 1%, Lutron Athena Node 1%, DALI-2 0.1%	0-10V 1%, Lutron Athena Node 1%, DALI-2 0.1%	0-10V 1%, Lutron Athena Node 1%, DALI-2 0.1%	0-10V 5%	TRIAC/ELV 5%
EMERGENCY	–	–	Optional Emergency Driver	Optional Emergency Driver	Optional Emergency Driver	Optional Emergency Driver	Optional Emergency Driver	–
STANDARDS	JA8 Title 24, UL Certified US-CA, ENERGY STAR®, Declare, NSF/ANSI 2, DarkSky Approved	JA8 Title 24, UL Certified US-CA, ENERGY STAR®, Declare	JA8 Title 24, UL Certified US-CA, ENERGY STAR®, Declare, NSF/ANSI 2, DarkSky Approved	JA8 Title 24, UL Certified US-CA, ENERGY STAR®, Declare	UL Certified US-CA, ENERGY STAR®, Declare, NSF/ANSI 2, DarkSky Approved	UL Certified US-CA, ENERGY STAR®, Declare	UL Certified US-CA, ENERGY STAR®, Declare, NSF/ANSI 2	JA8 Title 24, UL Certified US-CA, ENERGY STAR®, Declare, NSF/ANSI 2
RATINGS	Wet Location	Damp Location	Wet Location	Damp Location	Wet Location	Damp Location	Wet Location	Wet Location
LIFETIME (L70)	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs
WARRANTY	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years



For Patent information, please visit:  
[dmflighting.com/ourpatents/](https://dmflighting.com/ourpatents/)

**DMF Lighting**  
1118 East 223rd Street  
Carson, CA 90745  
323.934.7779  
[info@dmflighting.com](mailto:info@dmflighting.com)  
[dmflighting.com](https://dmflighting.com)

