

Product data sheet

Specifications



APC NetShelter 9U Wallmount Rack Enclosure Cabinet Single Hinged Server Depth

AR109SH6

Overview

| | |
|--------------|--|
| Presentation | Ideal for retail, healthcare, and educational facilities, this wall mount rack offers an efficient solution for deploying server and networking equipment for edge computing applications. This rack enclosure is wall mountable, ideal for areas with limited floor space, and is designed specifically for servers and network switches, and patch panels. The cabinet's door is reversible and is compatible with APC's Netbotx security upgrade to provide remote access, video surveillance, and environmental monitoring (sold separately). Optional 120V fan tray can be top or bottom mounted (sold separately) Both the top and bottom feature knockouts of 1/2U mounting space for accessories. And several APC Smart-UPS models low-profile provide easy UPS integration and mounting 9U Wall mount cabinet, the mounting depth range of 2.87 to 20.8 inches, 200lb weight capacity, 19" rack width, ships fully assembled, ventilated with accessory integration options, 5 year APC warranty. |
| Lead Time | Usually in Stock |

Main

| | |
|---------------------------|----------------|
| Product Or Component Type | Rack enclosure |
| Number Of Rack Unit | 9U |

Physical

| | |
|----------------------------|------------------------------|
| Height | 19.09 in (48.5 cm) |
| Width | 23.62 in (60 cm) |
| Depth | 23.62 in (60 cm) |
| Net Weight | 36.80 lb(US) (16.69 kg) |
| Color | Black |
| Mounting Support | Wall |
| Mounting Preference | No preference |
| Mounting Mode | Not rack-mountable |
| Maximum Mounting Depth | 20.80 in (52.83 cm) |
| Minimum Mounting Depth | 2.87 in (7.29 cm) |
| Rack Width | 19" |
| Permanent Permissible Load | 200 lb(US) (90.72 kg) static |

Conformance

| | |
|-----------|---------------------|
| Standards | UL 2416 EIA-310E |
|-----------|---------------------|

Ordering and shipping details

| | |
|----------|------------------------|
| Category | 80230-IG SEBA TO SEUSA |
|----------|------------------------|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------------------|--------------|
| Discount Schedule | BMS1 |
| Gtin | 731304402718 |
| Returnability | No |
| Country Of Origin | PH |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 22.24 in (56.5 cm) |
| Package 1 Width | 26.97 in (68.5 cm) |
| Package 1 Length | 26.97 in (68.5 cm) |
| Package 1 Weight | 45.19 lb(US) (20.5 kg) |

Contractual warranty

| | |
|----------|--------------------------|
| Warranty | 5 year repair or replace |
|----------|--------------------------|

Sustainability




Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back RoHS/REACH

Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Reach Free Of Svhc

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)