



- Manufactured in the UK
- Unbeatable Recovery & Efficiency
- 316 Stainless Steel Frame & Pipework
- Fully Programmable
- 2 Line LED Display
- Customisable Colour and Logo
- Stainless Solenoids and Control Valves
- Stainless Membrane Housing and End Caps
- Stainless Inlet Filter
- Fully Factory Tested and Set Up to your spec
- IP65 Rated
- Compatible with One Flow Technology

Complete Water Treatment Ltd

20 Lawnbrook Drive, Newtownards, BT23 8XD

T : 02891 828 505 07955 054 897

MODEL COMPACT		150
Permeate flow rate	l/h	150
Min. salt rejection	%	95
Recovery	%	Up to 80
Operating pressure	bar	10.0
Membrane element / number		4021/1
Voltage	V/Hz	230/50
Motor power	kW	0.4
Pre-fusing	A	13
Feedwater connection	BSP	¾"
Permeate connection	BSP	½"
Concentrate connection	BSP	½"
Conductivity range	µS/cm	1 – 99
Min. / max. feed water pressure	bar	3 / 6
Min. / max. feed water temp	°C	5 / 35
Max. ambient temperature	°C	40
pH		3 – 11
Height	mm	370
Width	mm	800
Depth	mm	370
Weight approx	ca. kg	31
Code no		