









## Trimless Downlight Optima 01

-  IP20
-  Class II
-  AC220-240V
-  Recessed Ceiling
-  Highly recyclable
-  50k Hours Lifetime
-  Dimming Optional: DALI, Phase Cut & 1/0-10V
-  Adjustable Tilt

### Product Features:

- ✓ Sleek and Space-Saving structure
- ✓ Seamlessly integrates into ceilings for a clean, architectural aesthetic.
- ✓ Advanced Heat-Sink Technology for Superior Heat Mangement
- ✓ Extended Durability with a Lifespan of Up to 50,000 Hours L80

### Product Specifications:









- ✓ Housing: Die-Cast Aluminum Body
- ✓ Diffuser: PMMA lens.
- ✓ Outstanding Temp: 0~45°C
- ✓ Delivered Lumen Output: 100lm/W
- ✓ Color Render Index > 90




### Model Selection

Model No.	Wattage	Lumen	Cut Out (mm)	Dimension (mm)DxH
DLO1-008	8 W	800 lm	55	82x89
DLO1-012	12 W	1200 lm	75	100x90
DLO1-016	16 W	1600 lm	75	100x102
DLO1-020	20 W	2000 lm	95	131x113

### Selectable Options

CCT	Beam Angle	Housing
 3000K	 15°	 Grey
 4000K	 24°	
 6500K	 38°	
	 55°	



### Reflector Color

