








COB Downlight Optima 04

-  IP20
-  Class II
-  AC220-240V
-  Recessed Ceiling
-  Highly recyclable
-  50k Hours Lifetime
-  Dimming Optional: DALI, Phase Cut & 1/0-10V



Product Features:

- ✓ Sleek and Space-Saving structure
- ✓ Multiple Configurations for Optics and Decorative Trims.
- ✓ Advanced Heat-Sink Technology for Superior Heat Management
- ✓ Extended Durability with a Lifespan of Up to 50,000 Hours L80









Product Specifications:

- ✓ Housing: Die-Cast Aluminum Body
- ✓ Diffuser: PMMA lens.
- ✓ Outstanding Temp: 0~45°C
- ✓ Delivered Lumen Output: 100lm/W
- ✓ Color Render Index > 90

Model Selection

Model No.	Wattage	Lumen	Cut Out (mm)	Dimension (mm)DxH
DLO4-006	6 W	600 lm	32	40x55
DLO4-008	8 W	800 lm	52	60x77
DLO4-012	12 W	1200 lm	72	81x102
DLO4-016	16 W	1600 lm	72	81x102

Selectable Options

CCT	Beam Angle	Trim
 3000K	 15°	<input type="checkbox"/> White
 4000K	 24°	<input type="checkbox"/> Black
<input type="checkbox"/> 6500K	 38°	
	 55°	

