

Trimless Downlight Optima 05

- IP65
- Class II
- AC220-240V
- Recessed Ceiling
- Highly recyclable
- 50k Hours Lifetime
- Dimming Optional: DALI, Phase Cut & 1/0-10V
- Adjustable Tilt

Product Features:

- ✓ Sleek and Space-Saving structure
- ✓ Seamlessly integrates into ceilings for a clean, architectural aesthetic.
- ✓ Suitable for wet areas and high-moisture environments, ensuring durability and water resistance.
- ✓ Advanced Heat-Sink Technology for Superior Heat Management
- ✓ Extended Durability with a Lifespan of Up to 50,000 Hours L80

Product Specifications:


- ✓ Housing: Die-Cast Aluminum Body
- ✓ Diffuser: PMMA lens.
- ✓ Outstanding Temp: 0~45°C
- ✓ Delivered Lumen Output: 100lm/W
- ✓ Color Render Index > 90

Model Selection

Model No.	Wattage	Lumen	Cut Out (mm)	Dimension (mm)DxH
DLO5-008	8 W	800 lm	55	74x88
DLO5-012	12 W	1200 lm	75	100x98
DLO5-016	16 W	1600 lm	75	100x124
DLO5-020	20 W	2000 lm	95	114x116

Selectable Options

CCT	Beam Angle	Housing
<input checked="" type="checkbox"/> 3000K <input type="checkbox"/> 4000K <input type="checkbox"/> 6500K	<input checked="" type="checkbox"/> 15° <input type="checkbox"/> 24° <input type="checkbox"/> 38° <input type="checkbox"/> 55°	<input checked="" type="checkbox"/> Grey



Reflector Color

