








## LED Backlit Panel BP21 (IP54)

-  IP54
-  Class II
-  AC220-240V
-  Recessed Ceiling
-  Highly Recyclable
-  50K hours lifetime
-  Dimming Optional



### Product Features:

- ✓ Sleek and Space-Saving Structure
- ✓ Highly energy-efficient compare to traditional lighting source
- ✓ Uniform illumination, no dark-spot
- ✓ Tunable wattage option
- ✓ Extended Durability with a Lifespan of Up to 50,000 Hours L80

### Product Specifications:


- ✓ Housing: Powder coated CRCA steel sheet + Aluminum Frame
- ✓ Diffuser: PC Opal
- ✓ Ambient Temperature: 0~45°C
- ✓ Delivered Lumen output: 100lm/W
- ✓ Color Render Index > 80
- ✓ Power Factor > 0.9
- ✓ Mesh Guard Protection - Optional



### Model Selection

Model No.	Wattage	Lumen	Dimension (mm) AxBxC
BP21-040	36-40 W	Up to 4000 lm	595x595x26
BP21-040B	36-40 W	Up to 4000 lm	1195x295x26
BP21-060C	40-50-60 W	Up to 6000 lm	1195x595x26

### Selectable Options

CCT	Beam Angle	Body Color
<input checked="" type="checkbox"/> 3000K <input type="checkbox"/> 4000K <input type="checkbox"/> 6500K	 160°	<input checked="" type="checkbox"/> White

