








## Clean Room Light CRP1

-  IP65
-  Dust Proof
-  Class I
-  AC220-240V
-  Recessed Luminaire
-  Accessible from Down
-  50K hours lifetime



### Product Features:

- ✓ Lights are sealed with special materials, diffuser is made from Polycarbonate, PMMA prismatic, seamless, it can be dustproof and IP65.
- ✓ High thickness quality steel, rust and oil removed, under anti-rust treated and rust proof for 8-10 years under normal application, with white powder coating.
- ✓ Moderate illumination intensity, uniform illumination, reduce visual errors, can prevent visual fatigue, and effectively prevent the effect of irradiation and poor visual blind
- ✓ Equipped with SMD2835 or T5 LED Tubes as option.
- ✓ The lamp panel can be equipped with emergency devices and batteries to ensure continuous operation for 3 hours in the case of power failure.
- ✓ Light is suitable for front open for maintenance.
- ✓ Easy recessed mounted installation to all kinds of ceiling
- ✓ Extended Durability with a Lifespan of Up to 50,000 hours L80.
- ✓ Application: Hospital, Laboratory, Pharmaceutical factory, Food factory, Decontamination chamber.



### Product Specifications:


- ✓ Housing: High Thickness quality steel with Powder Coating
- ✓ Diffuser: PMMA and Tempered Glass
- ✓ Outstanding Working Temp: 0-50 C
- ✓ Delivered Lumen output: 105lm/W
- ✓ Color Render Index > 80

### Model Selection

Model No.	Wattage	Lumen	Dimension (mm)WxLxD
CRP1-036	36 W	3780 lm	595x595x100
CRP1-040	40 W	4200 lm	595x595x100
CRP1-050	50 W	5250 lm	1195x295x100
CRP1-060	60 W	6400 lm	1195x295x100

\* 40W is available also in 1195x295x100mm Size

### Selectable Options

CCT	Beam Angle
<input checked="" type="checkbox"/> 3000K	 160°
<input type="checkbox"/> 4000K	
<input type="checkbox"/> 6500K	

