





COB Downlight Gemini 03



IP20



Class II



AC220-240V



Recessed Ceiling



Highly recyclable



50k Hours Lifetime



Dimming Optional: DALI, Phase Cut & 1/0-10V



Adjustable Tilt



- Sleek and Space-Saving structure
- Multiple Configurations for Optics and Decorative Trims.

 Advanced Heat-Sink Technology for Superior Heat Mangament
- Extended Durability with a Lifespan of Up to 50,000 Hours L80

Product Specifications:

- Housing: Die-Cast Aluminum Body
- Diffuser: PMMA lens.
- Outstanding Temp: 0~45°C
- Delivered Lumen Output: 100lm/W
- Color Render Index > 90
- Power Factor > 0.9

Model Selection

Beam Angle 38°

Model No.	Wattage	Lumen	Cut Out (mm)	Dimension (mm)DxH
DLG3-007	7 W	700 lm	55	65x75
DLG3-012	12 W	1200 lm	75	85x90
DLG3-020	20 W	2000 lm	95	105x105
DLG3-025	25 W	2500 lm	95	105x105

Selectable Options

ССТ	Beam Angle	Housing	Trim
3000K	8°	Grey	White
4000K	15°		Black
	24°		
6500K	38°		
	55°		



Reflector Color

















