







LED Downlight DLS10



IP54



Class II



AC220-240V



Recessed Ceiling



Highly recyclable



50k Hours Lifetime



Product Features:

- Delivers exceptional luminous efficiency, providing bright illumination while minimizing energy consumption, resulting in cost savings and environmental benefits.
- Constructed with a durable die-cast aluminum body, ensuring robustness and longevity in outdoor and industrial environments, with excellent heat dissipation properties for optimal performance.
- Incorporates Surface Mounted Device (SMD) technology, Known for its reliability, efficiency, and consistent light output, ensuring uniform illumination and reduced maintenance requirements.
- With its high efficacy and advanced LED technology, the downlight offers exceptional energy efficiency, helping to lower electricity bills and reduce carbon footprint.
- Extended Durability with a Lifespan of Up to 50,000 Hours L80.





Product Specifications:

- Housing: Die-Cast Aluminum
- Diffuser: Opal Polycarbonate
- Outstanding Temp: 0~45°C
- Delivered Lumen Output: 140lm/W
- Color Render Index > 80
- Power Factor > 0.9

Model Selection

Model No.	Wattage	Lumen	Cut Out (mm)	Dimension (mm)DxH
DLST-010	10 W	1400 lm	120	145x70
DLST-015	15 W	2100 lm	165	190x70
DLST-020	20 W	2800 lm	165	190x70
DLST-030	30 W	4200 lm	190	215x70





Selectable Options

ССТ	Beam Angle	Housing	
3000K	110°	White	
4000K			
6500K			

