








LED Downlight DLSQ

-  IP54
-  Class II
-  AC220-240V
-  Recessed Ceiling
-  Highly recyclable
-  50k Hours Lifetime
-  Dimming Optional: DALI, Phase Cut & 1/0-10V



Product Features:

- ✓ Delivers exceptional luminous efficiency, providing bright illumination while minimizing energy consumption, resulting in cost savings and environmental benefits.
- ✓ Constructed with a durable die-cast aluminum body, ensuring robustness and longevity in outdoor and industrial environments, with excellent heat dissipation properties for optimal performance.
- ✓ Incorporates Surface Mounted Device (SMD) technology, Known for its reliability, efficiency, and consistent light output, ensuring uniform illumination and reduced maintenance requirements.
- ✓ Features an IP54 rating, providing complete protection against dust and water, making it suitable for both dry and wet area installations.
- ✓ With its high efficacy and advanced LED technology, the downlight offers exceptional energy efficiency, helping to lower electricity bills and reduce carbon footprint.
- ✓ Extended Durability with a Lifespan of Up to 50,000 Hours L80.








Product Specifications:

- ✓ Housing: Die-Cast Aluminum
- ✓ Diffuser: Opal Polycarbonate
- ✓ Outstanding Temp: 0~45°C
- ✓ Delivered Lumen Output: 110lm/W
- ✓ Color Render Index > 80
- ✓ Power Factor > 0.9

Model Selection

Model No.	Wattage	Lumen	Cut Out (mm)	Dimension (mm)WxDxH
DLSQ-012	12 W	1320 lm	100x100	110x110x49
DLSQ-018	18 W	1980 lm	135x135	145x145x53
DLSQ-024	24 W	2640 lm	156x156	170x170x54

Selectable Options

CCT	Beam Angle	Housing
 3000K	 100°	 White
 4000K		
 6500K		

