







## Explosion Proof Light EP06

-  IP66
-  Class I
-  AC220-240 50/60 HZ
-  Highly recyclable
-  50K hours lifetime
-  II 2D Ex tb IIIC T6 Db IP66  
II 2G Ex de IIC T4 Gd

### Product Features:

- ✓ Die-Cast Aluminum Housing and PC Lens diffuser
- ✓ Heavy-duty and high impact resistance
- ✓ Suitable for Zone 1, Zone 2 (Gas) and Zone 21 and 22 (Dust)
- ✓ Multiple installation options: Ceiling, Wall and Pole Mounted
- ✓ Optional Emergency LED Driver

### Product Specifications:

- ✓ Housing: Die-Cast Aluminum
- ✓ Diffuser: PC Lens
- ✓ Ambient Temperature: -40~60°C
- ✓ Delivered Lumen output: 130lm/W
- ✓ Power Factor: > 0.9
- ✓ Color Render Index > 80
- ✓ Weight: 6.7 Kg / 8.3 Kg



### Model Selection

Model No.	Wattage	Lumen	Dimension (mm)LxWxH
EP06	80 W	10400 lm	403x275x65
	100 W	13000 lm	403x275x65
	120 W	15600 lm	403x275x65
	150 W	19500 lm	505x275x65
	200 W	26000 lm	505x275x65

### Selectable Options

CCT	Beam Angle	Body Color
<input checked="" type="checkbox"/> 3000K	Type III	<input checked="" type="checkbox"/> Yellow
<input checked="" type="checkbox"/> 4000K		
<input type="checkbox"/> 6500K		

