







# Explosion Proof Light EP04


-  IP66
-  Class I
-  AC220-240 50/60 HZ
-  Highly recyclable
-  50K hours lifetime
-  II 2D Ex tb IIIC T6 Db IP66  
II 2G Ex de IIC T4 Gd

## Product Features:

- ✓ Die-Cast Aluminum Housing and Tempered Glass diffuser
- ✓ Heavy-duty and high impact resistance
- ✓ Suitable for Zone 1, Zone 2 (Gas) and Zone 21 and 22 (Dust)
- ✓ Multiple Installation options: Ceiling, Wall and Pole Mounted
- ✓ Optional Emergency LED Driver
- ✓ Optional Aluminum Reflector

## Product Specifications:






- ✓ Housing: Die-Cast Aluminum
- ✓ Diffuser: Tempered Glass
- ✓ Ambient Temperature: -40~60°C
- ✓ Delivered Lumen output: 130lm/W
- ✓ Power Factor: > 0.9
- ✓ Color Render Index > 80




## Model Selection

Model No.	Wattage	Lumen	Dimension (mm)AxBxCxD
EP04	80 W	10400 lm	275x280x190x230
	100 W	13000lm	320x330x205x280
	120 W	15600lm	320x330x205x280
	150 W	19500 lm	370x380x215x275
	160 W	20800 lm	370x380x215x275
	200 W	26000 lm	370x380x215x275

## Selectable Options


CCT	Beam Angle	Body Color
 4000K	 120°	 Yellow
 5000K		
 6500K		




# Explosion Proof Light EP04

## Installation Type


No.1: Ceiling Mounting



No.2: Wall Mounting



No.3: Pole Mounting



## Net Weight

Wattage	Weight (Kg)
80 W	5
100 / 120 W	7.8
150 / 200 W	9.5