







## Explosion Proof Light EP02

-  IP66
-  Class I
-  AC220-240 50/60 HZ
-  Highly recyclable
-  50K hours lifetime
-  II 2D Ex tb IIIC T6 Db IP66  
II 2G Ex de IIC T5 Gb



### Product Features:

- ✓ ABS Housing and Polycarbonate diffuser with outstanding impact resistance Anti-Corrosion Material
- ✓ Suitable for Zone 1, Zone 2 (Gas) and Zone 21 and 22 (Dust)
- ✓ Multiple installation options: Rod, Chain, Surface/Flange/Mounted
- ✓ High Efficiency LED Chips


### Product Specifications:



- ✓ Housing: ABS
- ✓ Diffuser: PC
- ✓ Ambient Temperature: -40~60°C
- ✓ Delivered Lumen output: 120lm/W
- ✓ Power Factor: > 0.9
- ✓ Color Render Index > 80 Weight:
- ✓ 5.2 Kg

### Model Selection

Model No.	Wattage	Lumen	Dimension (mm)LxWxH
EP02	20 W	Up to 2400 lm	690x200x50
	30 W	Up to 3600 lm	690x200x50
	40 W	Up to 4800 lm	690x200x50
	50 W	Up to 6000 lm	1340x200x70
	60 W	Up to 7200 lm	1340x200x70
	75 W	Up to 9000 lm	1340x200x70

### Selectable Options

CCT	Beam Angle	Body Color
<input type="checkbox"/> 3000K	 110°	<input type="checkbox"/> White
<input type="checkbox"/> 4000K		
<input type="checkbox"/> 6500K		



## Explosion Proof Light EP02

### Installation Type

