

## Flood Light FL02

- IP66
- Class I
- AC220-240V
- Surface Mounted Luminaire
- Highly recyclable
- 50K hours lifetime
- DALI Dimming



### Product Features:

- ✓ Crafted with high-quality materials to withstand outdoor elements, ensuring longevity and resilience.
- ✓ Creates an attractive and stylish ambiance on building facades, walls, or outdoor spaces, enhancing the visual appeal of the area.
- ✓ Suitable for a wide range of outdoor applications, including architectural lighting, accentuating building features, and illuminating walkways.
- ✓ Sleek and Space-Saving Structure
- ✓ Extended Durability with a Lifespan of Up to 50,000 Hours L80

### Product Specifications:

- ✓ Housing: Die-Cast Aluminum Body
- ✓ Diffuser: Clear Tempered Glass
- ✓ Ambient Temperature: 0~50°C
- ✓ Delivered Lumen output: 100lm/W
- ✓ Color Render Index > 80

### Model Selection

Model No.	Wattage	Lumen	Dimension (mm)LxWxH
FL02-020	20 W	2000 lm	96x97x170
FL02-054	54 W	5400 lm	200x140x260

### Selectable Options

CCT	Beam Angle	Body Color
3000K	15°	Black
4000K	24°	Grey
6500K	45°	White

