








Flood Light FL31 Asymmetric

-  IP66
-  Class I
-  AC220-240V
-  Surface Mounted
-  Highly recyclable
-  50K hours lifetime
-  Dimming Options



Product Features:

- ✓ Provides superior brightness with excellent energy efficiency, ensuring maximum lumen output with minimal power consumption.
- ✓ Offers complete protection against dust ingress and powerful water jets, making it ideal for harsh outdoor environments.
- ✓ Designed with efficient heat dissipation to maintain optimal performance and prolong the lifespan of the LEDs.
- ✓ Asymmetric Beam Angle
- ✓ Extended Durability with a Lifespan of Up to 50,000 Hours L80.







Product Specifications:

- ✓ Housing: Die-Cast Aluminum
- ✓ Diffuser: Toughed Glass
- ✓ Outstanding Working Temp: -20~50°C
- ✓ Delivered Lumen Output: 130lm/W
- ✓ Color Render Index > 70
- ✓ Power Factor > 0.9

Model Selection

Model No.	Wattage	Lumen	Dimension (mm)LxWxH
FL31-085	85 W	11,050 lm	402X295X60
FL31-100	100 W	13,000 lm	402X295X60

Selectable Options

CCT	Beam Angle	Body Color
 3000K	Asymmetric 140X50	 Black
 4000K		
 6500K		

