

Flood Light FLV2 Series

- IP66
- Class I
- AC220-240V
- Recessed Mounted
- Highly recyclable
- 50K hours lifetime
- Vibration Proof



Product Features:

- ✓ Provides superior brightness with excellent energy efficiency, ensuring maximum lumen output with minimal power consumption.
- ✓ Offers complete protection against dust ingress and powerful water jets, making it ideal for harsh outdoor environments.
- ✓ Designed with efficient heat dissipation to maintain optimal performance and prolong the lifespan of the LEDs.
- ✓ Designed for durability, vibration-proof flood lights ensure consistent, high-performance illumination in environments subject to frequent vibrations.
- ✓ Extended Durability with a Lifespan of Up to 50,000 Hours L80.

Product Specifications:

- ✓ Housing: Stainless Steel
- ✓ Diffuser: Tempered Glass
- ✓ Outstanding Temp:-40°C ~ 60°C
- ✓ Delivered Lumen Output: 100lm/W
- ✓ Color Render Index > 80
- ✓ Power Factor > 0.9



Model Selection

Model No.	Wattage	Lumen	Dimension (mm)LxWxH	Cutout (mm)
FLV2-072	72 W	7200 lm	ø 320x100x292	ø 292

Selectable Options

CCT	Beam Angle	Body Color
<input checked="" type="checkbox"/> 3000K	60°	<input checked="" type="checkbox"/> Black
<input type="checkbox"/> 4000K		
<input type="checkbox"/> 6500K		

