



Glowing 1 Test - 85 Balan E



Strip Light STSC



IP20/IP65



Class II



DC24V



Strip Light / Aluminum Profile




Highly recyclable



50K hours optional







Product Features:

- Utilizes Surface Mounted Device (SMD) LED technology for efficient and uniform illumination.
- \checkmark Offers high luminous efficacy, providing bright illumination while minimizing energy consumption.
- Excellent Linearity: Provides consistent and seamless lighting without glare, ensuring a visually appealing lighting experience.
- High Color Consistency: Maintains color uniformity across the entire length of the strip, enhancing the aesthetic appeal of illuminated spaces.
- ✓ Extended Durability with a Lifespan of Up to 50,000 Hours L80
- Widely used in hotels, shopping malls, furniture, cabinets, shelf, as decoration lighting, direct lighting or indirect lighting

Product Specifications:

- ✓ Outstanding Temp: -20~45°C
- ✓ Delivered Lumen output: 130lm/W
- ✓ Color Render Index > 80
- √ Power Factor > 0.9
- √ 5 Meters Rolls

Model Selection

Selectable Options


Model No.	Wattage Per Meter	Lumen Per Meter	LED Qty LEDs/M	Min Cut (mm)
STSC-004	4.8 W	624	144	55.56
STSC-007	7 W	910	144	55.56
STSC-009	9.6 W	1250	144	55.56
STSC-014	14.4 W	1900	288	55.56

ССТ	Beam Angle	
3000K	140°	
4000K		
6500K		

Packing









✓

- The light strip and other accessories can not be pressed;
- ✓ Do not damage the conducting wire of the circuit board during installation;
- The installation of the light strip should be in accordance with the electrical safety standards.
 - Only professional personnel can install it;

INSTALLATION REQUIREMENT

- Ensure that the power supply is loaded by transformer conversion;
- When installed in contact with metal or conductor, insulation protection should be made at the contact place;
- \checkmark . Observe the polarity before installing, connect properly to prevent damage to the light strip;
- ✓ Please prevent static discharges when installing;
- Provide anti-corrosion environment for products, avoiding adverse factors such as wet water drops;

