



GENTILL AERATOR TOOLBAR

NEW GENERATION SERIES



3 Point Hitch or Pull Type Units | Various Widths | Bolt Down 6" Swing Arm Tower Assembly
6" Double Pivot and Swivel | Hydraulic Operated 6" Valves | Hydraulic Folding Wings
Purge Ball Bypass with Adjustable Spray Deflector | Manifold System w/ Rear Splash Plate Nozzles
Large Super Single Rear Wheels | Large Axles w/ 8 Bolt Hubs
Heavy Duty Frame w/ Self-Leveling Hitch | C-Flex Bearing Design | Adjustable Gangs
Cast Ductile Iron Tines, Heat Treated
Can Fracture and Loosen Soil up to 8 1/2" Depth | 6" Flow Meter



19151 KETTLERSVILLE RD | NEW KNOXVILLE, OHIO 45871 | (419) 753-2275
WWW.BAMBAUEREQUIPMENT.COM | INFO@BAMBAUEREQUIPMENT.COM



30' PULLTYPE

- 6" or 8" Swing arm dual pivot
- Hydraulic folding wings
- Self leveling hitch frame
- 15' Transport width
- (6) Large floatation tires
- (12) Rear low spray hoods



30' 3 POINT NARROW FOLD

with 8" z pipe & 8" swivels

- (8) 6 ring Gen II roller assemblies, mounted to c-flex springs
- Each gang is adjustable to 0°, 2 1/2°, 5°, 7 1/2° or 10° angles
- Hydraulic manifold distributor with stainless steel discharge ports
- 8" rear hydraulic valve

