TO SUIT FLEX & RIGID COMBS / DRAPERS

COMB **TRAILERS**

FARMHAND | CONTRACTOR

Two models to suit most makes and models of flex and rigid harvester combs and drapers.

Easily and safely move them around the farm and between paddocks. Our **Comb Trailers** are also perfect to store the combs between harvests. Built to suit your requirements in Australia.

ORDER NOW

1300 562 337



Key features:

24ft to 50ft trailers available.

Australian made quality.

Custom designed to fit your comb.

Many options available.

40 years manufacturing experience.



Customisable

Customise your comb trailer with options like braked axles, toolboxes, spare wheels, lights, beacons and more.



Australian Made

Quality and durability you can trust from an Australian manufacturer with over 40 years experience.





COMB TRAILERS



Model Comparison





FARMHAND

CONTRACTOR

The Farm Hand Comb Trailer is the base model designed for moving combs around the farm and between paddocks.

The Contractor Comb Trailer is a heavy-duty model built for long journeys and heavier combs, perfect for contractors traveling between jobs.

Available in 24ft, 30ft, 36ft, 42ft and 45ft lengths.

Available in 36ft, 42ft, 45ft and 50ft lengths.

45mm axle with 6 stud Landcruiser pattern.

50mm axle with 6 stud Landcruiser pattern. Wider rear axle width for improved road travel.

Mudguards as standard.

Mudguard as standard.

High quality greased tandem rocker suspension.

Heavy duty front axle rocker assembly for better travel over rough terrain.

Optional braked rear trailer.

Heavy duty braked rear axle.

Multi-height pull as standard.

Multi-height pull as standard.

Fully adjustable rear axle assembly as standard.

Fully adjustable rear axle assembly as standard.

Fully adjustable and interchangeable comb mounts.

Fully adjustable and interchangeable comb mounts.

Heavy duty greaseable ball race turntable.

Heavy duty greaseable ball race turntable.

Unique bolt together design on the longer models to allow for length adjustment.

Unique bolt together design on the longer models to allow for length adjustment.

Standard 40mm ring feeder. Optional 50mm tow ball.

Standard 40mm ring feeder. Optional 50mm tow ball.

