

Innovative Energy-Efficient Air Conditioning Solutions

"A Breath of Fresh Air in the HVAC Industry"



















What We Offer

We offer complete, end-to-end, bespoke HVAC solutions to industrial, commercial, and residential customers across the Kingdom of Saudi Arabia, serving both private and governmental sectors. Leveraging our technical knowledge and experience, we customize our services and project solutions to meet the unique needs of our clients while addressing the specific challenges of their buildings and facilities. We provide HVAC solutions featuring globally recognized brands, including **Clivet, Midea, LG, Daikin, Trane, and York**, ensuring high-quality, efficient, and reliable systems tailored to each project's requirements.







Our Products







Chiller Systems

Offices & Small Commercial Buildings; Shopping Centers; Hospitals

VRF Systems

Commercial buildings; Hotels; residential & more

AHU & FCU

Malls & Retail Centers; Stations & Airports









Residential Systems

New Homes & Retrofits

Rooftop Package

Malls & Showrooms; Industrial Facilities

Control Systems

Digital Automated Control & Building Management Systems (BMS)



Rooftop Package



Specifications

| Nominal tons * | | | 7.5 | 10 | 25 | |
|--|----------------------|--------------------------|---------------------------|---------------------------|--------------------------------|----------|
| Model | | | CKTC-3-XHE 10.1 | CKTC-3-XHE 14.2 | CKTC-3-XHE 38.2 | |
| Power supply | | | 380 - 415V~, 3Ph, 60Hz | 380 - 415V~, 3Ph, 60Hz | 380 - 415V~, 3Ph, 60Hz | |
| топстварру | | Btu/h | 84,000 | 124,000 | 282,000 | |
| Cooling (T1) | Capacity | kW | 24.6 | 36.3 | 82.6 | |
| | Power input | kW | 7.240 | 11.071 | 28.200 | |
| | EER | Btu/h.W | 11.6 | 11.2 | 10.0 | |
| Cooling (T3) | Capacity Power input | Btu/h | 72,000 | 107,000 | 248,000 | |
| | | kW | 21.1 | 31.4 | 72.7 | |
| | | kW | 8.670 | 13.300 | 34,100 | |
| | EER | Btu/h.W | 8.3 | 8.0 | 7.3 | |
| | LLIN | CFM | 2,800@ 60Pa(0.24 in.wg.) | 3,800@ 70Pa (0.28 in.wq.) | 10,000@ 110Pa (0.44 in.wg.) | |
| Air flow (Evaporator) I/s | | | 1,322@ 60Pa (0.24 in.wg.) | 1,794@ 70Pa (0.28 in.wg.) | 4,722@ 110Pa (0.44 in.wg.) | |
| ESP range (Standard) ESP range (Customized) Pa in.wg. Pa | | | 150 - 0 | 200 - 0 | 300 - 0 | |
| | | | 0.6 - 0 | 0.8 - 0 | 1.2 - 0 | |
| | | | 500 - 250 | 500 - 250 | 500 - 200 | |
| (High static pressure) in | | | 2.0 - 1.0 | 2.0 - 1.0 | 2.0 - 0.8 | |
| | | in.wg. | (1) 0 - %100 | (2) 0 - %50 - %100 | | |
| Capacity steps (Circuits) | | 40 | (2) 0 - %50 - %100 | (2) 0 - %50 - %100 | | |
| Max. overcurrent protection | | A | 40 Scroll | Scroll | 90 | |
| | Type | | Scroll 1 | Scroll 2 | Scroll | |
| Compressor | Quantity | | | _ | 2 | |
| | Brand | | Danfoss | Copeland | Danfoss | |
| Condenser fan | Type | | Axial | Axial | Axial | |
| | Quantity | | 1 | 2 | 2 | |
| | Drive type | | Direct drive | Direct drive | Direct drive | |
| | Materials | | Plastic | Metal | Plastic | |
| Condenser motor insulation class | | | F | F | F | |
| Condenser motor protection class | | | IP44 | IP44 | IP44 | |
| Evaporator fan | Type | | Centrifugal | Centrifugal | Centrifugal | |
| | Quantity | | 1 | 1 | 1 | |
| | Drive type | | Belt, adjustable | Belt, adjustable | Belt, adjustable | |
| | Materials | | Metal | Metal | Metal | |
| Condenser / Evaporator | | | | Hydrophilic alı | ıminum fin / Inner grooved cop | ner pipe |
| Sound pressure leve | | dB(A) | 78.0 | 72.0 | | l pipe |
| Sound pressure leve | Type | GD(/ I) | R410A | R410A | 79.0 | |
| | Control | | Throttle valve | Throttle valve | R410A | |
| Refrigerant | Control | lum. | 7.4 | 6.4 + 6.4 | Capillary | |
| | Charged | kg | 16.31 | 14.11 + 14.11 | 14.0 + 14.0 | |
| | 0.00 | lbs | 10.51 | 20 | 30.87 + 30.87 | |
| EHK power input | Option 1 | kW | 14 | 24 | 28 | |
| | Option 2 | kW | 14 | | 36 | |
| Thermostat | | | KJR-29B | KJR-29B | | |
| Centralized controller (Customized) | | Yes | Yes | Yes | | |
| Ambient temperatu | re | °C | 52 - 10 | 52 - 10 | 52 - 10 | |
| Turible temperature | | °F | 125.6 - 50 | 125.6 - 50 | 125.6 - 50 | |
| Operation temperature | | °C | 30 - 17 | 30 - 17 | 30 - 17 | |
| | | °F | 88 - 62 | 88 - 62 | 88 - 62 | |
| Drainage pipe | | 3/4" NPT | 3/4" NPT | 3/4" NPT | | |
| Filter | Quantity | | 2 | 3 | 3 | |
| | Type | | Nylon, washable | Nylon, washable | Nylon, washable | |
| | Size | mm | (12 × 500 × 1,050)×2 | (12 × 575 × 1,040)×3 | (12.5 × 640 × 1,420)×3 | |
| | | inch | (2/1 × 4/3-19 × 8/3-44)×2 | (2/1 × 8/5-22 × 41)×3 | (2/1 × 4/1-25 × 8/7-55)×3 | |
| | | _ | 1,130 × 1,230 × 1,965 | 1,965 × 1,255 × 2,230 | 2,230 × 1,655 × 2,885 | |
| | | 2/1-44 × 2/1-48 × 8/3-77 | 8/3-77 × 8/3-49 × 8/7-87 | 8/7-87 × 8/1-65 × 8/5-113 | | |
| | | 1,145 × 1,265 × 1,975 | 1,980 × 1,290 × 2,250 | | | |
| | | 45 × 8/7-49 × 4/3-77 | 78 × 4/3-50 × 8/5-88 | 2,230 × 1,690 × 2,895 | | |
| | | 390 /370 | 650 / 615 | 8/7-87 × 2/1-66 × 114 | | |
| Net / Gross weight kg | | 860/816 | 1,433 / 1,356 | 1,260 / 1,180 | | |
| Loading | | lbs | 24/5 | | 2,778 / 2,602 | |
| | 40 / '20'HQ | Pcs | 24/5 | 12/3 | 4/2 | 1 |

- *: Nominal ton is only for reference, cooling capacity as per specifications.
- #. Please contact with Clivet sales team, when adjust the fan speed of 5 ton unit.

 1. Cooling (T1) test condition: Indoor temperature 27°C (80.6°F) DB/19°C (66.2°F) WB, outdoor temperature 35°C (95°F).
- 2. Cooling (17) test condition: Indoor temperature 29°C (84.2°F) DB/19°C (66.2°F) WB, outdoor temperature 46°C (114.8°F).

 3. Units are suitable for operation to ±9620 of nominal air flow.
- 4. EHK means Electric Heater Kit. Only one EHK can be fixed per unit.
- 5. Sound pressure values are measured in a semi-anechoic room, at a position 1m front of the unit and 'H/0.5 + 2m' above the floor (H for unit's height).
- 6. Specifications are subject to change without prior notice for product improvement.
- 30 .7 ton unit hasn't high static pressure model.

Features



- ❖ Press the 'Check' button, the LED display in PCB board of the unit will dislay the normal checking code.
- ❖ If the unit is in running with abnormal operation, the LED display will show the error code.

SYSTEM SELF-DIAGNOSTIC



EXTERNAL PRESSURE GAUGE PORTS

The unit provides external pressure gauge ports for convenient and fast checking system pressure without removing the panel.



WASHABLE FILTER

Washable nylon filter as standard. Aluminum filter is optional.

FLEXIBLE INSTALLATION

- Compact design
- Flanges of air flow inlet and outlet as standard
- It is suitable for installation in rooftop and ground.





Electric heater kit is optional.









Vision Co & Innovation

1 Efficient

The strategic adoption of innovative technologies and thoughtful systems design can yield remarkable outcomes, including substantial reductions in energy usage and operating costs for businesses

2 Smart

Intelligent monitoring and control systems enable our solutions to perform at maximum efficiency, while also ensuring that faults and operational issues are managed proactively


3 Maintained

By helping people to understand how to use or systems sensibly and responsibly, we can significantly reduce the consumption of energy and other resources

4 Educated

Rigorous preventative and reactive maintenance protocols are critical to keeping our HVAC systems functioning effectively and energy-efficiently







Abu Dhabi, UAE

Water cooled screw Chillers (4 Nos.* 820 KW), COP: 6.3





AJMAL REAL ESTATE Ajmal Sarah Tower Dubai, UAE

Water Cooled Screw Chillers (300 Tons * 4 Nos. Chillers) +FAHU & FCU





Dubai, UAE

Screw Chillers 3 Nos., Scroll Chillers 3 Nos. AHU & FCU



Fakeeh University Hospital Dubai, UAE

2 Nos. 140 T.R. Water Cooled Heat Pumps





Sharjah, UAE

WSAT XTR CHILLERS 2 Nos. / AHUs 17 Nos. / FAHUs 9 Nos. / FCUs / CCU





Expo 2020 Italian Pavillion Dubai, UAE

VRF Systems





kerzner

Atlantis - Kerzner International Resorts Dubai, UAE


Package Units, AHU





Hermes 1 Data Centre - AUH 7 Abu Dhabi, UAE

VRF System , FAHU & DX





ALDAR
Al Dar Headquarters
Abu Dhabi, UAE

AHU (15 Nos.) FCU (250 Nos.)





Moro 2.0 Data Centre Dubai, UAE

VRF System , Package Unit, FAHU & DX





Grand Salalah Mall Salalah, Oman

Air Cooled Screw Chillers 6 nos. (Capacity: 8,580 KW), AHUs, FCUs





Abu Dhabi National Exhibition Centre Abu Dhabi, UAE

AHU (60 Nos.) & FCU (530 Nos.)







Burj Khalifa Water Fountain, Dubai, UAE

AHU (41 Nos.) & FCU







Dubai Maritime City Commercial Complex, Offices, Congresses Dubai, UAE

AHU & FCU





Al Zahra Hospital, Alsharjah, UAE

AHU & FAHU (15 Nos.), FCU (355 Nos.), CCU





Tower A Business Bay Hotel - P106, Dubai, UAE

AHU (88 Nos.)





Al Fattan Palm Resort – Jumeirah Dubai, UAE

AHU & FAHU (25 Nos.)





Al Zahra Hospital, Alsharjah, UAE

AHU (50 Nos.), FCU (230 Nos.), CCU







Al Bandar, UAE

FCU (1,530 Nos.) & AHUs (Nos.10)





Al Zeina, UAE

FCU (3,270 Nos.) & AHUs (34 Nos.)





Sorbonne University Abu Dhabi , UAE

AHU (62 Nos.)





W Hotel – The Palm Dubai, UAE

FCU (2,100 Nos.)



Certifications



Eurovent

Clivet is part of the **EUROVENT Certification** Programme for "Water Chillers", "Rooftop units", "Air handlingunits" and "VRFs".





Integrated Management System

Clivet has certified its Quality, **Environment and Safety** Management Systems according to the international standards ISO 9001. ISO 14001 and ISO 45001.



Slovenian government

brand for the promotion and protection of the environment and sustainable development.



Safety standard

Products compliant with applicable Directives as required in all EU countries.



ERP – Energy-related **Products**

Clivet products and systems meet the requirements of the ErP Delegated Regulations.



SG-Ready

KeyMark

European brand for the

provision of incentives

domestic hot water.

Products avalabile at

keymark.eu/en

Ekosklad

for the installation of heat

pimps to heat and produce

Countries where the brand

is recognised and Certified

Heat pumps certified to be connected to a smart grid to optimise consumption in combination with renewable energy systems.



AHRI's globally recognized and industry respected certification program helps you, as equipment and component manufacturers, sell more products, win bids, differentiate yourselves from competitors, and comply with government requirements.



TUV Sud - Europe Air handling unit in hygienic design range "AQX"



Saudi Arabia Standards Products compliant with Saudi Arabia standards (SASO)



MEPS Australia & New Zealand



Clivet Clients







































































Saudi Vision 2030

At Vision Co., we are proud to support the ambitions of the Saudi Vision 2030 and we are committed to helping our nation achieve the goals of the Vision Realization Programs. In particular, through our innovative and sustainable solutions, we will help support:



Housing Program

Which works to provide housing solutions that enable Saudi families to own and benefit from suitable houses based on their personal needs and financial capabilities



National Industrial Development and Logistics Program

Which aims to transform the Kingdom into a leading industrial powerhouse and a global logistics hub.



Quality of Life Program

Which endeavors to improve quality of life by creating the environment to develop and support new livable and lifestyle options.

Working Together For A Vibrant Society

A Thriving Economy

An Ambitious Nation





Riyadh Headquarters2855 Al Hajjaj Ibn YusufAz Zahra Dist., Riyadh 12812

% 0599100679

□ h.office@visionco.ltd

