

SIPOMER[®] MAC

TECHNICAL DATA SHEET NA 90101640 – DECEMBER 2024

IDENTIFICATION

Chemical Name: PROPRIETARY

SPECIFICATIONS

Appearance (25°C)
Acid Value 1, mgKOHg
Free Phosphoric Acid, %
MEHQ, ppm

RESULTS

Clear Liquid
254.0 – 265.0
17.0 Max
5000 - 7500

METHOD

VISUAL
RP-0427
RP-0427
RP-1408

TYPICAL PROPERTIES

pH (As Is) 4 Max
Odor Mild Acrylic Odor

STANDARD APPLICATIONS

SIPOMER[®] MAC into acrylic or styrene acrylic systems improves adhesion to metallic substrates. It also enhances properties such as polymer stability and gloss. This monomer has been used mainly in specialty purpose coatings, including industrial maintenance, OEM, as well as high performance structural adhesives

STANDARD PACKAGING

SIPOMER[®] MAC is available in Bulk Quantities, 525 LB. Closed Head Poly Drums, and 275 Gallon 2600 LB.Totes. Alternative package sizes may be available upon request.

SHELF LIFE

SIPOMER[®] MAC has a shelf life of 365 days.

DISCLAIMER

The information contained in this document is given in good faith and based on our current knowledge. It is only an indication and is in no way binding, notably as regards infringement of or prejudice to third parties through the use of our products. SYENSQO GUARANTEES THAT ITS PRODUCTS COMPLY WITH ITS SALES SPECIFICATIONS.

This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of the present document and SYENSQO is at their disposal to supply any additional information.



For orders or questions, visit us at www.syensqo.com