



Dry fertilizer coating

Nuvano BoMZ is a high-efficiency, water-based dry fertilizer coating engineered to deliver essential micronutrients directly onto granular fertilizer while minimizing dust and improving fertilizer handling. By turning every granule into a green, high-performance delivery system, it guarantees uniform nutrient distribution across the field while using Nuvano's Optimizer Technologies to enhance micro and macronutrient availability.

nuvano.ag/bomz

LIMITATIONS OF WARRANTY AND LIABILITY: Nuvano, and any other seller, warrants only that this product conforms to the chemical description on the product label. No other warranty, express or implied, as to the merchantability, fitness for a particular use, or otherwise shall apply. Purchaser's exclusive remedy for loss or damage related to the purchase and/or use of this product shall be limited to the refund of the purchase price only. By using this product, you are deemed to have accepted the terms of this notice.

FOR COMMERCIAL USE ONLY. USE ONLY AS DIRECTED. ©2026 Nuvano. ALL RIGHTS RESERVED. 091526

Technical Data Sheet

Principal Functioning Agents:

Guaranteed Analysis:

Sulfur: 3.6%

Boron: 0.5%

Manganese: 3%

Zinc: 6%

Derived From: Ammonium Sulfate, Boric Acid, Manganese Sulfate, Zinc Sulfate

Also Contains Non-Plant Food Ingredients:

Lipophilic Carriers: 0.3%

Graphene Carbon: 0.1%

Density:

10.9 pounds per gallon at 68°F

Application Rate:

For impregnation of granular fertilizer, apply 2 to 4 quarts per ton of granular fertilizer. It may be applied to dry granular fertilizer blends, including NPK blends, during the blending process.

Mixing Compatibility:

Compatible with other efficiency technologies. Compatibility testing is recommended before application.

Available Packaging:

2.5 gal jug, 2x2.5 gal box, totes

Storage & Disposal:

Storage and handling of Nuvano BoMZ shall be in either fiberglass, polypropylene, plastic or low carbon stainless steel (316LSS) containers. Avoid steel or nylon vessels or steel or nylon valves and plumbing as prolonged contact will deteriorate valves and plumbing. Dispose of contents and container to an approved waste disposal plant in accordance with local, regional, and national regulations.

