

Next Generation HVAC Coating



The inorganic HVAC coating that protects against corrosion, mold growth, chemicals, heat, UV light, pollution and more. Extending the life of your HVAC equipment, improving indoor air quality and saving energy!



JSA Service
Chiller & HVAC Specialists

WWW.JSASERVICE.COM



**INTERRUPT THE
EXPENSIVE REPLACEMENT
CYCLE OF YOUR HVAC
EQUIPMENT WHEN USING
MG1-3500 ON GOOD
CONDITION COILS!**

Side by side comparison using MicroGuard1-3500

THERE IS A BETTER WAY

Introducing Adsil's next generation HVAC/R coating - MicroGuard1-3500. MG1-3500 is among the most advanced protective coating available to protect your new HVAC equipment. Proven to positively arrest corrosion, protect against chemical and environmental assault, extend the life of equipment, save energy and mitigate microbial growth providing sustainable results with a verifiable ROI. For best results MG1-3500 is most effective when coils are treated whilst still in good condition and pre-erosion/corrosion/wear and degradation.



STOP USING COATINGS THAT ONLY PROTECT AGAINST CORROSION!



STOP APPLYING THICK COATINGS THAT REDUCE LAMINAR AIR FLOW & IMPEDE HEAT TRANSFER!



STOP USING ORGANIC COATINGS THAT FEED MOLD & DEGRADE INDOOR AIR QUALITY!

PRESERVE

MicroGuard1-3500 is an inorganic cross link cured, glass-like film that chemically bonds to non-ferrous metal ensuring maximum adhesion and protection in the harshest environments. At 6-8 microns thick, the coating preserves your new HVAC/R system's performance without affecting heat transfer or laminar air flow.

PROLONG

MG1-3500 can prolong your HVAC/R system beyond its normal engineered life expectancy when applied to coils in good condition, extending the replacement cycle and capital budget outlay. Deferred capital expenses and provided energy savings drop directly to the bottom line.

PROTECT

MG1-3500 offers superior corrosion protection, but it doesn't stop there! MG1-3500's advanced formula protects against pollution and chemical assault other coatings can't, cannot oxidize, will not support mold growth improving indoor air quality. Its hydrophobic properties repel debris, reduce maintenance and save energy protecting your assets and your bottom line.

WWW.JSASERVICE.COM

FEATURES & BENEFITS

Preserve, prolong and protect your most valuable assets, and your bottom line, with MicroGuard1!

LOW VOC Product

Environmentally friendly formula with "0" Global Warming Potential value after cure

Extreme Corrosion Protection

ISO 16773 EIS tested to be significantly more resistant to ion migration to positively arrest corrosion

Unmatched Chemical, UV & Pollution Protection

Proven to withstand the harshest environments

9H Pencil Hardness for Superior Durability

Mitigates Fungal and Microbial Growth

Inorganic formula cannot feed microbes resulting in reduced maintenance costs and better indoor air quality

Covalently Bonds with 5-B Adhesion

Strongest adhesion available to aluminium, copper and stainless; and will not delaminate, peel or crack

Microscopically Thin

No air flow reduction or heat transfer degradation after coating for better efficiency and energy savings; protects both round tube and microchannel coil designs

UV Stable

Will not photo-oxidize, yellow or flake

Hydrophobic

Coils are easier to clean, stay cleaner longer and green cleaners can be effectively used

Sustainable with Verifiable ROI

Lowers maintenance costs, lowers life-cycle costs and extends service life of equipment

Coats Compressors, Evaporator Coils & Painted Surfaces

REACH Exempt and RoHS Compliant

Complies with EU regulations

LEED Points Available

Building certification rewards sustainable and environmentally friendly decisions and can qualify to obtain state and local government incentives

Installation in the Field or at a Coating Center

Professional installation with fast turnaround time



KNOW YOUR COATING CHEMISTRY

Chemistry is the key to a coating's performance. MG1-3500 has a proprietary inorganic, siloxane-based formula. Many times stronger and thinner than traditional organic coatings, it provides superior protection from the harshest environment, has no detrimental impact on heat transfer, can coat microchannels and retains a long-lasting barrier that protects HVAC coils against corrosion for an extended period of time (typically 5 years or more). Unlike its organic counterparts, MG1-3500 coating cannot be degraded by heat, light or oxygen (photo-oxidation) or feed mold because of its chemical make-up.

COATING COMPARISON	MicroGuard1-3500 Coating	Traditional HVAC Coatings
Coating Chemistry	In-Organic	Organic
Bond Strength	193.5 (33% Stronger)	145
Degraded by Heat, Light or Oxygen	No	Yes
Mold/Fungal Food Source	No	Yes
Dry Film Thickness (Microns)	6-8	25-75
Impedes Air Flow, Heat Transfer	No	Yes
Pencil Hardness	9H	HB -5H
ASTM G21 Rating	Rated 0 – No Growth	Pass or Not Tested
Flexibility	180 Degree	1/8" or Less



01932 780 321



info@jsaservice.com



123 Harris Way, Sunbury-on-Thames, Middlesex TW16 7EL



Department DD Number

Service Desk 01932 756 969

Parts ID 01932 756 968

Technical - Training 01932 756 967

Accounts 01932 756 9669



WWW.JSASERVICE.COM