



APEX

PROFILE

HYBRID
VEHICLE WASH SYSTEMS

WASHWORLD

www.washworldinc.com | 920.338.9278 | 888.315.7253

TRUSTWORTHINESS

VISION:

Creating global partner success through world class wash experiences.



WHY CHOOSE

WASHWORLD®



Washworld has consistently been on the cutting edge of car wash technology. We are continually striving to provide innovations that improve the efficiency and quality of our wash systems while keeping them simple to operate and maintain. Our designs and features create a unique and memorable experience that keeps your customers coming back! As a company of car wash owners ourselves, Washworld is well versed in the daily operations of running a car wash business. This is the inspiration for all our technologies. What does this mean for you? Washworld will provide the most user friendly, technologically advanced and consistently reliable in-bay automatic car wash systems available.

RELATIONSHIPS

TABLE OF CONTENTS

01-14 PROFILE® APEX

- 01 - 05 STANDARD FEATURES
 - 06 - 8 OPTIONAL FEATURES
 - 9 HEAVY DUTY PUMP STATION
 - 10 MEDIUM PRESSURE SDS
 - 11 IN-BAY EQUIPMENT PACKAGE
 - 12 STANDARD FEATURES - QUICK LIST
 - 13 OPTIONAL FEATURES - QUICK LIST
 - 14 PROFILE APEX SPECS
-

15-16 DRYING SYSTEMS

- 15 HIGH VELOCITY VEHICLE DRYING SYSTEM
 - 16 ON-BOARD VEHICLE DRYING SYSTEM
-

17 SIGNS

18 WATER TREATMENT

19 CUSTOMER SERVICE

20 WARRANTY

WHAT MAKES
APEX
PROFILE *different*



Washworld's Profile® Apex hybrid vehicle wash system is specifically designed to give you the best of both worlds. It combines Profile's soft touch technologies with Washworld's advanced touch-free technologies giving you the freedom to offer a totally touch-free experience, an entirely soft touch experience or a seamless combination of both. Profile Apex was designed to provide the ultimate customer experience utilizing the latest technology with emphasis on durability, simplicity of use and reduced maintenance.

PROFILE® APEX STANDARD FEATURES

wwexclusive™ APEX CONTOURING OVERHEAD ARCH WITH DOUBLE BARREL TECHNOLOGY

The Apex Double Barrel contouring overhead arch consists of a protective polyethylene cross-link face foam that houses the nozzles and dual overhead manifolds. A stainless steel valance conceals the top energy chain and a secondary sensor array was included for additional safety.

Apex utilizes dual overhead manifolds (low pressure and high pressure) for solution applications, high-pressure cleaning, and rinsing. Digital Surface Profile (DSP) is the advanced method of reading a vehicle's contours and adjusting the rotation of the overhead manifold keeping it perpendicular to the vehicle surface and a prescribed distance from the vehicle resulting in optimal cleaning of front bumper/grill, windshield/mirrors, rear window visor and rear bumper.

The Apex overhead arch offers the ability to do a full contour of the vehicle down to the lowest point of the front and rear bumpers, offers triple pass technology and will even rotate to reach the back of pick-up truck windows and tailgates. Additionally, the top arch can be programmed to stay high for quick pre-soak or rinse application.

The stainless steel low-pressure manifold utilizes 10 top VeeJet nozzles for applying low-pressure pre-soak functions to all horizontal surfaces of the vehicle. The high-pressure manifold utilizes 16 top zero degree rotating turbo nozzles.




wwexclusive™ APEX ADJUSTING SIDE ARCHES WITH DOUBLE BARREL TECHNOLOGY

Apex is equipped with dual side manifolds (low pressure and high pressure). Digital Surface Profile (DSP) is the advanced method of locating the vehicle then adjusting to the measured location of the vehicle's sides and position in the wash bay. DSP enables the Double Barrel side arches to adjust for various vehicle sizes and location in the bay providing the most precise cleaning possible.

The stainless steel low-pressure manifold utilizes 14 VeeJet nozzles (7 on each side) for applying low-pressure pre-soak functions to all vertical surfaces of the vehicle. The high-pressure side manifolds utilize 26 zero degree rotating turbo nozzles (13 on each side).

**Shown with optional Touch Power Wheel Detailer™*



PROFILE® APEX STANDARD FEATURES



LONGEVITY / ROI

STAINLESS STEEL

Without a doubt, the most durable material for use in a car wash is stainless steel. When other manufacturers are using cheaper, less durable materials in their machines, Washworld refuses to compromise on quality and uses stainless steel throughout. The stainless steel used for Apex's wall mounting system, travel rails and laser cut overhead wash carriage, ensures that Apex is the most long lasting, durable system.

ADVANCED DRIVE MOTION TECHNOLOGY

Apex's belt drive utilizes multiple variable frequency drive technology with a clean and simple design. Both the rotation and independent movement of the dual side wash media and top wash media are variable frequency drive controlled to ensure a smooth operation and a precise application of all solutions and water. What does this mean for you? A gentle yet effective wash experience, no wasted water or chemicals, fewer moving components, less weight, reduced maintenance and most of all a quicker return on investment!

REDUCED MAINTENANCE

All Washworld systems are designed with a focus on reduced maintenance costs. Sealed gearboxes eliminate the need for oil changes. Reduced weight and less motion equal less wear and tear. High quality, premium components and materials withstand the harsh wash bay conditions resulting in a longer life.

DOUBLE STACKED ENERGY CHAIN

The Apex innovative double stacked cable carrier protects moving cables and hoses from abrasion and entanglement in a compact, space saving design. The double stacked feature makes the overall width smaller allowing the machine to fit in narrower wash bays. The energy chain also provides controlled bend radius of cables and hoses to prevent pinching or kinking. The non-metallic construction ensures quiet performance, longer cable life and extended supply line life.



Especially important when positioning vehicles within a soft touch vehicle wash bay, Washworld's Vehicle Sizing System (VS2®), with precise loading feature, utilizes advanced software coupled with photo eye technology to provide a safe and reliable means of positioning the vehicle in the wash bay. This eliminates the need for floor mounted treadle plates or wheel stops, resulting in a significant reduction in wiring and fewer components to maintain.

PROFILE® APEX STANDARD FEATURES

WWexclusive

DSP - DIGITAL SURFACE PROFILE

DSP - WASH MEDIA CONTROL

Washworld's exclusive DSP - Digital Surface Profile system is the advanced method of reading a vehicle's contours to allow for the most precise cleaning possible. Utilizing 3D imaging, DSP enables Profile to adjust for various vehicle surfaces to deliver a wash that reaches every angle with Profile's super soft polyethylene foam wash media. The DSP System offers consistent length, width and height measuring of vehicles for optimal product application and cleaning. This results in a gentle and effective wash experience and ensures that products are applied to the vehicle not the floor, which saves money and reduces wash times by customizing the travel distance of the Profile based on the length of each individual vehicle.

DSP - DOUBLE BARREL CONTOURING OVERHEAD MANIFOLD CONTROL

DSP is the advanced method of reading a vehicle's contours and adjusting the rotation of the overhead manifold keeping it perpendicular to the vehicle surface and a prescribed distance from the vehicle resulting in optimal cleaning of front bumper/grill, windshield/mirrors, rear window visor and rear bumper. DSP ensures that products are applied to the vehicle not the floor, which saves money and reduces wash times by customizing the travel distance of Apex based on the length of each individual vehicle.



WASH MEDIA

INNOVATIVE WASH MEDIA

Apex's super soft blue side and top polyethylene foam wash media comes equipped with Clean Rinse, Washworld's wash media cleaning and lubricating system. The Clean Rinse System keeps the media from retaining dirt and debris which results in the best possible customer experience.

PROFILE APEX MIRROR DETAILER

The mirror detailer feature offers the ability to increase throughput by cleaning both sides of mirrors using a single soft touch pass. The wash media pass can start at the front or the rear, once the side brush has passed the mirror it will reverse direction to effectively clean both sides of the mirror, then completes the pass.

SIDE BRUSH EXCHANGE

This feature is an added benefit to customers that run a single side brush on the front and rear of a vehicle. When enabled, it will alternate each side brush ensuring that both the left and right brushes are used equally.



PROFILE® APEX STANDARD FEATURES



Waterproof hand held RF remote control for manual movement and machine functions



WASHVIEW —HMI ON-SITE

With Apex's standard Washview® HMI On-Site, a color touch screen gives you complete access to Apex including programming, maintenance, diagnostics and wash counts. No on-site PC or laptop is needed to configure your wash. Apex also features a comprehensive integrated notification system which can monitor auto cashiers, doors, fluid levels and more. In addition, the Wash Package Storage capability allows for 4 groups of 8 wash packages.



ww exclusive FLEX PASS

Standard on Apex is Washworld's Flex Pass® dual application system. This stainless steel, angled flood style pods and an overhead 6 nozzle stainless steel manifold applies up to 8 different applications to the entire vehicle (top, sides, front and rear). The Flex Pass application system is mounted on both the entrance and exit end of the Profile carriage. This allows for two product applications to be applied to the vehicle in a single pass. Applications can be programmed from front to rear or rear to front to minimize machine movement. The speeds are adjustable individually in both directions which expedites the wash process to increase the throughput of cars, which in turn translates into greater profits for you!



VALUE ADDED

EYE CATCHING LEDS

For can't miss customer attraction, brilliant blue LEDs illuminate Apex's high gloss composite wash carriage cover.

Dual 10" long green and red LEDs line the entrance side cover, combined with audible voice prompts that coincide with the in-bay instructional signage, help to position the vehicle in the wash bay. Even when idle, the red and green LEDs can sequence to draw attention to the wash bay with an eye-catching light show.

BUY-UP OPTION

Four customizable buy-up options allow your Auto Cashier to up-sell for you which renders greater wash package flexibility and maximized profits!

VOICE PROMPTS

Your customers will never need to guess what to do next with Apex's voice prompts. Audible instructions and information are linked to Apex's instructional signage. Standard on Apex, the voice prompt is in English, however is customizable for other languages, dialects or custom voice messages.



PROFILE® APEX OPTIONAL FEATURES



Washworld's optional Washview® Mobile provides virtually the same technologies as Washview® On-Site (standard), however it allows you to access and control Apex from anywhere in the world via a high-speed Internet connection. Washview Mobile uses a standard web browser on your smart phone or tablet to give you mirror image access of your HMI. It even gives you the ability to receive text or email notifications to keep you fully informed!



POWER TOWER WHEEL CLEANER

Effective wheel cleaning that will keep your customers coming back! The 40" high tower features 4 zero degree rotating turbo nozzles, providing intense cleaning as well as great customer appeal. Power Tower Wheel Cleaner® manifolds are fabricated completely from stainless steel wrapped in a vibrant blue, rotationally molded polyethylene cover and is available with or without eye-catching blue LEDs. Not only is the Power Tower Wheel Cleaner effective for wheel cleaning, but it is great for removing mud, snow and ice from rocker panels and running boards!



BIG SHOT CHEMICAL TIRE APPLICATION

Big Shot™ chemical tire applicator is constructed from stainless steel and specifically designed to target your tires/wheels for impeccable results. Pre-charged solution and air manifolds are photo eye activated and software controlled with customizable settings. Big Shot's strategic placement after the undercarriage provides maximum dwell time for optimal performance. Two separate manifolds with 3 nozzles on each (driver and passenger side) provide complete coverage. Each set of application nozzles can deliver a different tire/wheel cleaning product (high pH and low pH) or a dual application of the same product. No matter what size tires, Big Shot has it covered!



UNDERCARRIAGE & ROCKER PANEL BLASTER

The undercarriage and rocker panel blaster is specially designed to thoroughly attack any dirt, debris and snow on the lower portion of your vehicle. The undercarriage and rocker panel blaster consists of 11 stainless steel nozzles; 3 on the undercarriage and 4 on each rocker panel blaster.



PROFILE® APEX OPTIONAL FEATURES



TOUCH POWER WHEEL DETAILER

Washworld's Touch Power Wheel Detailer™ combines tire chemical application, high pressure nozzles and a soft yet durable wash media for sparkling clean results. Apex's DSP (Digital Surface Profile) identifies the size and location of the tires. The wash media rotates clockwise and counterclockwise for a precise clean every time. (Not available with Apex On-Board Dryer)


Requires ESD2 for chemical application.



TOUCH-FREE POWER WHEEL DETAILER

Washworld's Touch-Free Power Wheel Detailer™ combines tire chemical application, high pressure nozzles and rapid wheel blasters for better than hand applied results. Apex's DSP (Digital Surface Profile) identifies the size and location of the tires for a precise wheel blast every time! Additionally, when traveling along the vehicle during the high-pressure rinse, the front facing side nozzles will activate to give your mirrors a deep clean.

Requires ESD2 for chemical application.



Washworld is launching an all-out war on bugs and salt residue with our extra step vehicle preparation Bug A'Salt™. This unique concentrated attack targets bugs and salt film on the front bumper/grill and windshield/mirrors leaving vehicles cleaner and your customers happier.

A specific bug/salt formulated product is applied through a specific Bug A'Salt manifold utilizing a low-pressure injector. The manifold applies the product on the front bumper/grill on the first pass. Then targets the windshield/mirrors on the return motion ensuring full coverage and providing extensive dwell time for superior results.

Bug A'Salt is included in the optional Extended Solution Delivery ESD1 or ESD2.



More show, more shine, more revenue with Washworld's Foam 'n Flow® application system! It produces high end results for extra profit generation. Complete with full, dramatic product enhancing LED backlighting, Foam 'n Flow can be used to make an impressive foaming sheet with most Carnauba, hot wax, polish and conditioning products on the market.

PROFILE® APEX OPTIONAL FEATURES

TRI-COLOR FOAM

There is simply no better Tri-Color Foam application available! Washworld's Tri-Color Foam features completely adjustable nozzles for coverage the way you want it, where you want it.

SPECTRARAY™

A spectacular array of over 4,500 LEDs fill the wash bay with SpectraRay™! The red, magenta, blue and green LEDs are fully programmable to add splashes of various colors during any or all of the product applications to accentuate the entire wash process. The colors can sequence through flashing colors for an intense experience, switch to a steady color at any point to coincide with your wash package and even coordinate with your in-bay instruction sign. Even when idle, SpectraRay can sequence through color to draw attention to the wash bay with an eye-catching light show making it unique and memorable. Transform your car washing experience in a big way by bathing your wash bay in red, magenta, blue and green!



SPECTRARAY+™

SpectraRay+™ works in conjunction with SpectraRay to take the spectacular LED light show to the next level!

SpectraRay+ includes an adjustable stainless steel wall or pedestal mounted system, bringing the intense light show to eye level. The colors can sequence through flashing colors for an intense experience, switch to a steady color at any point to coincide with your wash package and even coordinate with your in-bay instruction sign. When paired together, SpectraRay+ and SpectraRay synchronize to flood the wash bay with red, magenta, blue and green creating an ultimate light show that customers won't forget!

G&G INDUSTRIAL LIGHTING

Make your wash unforgettable! G&G ColorWash® integrates with your Washworld equipment to create dynamic light shows that highlight every stage of the wash process. It can be programmed with SpectraRay and SpectraRay+ to coincide with your wash packages and in-bay signage. The plug-and-play system makes installation and maintenance quick and easy. From eye-catching holiday shows to nighttime curb appeal, ColorWash combined with SpectraRay and SpectraRay+ turns your site into a revenue-generating spectacle—keeping members hooked and new customers rolling in!



HEAVY DUTY PUMP STATION

Washworld's Profile Apex Pump Station features a poly tank with electronic fill valve and capacitive level sensor, direct feed solutions system for touch-free presoaks with electronic air regulator, CAT 3535 pump complete with remote oil drain kit, leveling feet, easy tilt wiring access panel and easy access to all serviceable components.



STANDARD FEATURES


- Space saving design, simple installation, easy to maintain
- Heavy duty powder coated frame utilizes proven protective primer
- Cat 3535 Pump with deluxe oil change kit allows easy access for service
- One piece rotationally molded corrosion proof MDPE tank
- 4 Pre-soak injectors (2 top arch and 2 side arches)
- Low water level sensor to protect high pressure pump
- High level capacitive sensor, eliminates mechanical float valve
- Electronic fill valve, software controlled to extend valve life and overflow protection
- Resource conservation system lowers water consumption

OPTIONAL FEATURES

- Reclaim Adapter - for use with high pressure option
 - Plumbing inlet for Cat pump
 - Check valve installed in fresh water tank
 - Electronic signal control output for external reclaim system
- Available in different voltages
 - 208/230 (60 Hz)
 - 380/415 (50 Hz)
 - 460 (60 Hz)
 - 575 (60 Hz)
- Sound reduction kit

MEDIUM PRESSURE SDS

Profile Apex's wall mounted stainless steel solution delivery panel is built with high quality materials and built to last. The Solution Delivery System comes loaded with standard features such as direct feed solutions system, programmable dual low-pressure inlet (hot and cold incoming), stainless steel chemical manifold, electronic air regulators and Flex Pass dual application system. The solution delivery pump is wall mounted utilizing its own stainless steel bracket.



STANDARD FEATURES

- Wall mounted stainless steel panel
- Wall mounted medium pressure solution delivery pump
- 8 stainless steel / composite direct injectors
- Flex Pass® dual application system has the ability to apply 2 different product applications at the same time
- Direct feed solutions system provides more control
- Stainless steel chemical manifold
- Stainless steel / composite direct feed chemical delivery system

OPTIONAL FEATURES

- Tri-Color Foam application system
- Spot free re-pressurization pump
- Foam 'n Flow® application system
- High and low pressure blow down
- Extended solution delivery (ESD) including Bug A'Salt™ technology, tire wheel injector and 2 additional applications
- Big Shot™ chemical tire application

IN - BAY EQUIPMENT PACKAGE

For locations without an equipment room, the In-Bay equipment package comes with the Pump Station that offers the same cutting-edge technology incorporated in a space saving design to be located directly in your wash bay. Featuring a one piece heavy duty frame, stainless steel bulk head manifold for incoming and outgoing supply lines. Removable non corrosive ABS panels for the front, back, sides and top keep direct water spray and debris out. It includes an easy access port for maintenance without removing the panels. The standard UCC is replaced with a stainless steel cabinet, and a hinged water resistant, clear polycarbonate HMI cover. The In-Bay Equipment Package is designed for long life in even the harshest of conditions.



STANDARD FEATURES

- Simple to install, space saving design: 37"H x 96"L x 26"D
- Deluxe cover package with enclosed base protects equipment and looks great in your bay
- Removable panels allow for complete access and easy maintenance
- Heavy duty powder coated frame utilizes proven protective primer
- Cat 3535 Pump with deluxe oil change kit allows easy access for service
- 8 stainless steel / composite direct injectors, 4 pre-soak injectors (2 top arch, 2 side arches)
- One piece rotationally molded corrosion proof MDPE tank
- Stainless steel top feed and discharge manifold
- Low water level sensor to protect high pressure pump
- High level capacitive sensor, eliminates mechanical float
- Electronic fill valve, software controlled to extend valve life and overflow protection
- Flex Pass® dual application system has the ability to apply 2 different product applications at the same time
- Direct feed solutions system provides more control
- Stainless steel chemical manifold
- Stainless steel / composite direct feed chemical delivery system

OPTIONAL FEATURES

- Tri-Color Foam application system
- Foam 'n Flow application system
- Built in spot free re-pressurization system
- High and low pressure blow down
- Extended solution delivery (ESD) including Bug A'Salt™ technology, tire wheel injector and 2 additional applications
- Reclaim system adapter kit
- Built in high capacity 12kw electric water heater
- Big Shot™ chemical tire application

PROFILE® APEX STANDARD FEATURES - QUICK LIST

IN-BAY WALL MOUNT SYSTEM - STAINLESS STEEL

- Stainless steel travel rails (34' 0" overall length)
- Stainless steel wall mounting hardware
- Floor mounted blue reflectors for visual guidance

OVERHEAD CARRIAGE AND TROLLEY FRAME - LASER CUT STAINLESS STEEL

- High gloss composite wash carriage and side wash media covers with blue LED accent lighting on entrance carriage cover
- Dual 10" long red and green LEDs mounted on entrance cover
- Variable frequency controlled belt drive carriage and trolley movements
- VS²® (Vehicle Sizing System)
- DSP (Digital Surface Profile) technology
- Composite energy chain for electrical and solution distribution
- Super soft blue polyethylene foam wash media (side and top)
- Clean Rinse System - Wash media cleaning and lubricating system
- Stainless steel carriage, climate proof motors and gearboxes
- Mirror detailer - Cleans both sides of mirrors in a single pass
- Side brush exchange

HEAVY DUTY PUMP STATION

- Space saving design, simple installation, easy to maintain
- Heavy duty powder coated frame utilizes proven protective primer
- Cat 3535 Pump with deluxe oil change kit allows easy access for service
- One piece rotationally molded corrosion proof MDPE tank
- 4 pre-soak injectors (2 top arch and 2 side arches)
- Low water level sensor to protect high pressure pump
- High level capacitive sensor, eliminates mechanical float valve
- Electronic fill valve, software controlled to extend valve life and overflow protection

SOLUTION DELIVERY SYSTEM (SDS) / WALL MOUNTED STAINLESS STEEL PUMP PANEL

- Wall mounted stainless steel panel
- Wall mounted medium pressure solution delivery pump
- 8 stainless steel / composite direct injectors
- Flex Pass® dual application system has the ability to apply 2 different product applications at the same time
- Direct feed solutions system provides more control
- Stainless steel chemical manifold
- Stainless steel / composite direct feed chemical delivery system

DOUBLE BARREL WITH ADJUSTING SIDE ARCHES

- Dual side manifolds (low pressure and high pressure)
- DSP technology enables the Double Barrel side arches to adjust for various vehicle surfaces
- 14 VeeJet nozzles (7 on each side) for applying low pressure pre-soak functions
- 26 zero degree rotating turbo nozzles (13 on each side) are utilized for high pressure

DOUBLE BARREL CONTOURING OVERHEAD ARCH

- Dual overhead manifolds (low pressure and high pressure) for solution applications, high-pressure cleaning and rinsing
- DSP technology is the advanced method of reading a vehicles contour to allow the arch to stay perpendicular to the vehicles surface and prescribed distance from the vehicle
- 10 VeeJet nozzles for applying low pressure pre-soak functions to all vehicle surfaces
- 16 top zero degree rotating turbo nozzles are utilized for high pressure

ULTIMATE CONTROL CABINET

- Electrical control panel 208VAC (VFD controls on seven motors)
- Washview® HMI On-Site control interface - Complete on-site programming and diagnostic capability
- Wash activation buy-up compatibility
- Comprehensive integrated notification system
- In-bay voice module to communicate Apex actions to customer
- In-bay temperature monitoring system
- Waterproof hand held RF remote control for manual movement and machine functions
- Up to 16 wash packages can be saved and quickly copied to current wash packages
- Auto home feature

PROFILE® APEX OPTIONAL FEATURES - QUICK LIST

SYSTEM OPTIONS

- 30 HP (6 - 5 HP motors) On-Board Dryer
- 40 HP (4 - 5 HP motors and 2 - 10 HP motors) On-Board Dryer
- In-bay horizontal pump station with composite covers and in-bay stainless steel UCC
- UCC power conversion kit (converts standard UCC for use with 240 VAC 3 phase 60 Hz incoming power supply)
- Free standing frame (stainless steel or powder coated)
- Wash bay stop / backup loading eye pedestal mounting kit - Free standing frame or non-standard bays
- E-chain supply passenger side / right side while entering the bay
- E-chain supply driver side / left side while entering the bay

WASH OPTIONS

- Undercarriage and Rocker Panel Blaster - 11 Stainless steel nozzles; 3 on the undercarriage and 4 on each rocker panel blaster
- Power Tower Wheel Cleaner® - 4 Rotating nozzles per tower - Available with or without blue LEDs
- Big Shot™ - Chemical tire application
- SpectraRay™ - 4,528 LEDs (red, magenta, blue and green) - Light show during the wash process or while idle
- SpectraRay+™ - 5,568 LEDs (red, magenta, blue and green) - Mounting options: wall or pedestal mount
- Touch or Touch-Free Power Wheel Detailer™
- Primary HS / Washview® MOBILE - High speed DSL or cable Internet connection capability - Internet access without a static IP address
- Secondary HS / Washview® MOBILE - Additional high speed DSL or cable Internet connection at same location for multi-bay sites
- Tri-Color Foam application system - Both entrance and exit
- Foam n' Flow® application system
- Extended Solution Delivery 1 Includes: Bug A'Salt manifold, plus 2 additional applications
- Extended Solution Delivery 2 Includes: Bug A'Salt manifold, tire/wheel, plus 2 additional applications
- Medium pressure R.O. pump (13 GPM @ 110 psi) includes wall mount bracket and motor starter
- Spot free (R.O.) reject water reclaim system
- Custom voice option for in-bay voice module
- Premium door controls - Includes eyes
- Ultimate door controls - Includes eyes
- Blow down - Protects against hose and major component damage during freezing temperatures
- Custom graphics
- Custom wash media colors

WATER TREATMENT

- Water softener configuration for every need
- Reverse osmosis/spot free systems by Washworld
- Velocity Water Works & PurClean reclaim systems

SIGNAGE OPTIONS

- Stainless steel 12V LED individual signs and sign packages
- Fiberglass back-lit 24V LED individual signs
- Custom verbiage sign choices
- Countdown timers
- Clearance signs



PROFILE® APEX SPECS

PROFILE APEX WALL MOUNT WASH BAY DIMENSIONS*

	OPTIONS	PREFERRED	*MINIMUM	MAXIMUM
HEIGHT* STANDARD & 30 HP OBD	14' 8" - 16' 9" Bay Widths 16' 9" - 18' 0" Bay Widths	12' (3658mm) 12' (3658mm)	11' (3353mm) 11' 4" (3454mm)	N/A
HEIGHT* 40 HP OBD ONLY*	15' 4" - 16' 9" Bay Widths 16' 9" - 18' 0" Bay Widths	12' (3658mm) 12' (3658mm)	11' 6" (3505mm) 11' 10" (3607mm)	N/A
WIDTH*	Without On-Board Dryer With On-Board Dryer	16' (4877mm) 16' (4877mm)	14' 8" (4470 mm) 15' (4572 mm)	18' (5486mm) 18' (5486mm)
LENGTH*	Without Dryer Dryer With Covers	40' (12192mm) 45' (13716mm)	37' 4" (11379mm) 41' 6" (12649mm)	N/A

*NOTE: Minimum dimensions are from nearest inside obstructions entrance to exit e.g., door tracks, counterweights, etc. Add in additional length for these items.

PROFILE APEX FREE STANDING FRAME DIMENSIONS*

	OPTIONS	PREFERRED	*MINIMUM	MAXIMUM
HEIGHT* STANDARD & 30 HP OBD	11' 6" (3505mm) (Frame)	12' (3658mm)	11' 8" (3556mm)	N/A
HEIGHT* 40 HP OBD ONLY*	12' (3658mm) (Frame)	12' 6" (3810mm)	12' 2" (3708mm)	N/A
WIDTH*	15' 8" (4775mm) (Frame)	16' 6" (5029mm)	15' 8" (4775mm)	N/A
LENGTH*	Without Dryer Dryer With Covers	40' (12192mm) 45' (13716mm)	37' 4" (11379mm) 41' 6" (12649mm)	N/A

*NOTE: Minimum dimensions are from nearest inside obstructions entrance to exit e.g., door tracks, counterweights, etc. Add in additional length for these items.

PROFILE APEX MINIMUM UTILITY REQUIREMENTS

Does not include options or other equipment requirements

Water:25 GPM @ 35 psi (94.6 l/m @ 2.41 bars)
Air:100 psi @ 13 SCFM (6.89 bars @ 311 l/m)
Electrical:208/230 VAC, 3 PH, 60 Hz (5-wire, three phase with neutral and ground)

VOLTAGE	UCC CABINET	PROFILE HIGH PRESSURE PUMP STATION	EACH DRYER MOTOR		ADD FOR EACH ON-BOARD DRYER MOTOR (6 TOTAL) 5HP
208 VAC	54 Amps	73 Amps	10 HP 27 Amps	15HP 40 Amps	13.7 Amps
230 VAC	49 Amps	62 Amps	10 HP 24 Amps	15HP 35 Amps	12.4 Amps

*NOTE: Specifications Subject to Change Without Notice. The decibel level of the dryer (measured at 1.6 meters from the floor and 1 meter from the surface) is 94dB. The decibel level of the pump station measured at 1.6 meters from the floor and 1 meter from the surface) is 84dB for high pressure and 72dB for low pressure. Decibel levels are impacted by surrounding materials and conditions therefore will vary.

ON - BOARD VEHICLE DRYING SYSTEM

Washworld Profile Apex On-Board Vehicle Drying Systems provide controlled and consistent drying which results in greater customer satisfaction. The On-Board System moves together with the wash carriage while the customer's vehicle remains stationary for consistent drying. Where wash bay space is limited or for noise abatement, the On-Board Drying System is the answer!



40 HP OPTIONAL ON-BOARD DRYER

- Consistent, controlled touch-free drying
- Producers are constructed from stainless steel, composites and aluminum with welded impellers
- Powder coated aluminum inlet cone and producer back plate / motor mount
- Stainless steel inlet / outlet screens
- 6 producer configuration - (4) 5 HP aluminum / composite producer housing (sides), (2) 10 HP aluminum producer configuration (top)
- Energy efficient, space saving design
- Totally enclosed fan cooled industrial 5 HP and 10 HP motors
- Pre-wired and assembled energy chain for power supply
- On-Board drying process can initiate in either the front or rear of vehicle and can be programmed to run multiple drying passes
- On-Board Dryer can be programmed to continue operation in a fixed position as the vehicle exits for additional drying
- cETLus listed, CE compliant

30 HP OPTIONAL ON-BOARD DRYER

- Consistent, controlled touch-free drying
- Producers are constructed from stainless steel, composites and aluminum with welded impellers
- Powder coated aluminum inlet cone and producer back plate / motor mount
- Stainless steel inlet / outlet screens
- 6 producer configuration
- Energy efficient, space saving design
- (6) 5 HP aluminum / composite producer housing (sides and top)
- Totally enclosed fan cooled industrial 5 HP motors
- Pre-wired and assembled energy chain for power supply
- On-Board drying process can initiate in either the front or rear of vehicle and can be programmed to run multiple drying passes
- On-Board Dryer can be programmed to continue operation in a fixed position as the vehicle exits for additional drying
- cETLus listed, CE compliant

OPTIONS

- Stagger start motor control center
- VFD - Variable frequency drive motor starter control center
- Sound reduction package
- Available in international voltages, including 380-415/50 Hz & 575/60 Hz
- Center producer shut off kit (for open bed trucks)

HIGH VELOCITY® VEHICLE DRYING SYSTEM

The Washworld High Velocity® Free Standing and Wall Mount Vehicle Drying Systems incorporate proven energy efficient air producer designs. All of that power wrapped in our optional dryer image package make your wash stand out from your competitors... and keep your customers coming back for more!



STANDARD FEATURES

- Safe touch-free drying
- All aluminum, stainless steel and HDPE construction with welded impellers
- Stainless steel inlet / outlet screens
- Noncorroding HDPE producer housings
- Completely adjustable producer housings for enhanced drying coverage
- Stainless steel mounting hardware
- Energy efficient industrial 7.5 HP, 10 HP, or 15 HP TEFC motors



*Shown with blue LED dryer cover lighting and LED wash instruction signage

OPTIONAL FEATURES

- Aluminum cross beam and brackets for interior wall mount
- Powder coated aluminum frame for exterior (building face) wall mount or for interior / exterior (free standing) floor mount
- Energy conserving dryer shut-off kit
- Center producer shut off kit - When passing over the bed of a pickup truck contents of the truck bed aren't affected by the center dryers
- Dryer image package (front / rear covers)
- Custom graphics
- Blue LED dryer cover lighting
- Dryer cover with LED wash instruction signage
- LumenDry™
- LED countdown timer with stand or wall mount
- Dryer motor starter panel with stagger start controls
- VFD - Variable frequency drive motor starter control center
- Available in international voltages, including 380-415/50 Hz & 575/60 Hz
- Sound reduction package
- Elephant trunks
- Air knives
- Producer swivel plates



HIGH VELOCITY OSCILLATING NOZZLE

- Performance enhancing
- Available on single and dual nozzle dryer producers
- Pneumatic cylinder controlled, no in-bay wiring, fewer moving parts
- Stainless steel diverter gate (dual gate on a single producer, quad gate on a dual producer)
- Airflow channeled in a 50 degree sweeping motion




Numerous dryer configurations available. Contact Washworld today for more information!




Standard Arch
3 Producers



Standard Arch
4 Producers



Standard Arch 4
Producers, Dual Nozzle,
E-Trunks w/ Brackets



Standard Arch
5 Producers,
E-Trunks w/ Brackets



Interior or Exterior
Wall Mount



Progressive
Drying System



12V SIGNS

Washworld's 12V LED signs are fabricated from stainless steel with adjustable mounting brackets. The stop / drive forward sign is available with or without wash progress, which informs the customer of the estimated remaining wash time.

Easily inform your customers whether your car wash is open or closed. The open/closed status changes automatically based on the wash ready/out of service signal from the car wash equipment.

The white 8 panel and 10 panel LED signs are available with a protectant panel, Tri-Color Foam panel or can be fully customized to match your site's branding. The LEDs can be located on either the left or right side of the panel to accommodate your wash bay needs.

24V SIGNS

Washworld's 24V signs have a fully LED back-lit silver face with a white fiberglass housing. The 8 panel LED signs are available with or without the Tri-Color Foam panel.

COUNTDOWN TIMERS

Washworld's 24V countdown timers clearly inform the customer of the remaining dryer time. They are available as wall mounted or pedestal mounted. The countdown timers can be fabricated from stainless steel or a white fiberglass housing with a 2 digit LED display. Customizable options available upon request.

CLEARANCE SIGNS

Keep your customers informed of maximum overhead clearance when entering your car wash. Washworld's composite clearance signs are available non-lit or back lit with energy efficient LEDs. The sign face is customizable to compliment the site's branding. The HDPE color comes standard in blue, but is available in custom color options: red, yellow, green, gray and black. Clearance signs have additional mounting options that include hanging or ground mounted to fit the site's needs. The ground mounted option is powder coated white for durability and includes a breakaway feature.

WATER TREATMENT

STANDARD FEATURES

- Systems from 60,000 to 600,000 grain capacity (twin alternating)
- Twin alternating systems provide continuous soft water 24/7
- Simple, fully programmable controller maximizes efficiency and reduces operating costs
- Clack valves
- Noryl® composite valve body eliminates corrosion
- Professional series resin tanks
- PVC hub and lateral distribution system
- Brine tanks sized to match system requirements
- Retains custom program settings in the event of power interruption
- Electronic control interlock for multiple tank synchronization
- Incoming operating water - pressures from 30 - 100 psi
- Incoming operating water temperatures from 35°F-100°F
- Space saving footprint
- cETLus listed, CE compliant

OPTIONAL FEATURES

- Iron filtration
- Custom, tri-plex or over-sized systems to meet your specific site needs

WATER SOFTENERS



Washworld's Water Wise Reverse Osmosis (R.O.) system is fully tested and manufactured for maximum efficiency. The unit features an activated carbon pre-filter tank with programmable automatic backwashing and thin-film, high-efficiency membrane in stainless steel housings. The system also includes continuous electronic totally dissolved solids monitoring and can be floor standing or wall mounted. Available in sizes of 2,400 GPD, 4,800 GPD, 7,200 GPD, and 9,600 GPD and typically available for shipment within a week!

STANDARD FEATURES

- 2400, 4800, 7200 or 9600 GPD (gallons per day) systems (Based on 77°F incoming water supply)
- Stainless steel membrane housing
- Stainless steel frame
- All units are floor or wall mountable
- Activated carbon pre-filter tank with programmable automatic backwashing
- 4"x 40" thin film high efficiency membranes
- Large diameter, easy to read inlet, pump and membrane pressure gauges
- Permeate (product) and concentrate (reject) flow meters
- Pre-plumbed water test port
- Automatic inlet water shut-off valve
- Easily replaceable 2.5" x 20" cartridge style pre-filters on all systems
- VROC digital R.O. control
- Audible and visual alerts/alarms
- Continuous electronic TDS (total dissolved solids) monitoring with audible alarm with adjustable setting
- Automatic membrane flushing
- Low pressure automatic restart
- cETLus listed, CE compliant

OPTIONAL FEATURES

- Water storage tanks (UV rated)
- Re-pressurization pumps with mounting brackets



CUSTOMER SERVICE

Washworld takes our commitment to customer satisfaction very seriously and do our utmost to help car wash owners around the world run successful businesses. We offer expertise to every car wash owner from initial business planning, site selection, equipment layout, renovations and upgrades to 24/7 technical support and advice after the sale. Our service priority means no customer is ever just a number.




FREE ONLINE TECHNICAL TRAINING

The Washworld Customer Care Program leads the industry in customer service. Washworld takes that commitment to customer satisfaction very seriously by offering Free Online Technical Training to improve operator proficiency. The training is presented by several Washworld technicians and engineers who have years of experience with Washworld equipment as well as the car wash industry as a whole. Some of the items covered in this comprehensive course include wash components and their function, system installation, quick reference start up, routine maintenance, Washview® programming and troubleshooting.



TECHNICAL SUPPORT

Washworld is known for our world class customer service. With over 100 Distributors worldwide and a Technical Support Department, we can assist operators day or night, 24/7. Utilizing Washworld's exclusive Washview® Remote, you and our technical professionals are able to track your wash site performance from anywhere in the world often preventing the need for an on-site service call. Best of all, there is never a charge for Washworld technical support after the sale. At Washworld, we stand behind our vehicle wash systems and strive to provide the assistance you, our customer, need so that you're never alone. This is yet another example of our motto, "Our World Revolves Around Your World" in action.



REPLACEMENT PARTS

Keeping your vehicle wash system running is our priority. Pictorial parts books are available online for easy identification of components and part numbers. Need help? With over 100 Distributors worldwide, contact your local Washworld Distributor or Washworld's 24/7 technical support team for assistance!

*Washworld backs our equipment with a written warranty,
which sets the bar in the car wash industry. Don't take our
word for it, ask any Washworld customer!*

WASHWORLD EQUIPMENT LIMITED WARRANTY

Washworld Inc., a Wisconsin Corporation ("Washworld") warrants to the original purchaser of Washworld car wash equipment that the equipment will be free from defects in materials and workmanship for a period of 400 days from date of shipment, with the exception of the Cat Pump which is warranted for two (2) years. Claims under this warranty must be asserted in writing to Washworld within 10 days of discovery or before the end of the applicable warranty, whichever occurs first, and must follow the Washworld "RMA" (Returned Materials Authorization) process.

Any component or part alleged to be defective in materials or workmanship shall, at the option of Washworld, be returned with shipping cost prepaid. If upon examination such component or part is found to be defective in workmanship or materials, Washworld, at its option, will either repair or replace such component or part and ship such repaired or replaced component or part via standard ground. Expedited shipping costs (if requested) shall be the responsibility of purchaser. The cost of such replacement or repair (less any labor charges) shall be the exclusive remedy for any breach of any warranty and Washworld shall not be liable to any person for consequential damages for injury or commercial loss resulting from any breach of any warranty. This warranty does not cover any labor installation cost, either with respect to the original equipment or with respect to the repaired or replaced component or part which is found to be defective in workmanship or materials. Washworld does not warrant loss of income, or consequential damages, should there be any, during the time repairs are being made.

This warranty does not apply to damage resulting from components or parts that have been misused, altered, neglected, or not installed, adjusted, maintained, or used in accordance with applicable codes and ordinances and in accordance with Washworld's or manufacturer's recommendations. This warranty does not apply to damage resulting from improper operation or abuse, exceeding the rated capacities of the unit, running foreign particles or non-related solutions through pumps or valves, using acidic solutions, improper installation or maintenance, operational neglect, neglect of manufacturer's recommended maintenance, use of water containing solids in excess of twenty microns in diameter or 2000 PPM, damage caused by customer, unjustifiable nuisance calls or acts of God.

This warranty is in lieu of all other warranties, express or implied, and there are no warranties against infringement, of merchantability, of fitness for a particular purpose, or arising from course of dealing or usage of trade. Washworld shall not be liable for direct, indirect, incidental, special or consequential damages under any circumstances, including but not limited to: damage or loss resulting from inability to use the products, increased operating costs, or loss of sales, lost profits, punitive damages, or any other damages. Compliance with any laws or regulations relating to the sale, location, use or operation of the equipment, or its use in conjunction with other equipment shall be the sole responsibility of the purchaser. The rights and obligations of the parties shall be governed by the laws of the State of Wisconsin.

Washworld reserves the right to change or modify this Limited Warranty at any time without notice.



WASHWORLD

2222 American Blvd.
De Pere, WI 54115

© 2026 Washworld, Inc.

rev.4-2026