



Epson SureColor G9060 DTFilm

- High-speed production direct-to-film (DTFilm) printer
- Efficient operation with single and dual layer output
- 1.6 L ink packs for cost-effective production with minimal waste & mess
- Designed for nonstop production with automated cleaning to reduce downtime
- Continuous white ink recirculation, self-cleaning printhead & capping systems
- Epson UltraChrome DF ink for crisp and bright images with a low tack finish, high stretchability and good wash/UV durability
- Twin-roll flexibility, enabling simultaneous printing of two rolls up to 64" wide
- Supplied with Epson Edge Print PRO and Fiery Digital Factory Epson Production Edition RIP software
- Epson Cloud Solution PORT for enhanced costing, management, service & support
- Comprehensive service cover up to FIVE years, including printheads¹

SureColor G9060 DTFilm

Product Specifications

PRINTING TECHNOLOGY	
Print Engine	Self-cleaning 2.64" PrecisionCore Micro TFP printhead with ink-less nozzle status monitoring & compensation, Variable Sized Dot Technology (VSDT), Precision Dot Technology, optional user-replaceable printheads ²
Configuration	Total nozzles: 9,600 nozzles CMYK: 6,400 nozzles and Wh: 3,200 nozzles
Maximum resolution	1200 x 1200 dpi
Features	Continuous white ink recirculation, ink-less nozzle status monitoring, advanced head cleaning & cap cleaning systems
INK SYSTEM	
Ink type	Epson UltraChrome DF
Supply system	Bulk supply with 1.6 L bags
Configuration	CMYK + White + Maintenance Liquid
PERFORMANCE ³	
Single layer	8.6 ~ 68.8 m ² /hr (White or Colour)
Dual layer	4.3 ~ 34.1 m ² /hr (White + Colour)
MEDIA SUPPORT	
Single film roll	300 ~ 1,625 mm wide, 250 mm max diameter, 2" or 3" core, 45 kg max weight
Thickness	Up to 0.5 mm
Minimum borders	3 mm left & right
Handling	Roll unit, rear mounting
OPERATION	
Control panel	4.3" colour touchscreen
Utility software	Epson Setup Navi & Cloud Solution PORT
Application software	Epson Edge Print PRO (Win 64-bit) Fiery Digital Factory Epson Production Edition
Interface	100/1000 Base-T Ethernet (recommended) & USB
Memory	2 GB
Power consumption	440 W Operating, 70 W Ready, 42 W Sleep
Operational space (W x D)	9.27 m ² (3.95 m x 2.35 m recommended) ⁴
ENVIRONMENTAL	
Operational temp	10 ~ 35°C (20 ~ 25°C recommended)
Operational humidity	20 ~ 80% (no condensation, 40 ~ 60% recommended)
Power supply	240 V, 5 A, 50 Hz - 60 Hz
PHYSICAL	
Printer (W x H x D)	2.95 x 0.85 x 1.61 m, 370kg (no ink)
Printer shipping carton (W x H x D) ⁵	3.3 x 1.1 x 1.1 m (415 kg)

PURCHASE CONFIGURATIONS¹

SCG90601Y	Printer with 1-year onsite warranty
SCG90603Y	Printer with 1-year warranty + 2-year CoverPlus
SCG90605Y	Printer with 1-year warranty + 4-year CoverPlus

OPTIONAL ACCESSORIES

B41CK17401	SD-10 Spectrophotometer
B42B900311	Auto Table for SD-10
C12C941231	Media Edge Guide
YR2G9060	CoverPlus Year 2
YR3G9060	CoverPlus Year 3
YR4G9060	CoverPlus Year 4
YR5G9060	CoverPlus Year 5

CONSUMABLES

C13T57U100	1.6 L Black Ink Pack
C13T57U200	1.6 L Cyan Ink Pack
C13T57U300	1.6 L Magenta Ink Pack
C13T57U400	1.6 L Yellow Ink Pack
C13T57UA00	1.6 L White Ink Pack
C13T57UB00	1.6 L Maintenance Liquid Pack
C13T57Y100	1.6 L Cleaning Liquid Pack
C13T736200	Maintenance kit
C13S210181	Head cleaning set
C13S210182	Cap Station Set
C13S210183	Nozzle Refresh Tool
C13T724000	Replacement reusable waste tank

WHAT'S IN THE BOX⁵

Printer, Stand, Power Cord, a set of CMYKW+Ml 1.6L ink pouches, 1 x Roll Unit, 1 x Bulk Ink Solution, 1 x Reusable 4L Waste Ink Bottle, 1 x Ink charging tool, 1 x Head Cleaning Kit, 1 x Maintenance Kit, Epson Edge Print PRO License, Fiery Digital Factory Epson Production Edition Licence, warranty sheet and Set-Up guide. User manual and software provided via web download.

¹ 1-year standard warranty for non-consumable components, including printheads, using the genuine Epson UltraChrome DF ink. CoverPlus is conditional on activation of Epson Cloud Solution PORT. Please refer to the Epson Australia or New Zealand website for full details.

² To enable the user-replacement printhead feature, the printer must be registered and remain connected to Epson Cloud Solution PORT, and covered under an active CoverPlus plan. Operator is required to complete necessary training.

³ Figures are print speeds achievable with 1,625 mm film. Speeds will vary depending on the film width and print mode setting. Production times will depend on additional factors including image processing, powder application, melting and pressing.

⁴ Additional space will be required if operated with a powder applicator/oven.

⁵ Roll unit, Bulk Ink Solution and Ink are shipped separately to the printer. The DTF process requires powder to be subsequently applied and melted in an oven. A heat press will be required for subsequent transfer onto garments and merchandise.



Touch panel control



Fabric-based head wiper



Advanced cap cleaning

ULTRACHROME
DF INK



Epson Cloud Solution PORT

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and are trademarks of their respective owners; Epson disclaims any and all rights. Specifications are subject to change without notice. Visit www.epson.com.au or www.epson.co.nz for the latest information.

Epson Australia Pty Ltd
Tel: 02 8899 3666
www.epson.com.au

Epson New Zealand
Tel: 09 366 6855
www.epson.co.nz

06/2026

ABN: 91 002 625 783

EPSON