Magnetic Signs Care and Application Guide- All Magnetic Signs Users Must Read!

1) Preparation before applying magnetic signs

Both the vehicle and the back of the sign MUST be CLEAN & DRY.

Check all the edges of the sign for lumps, bumps or damage. A bump on the edge can allow air and moisture under the sign causing it to lift off the vehicle or damage the sign.

2) Applying magnetic signs

Let one edge of the sign contact the vehicle then allow the magnet to naturally contact the vehicle until it is all down. Rub over to make sure it is all down.

3) Precautions

- Care should be taken with all vehicles, in particular metallic and new paint finishes. All surfaces should be checked regularly.
- Re-painted surfaces should be avoided for around 3 months and should be polished before the sign is fitted.
- Remove signs frequently to allow the natural sun light to evenly bleach the vehicle.
- Magnetic signs on bonnets are not recommended due to the heat, curvature and air flow.
- DO NOT apply to FROZEN, FROSTED, WET, DIRTY or HOT vehicles.
- Avoid leaving the signs in extreme sunlight for prolonged periods whilst on or off the vehicle.
- When signs are fitted do not exceed legal speed limit (signs are tested up to 70mph but this does not take into account head winds, wind speed and air turbulence).

5) Maintenance

Magnetic sign should be kept as dry as possible

- Remove signs DAILY after rain and wipe dry. Moisture collecting behind the sign can ingress into the material and cause blistering if left unchecked.
- Remove during sleet or snowy weather.
- Remove the signs at least once a week. Clean and dry both the magnetic side and the surface of the vehicle.
- Remove the signs daily during heavy rain.
- Remove Road film and any dirt before applying or re-applying the sign.
- Wash signs with warm water and mild detergent. Avoid cleaning fluids and solvents.
- Remove signs from vehicle during hot and very sunny periods.

5) Storing

Store signs flat in a clean environment.

Do not put heavy objects on or leaning up against signs whilst in storage.

During cold weather allow the sign to uncurl in a warm atmosphere before use.

Store at room temperature out of direct sunlight

THERE IS NO WARRANTY EXPRESSED OR IMPLIED AGAINST LOSS OF SIGN OR DAMAGE TO VEHICLE SURFACES, AS THE SUPPLIER HAS NO CONTROL OVER HOW SIGNS ARE CARED FOR, ALTERED, STORED, AND/OR USED, OR THE SURFACE TO WHICH THE SIGNS ARE APPLIED. THERE IS NO WARRANTY OFFERED FOR FAILURE OF A PRODUCT OLDER THAN 12 MONTHS.