

10 Golden Crescent, BALLARAT VIC 3350 P: 03 5339 4859 | E: info@harrybilt.com.au F: 03 5339 9419 | W: www.harrybilt.com.au









Rail Trailer

Specifications:

- Triple gauge narrow/standard/broad
- Main rails 200 x 100 RHS. Width between rails 1100mm
- · Twist function on one end
- · 4 x compliant fully insulated wheels
- 4 x wheel brakes with fail safe breakaway braking system
- 50mm tow coupling 1 end to enable "Trailer to Machine" hook up with no personnel in the crush zone
- Drawbar with Ringfeder type eyes on each end
- 4 x fold down lifting points complete with 4 drop lifting chains
- 6 x post pockets on out-side of chassis rails to suit 75 x 75 SHS
- 4 x posts supplied
- · Operation & Maintenance Manual included.

Options:

- Sleeper Top or Flat Top
- Tipper bodies
- Fold down ramps for loading bobcat or excavator etc
- Regulation Lighting
- Container twist locks to suit ballast bins, containers etc.

Variants Available:

- · Light Weight
- 3 Metre
- 4 Metre
- 5 Metre
- 6 Metre
- Skeleton 2 Wheel
- Skeleton 4 Wheel





Work Lighting

Additional Drawbars



Front & Rear Directional Lighting

Related Products







Bullant



Fork Grab Rail Threader Platypus

Ballast Sweeper