



Centipede Undercutter / Ballast Remover

A time saver for any rail maintenance team, the Centipede - Undercutter / Ballast Remover removes spoil fast and without fuss.

It features:

- Hi-torque radial piston Poclain motor
- Replaceable double sided BIS80 wear plates
- Bolt on hitch options
- Low profile hitch position
- Replaceable bump pad to avoid sleeper damage
- Super heavy duty chain:
 - Highly wear resistant components
 - Replaceable Tungsten Carbide tips
 - Innovative rakers and tip position on chain for efficient spoil removal

	1.5 m (5 ft)	2.4 m (8 ft)	2.7 m (9 ft)	3 m (10 ft)	3.6 m (12 ft)
Tare Mass	640 kg (1411 lbs)	740 kg (1631 lbs)	800 kg (1764 lbs)	1120kg (2469 lbs)	1250kg (2756 lbs)
Height	610 mm (2 ft)	610 mm (2 ft)	610 mm (2 ft)	710mm (2 ft 3 in)	710mm (2 ft 3 in)
Width	500 mm (1 ft 7 in)	500 mm (1 ft 7 in)	500 mm (1 ft 7 in)	500mm (1 ft 7 in)	500mm (1 ft 7 in)
Length	2.45 m (8 ft)	3.23 m (10 ft 7 in)	3.53 m (11 ft 6 in)	4.10m (13 ft 5 in)	4.35m (14 ft 3 in)
Cutting Length	1.83 m (6 ft)	2.60 m (8 ft 5 in)	2.90 m (9 ft)	3.28m (10 ft 7 in)	3.60m (11 ft 8 in)
Motor Flow Rate	45-120 L/min (12-32 gpm)	45-120 L/min (12-32 gpm)	45-120 L/min (12-32 gpm)	120-160 L/min (32-42 gpm)	120-160 L/min (32-42 gpm)
Recommended Flow Rate	160 L/min (42 gpm)	160 L/min (42 gpm)	160 L/min (42 gpm)	185 L/min (49 gpm)	185 L/min (49 gpm)

