



**DECLARATION OF PERFORMANCE**  
**TG/CE-010CL-A000-B**  
**CONSTRUCTION PRODUCT REGULATION 2011**

We hereby certify that the glass as stipulated below complies with the relevant provisions of the E.C. construction product regulation & the requirement of:

Product Identification:

10mm Clear Annealed Glass

Type / Batch / Serial Number:

Each glass has its own identification label attached including bar code for traceability.

Intended use:

Glass in building — Thermally toughened soda lime silicate safety glass.

Manufacturer:

Toughglaze (UK) Ltd  
Unit 1, Badger Rise, Ridgmont, Brogborough, MK43 0YL

System Assessment:

System 2+

Harmonised Standard No:

EN 12150-2:2004

Chandos Park Industrial Estate, 10 - 14 Chandos Road, North Acton, London, NW10 6NF

ToughGlaze (UK) Ltd

General Enquiries

Quotations / Processing

Accounts

W [www.toughglaze.com](http://www.toughglaze.com)  
E [info@toughglaze.com](mailto:info@toughglaze.com)

T +44 (0) 208 838 4400  
F +44 (0) 208 838 3311

T +44 (0) 208 838 4400  
F +44 (0) 208 838 3322

T +44 (0) 208 838 6615 / 6110  
F +44 (0) 208 963 0666

### Declared Performance:

Light:			Energy:		
Transmittance	LT	87%	Direct Transmittance	ET	73%
	UV %	49%	Reflectance	ER	7%
Reflectance Out	LR Out	8%	Absorptance	EA	21%
Reflectance In	LR in	8%	Total transmittance	g	77%
<b>Performance Code:</b>			Shading Coefficient Total	0.89	
U <sub>g</sub> – value/Light/Energy	5.6 / 87 / 77		Shading Coefficient Shortwave	0.83	
Ra	97		Sound Reduction	R <sub>w</sub> (C;C <sub>tr</sub> ) dB	33 (-2;-3)
			Thermal Transmittance	W/m <sup>2</sup> K	5.6
Additional Values:					
Bullet Resistance	EN 1063	NPD	Burglar Resistance	EN 356	NPD
Explosion Resistance	ISO 16933	NPD	Pendulum Body Impact Resistance	EN 12600	NPD
Load Resistance (mm)	10		Resistance to Temperature	40	
Reaction to Fire	EN 13501	A1	Differentials (K)	40	
Resistance to Fire	EN 1364	NPD	External Fire Performance	NPD	
<p>* The values of some of the characteristics are stated as NPD which is for “No Performance Determined”.</p> <p>* Calculations are made according to EN 410 and 673/12898.</p> <p>* All data and values are subject to tolerances and ToughGlaze (UK) Ltd Terms &amp; Conditions.</p> <p>* Notified Body: BSI (No 0086).</p> <p>* BSI report (Ref 2370/7948560).</p>					

Signed for and on behalf of manufacturer by:

---

Mr. Bhavik Varsani  
(Managing director)



Location: London, UK

Date: Wednesday, 07 August 2019

Chandos Park Industrial Estate, 10 - 14 Chandos Road, North Acton, London, NW10 6NF

ToughGlaze (UK) Ltd

General Enquiries

Quotations / Processing

Accounts

W [www.toughglaze.com](http://www.toughglaze.com)  
E [info@toughglaze.com](mailto:info@toughglaze.com)

T +44 (0) 208 838 4400  
F +44 (0) 208 838 3311

T +44 (0) 208 838 4400  
F +44 (0) 208 838 3322

T +44 (0) 208 838 6615 / 6110  
F +44 (0) 208 963 0666