



DECLARATION OF PERFORMANCE
TG/CE-175CL-TOLA-B
CONSTRUCTION PRODUCT REGULATION 2011

We hereby certify that the glass as stipulated below complies with the relevant provisions of the E.C. construction product regulation & the requirement of:

Product Identification:

17.5mm Clear Toughened Acoustic Laminated Glass

Type / Batch / Serial Number:

Each glass has its own identification label attached including bar code for traceability.

Intended use:

Glass in building — Clear Toughened and laminated safety glass.

Manufacturer:

Toughglaze (UK) Ltd
Unit 1, Badger Rise, Ridgmont, Brogborough, MK43 0YL

System Assessment:

System 2+

Harmonised Standard No:

EN 14449:2005

Declared Performance:

Light:			Energy:		
Transmittance	LT	83%	Direct Transmittance	ET	59%
	UV %	0%	Reflectance	ER	6%
Reflectance Out	LR Out	8%	Absorptance	EA	35%
Reflectance In	LR in	8%	Total transmittance	g	67%
Performance Code:			Shading Coefficient Total		0.77
U _g – value/Light/Energy	5.2/83/67		Shading Coefficient		0.67
Ra	95		Shortwave		
			Sound Reduction	R _w (C;C _{tr}) dB	41(-1;-3)
			Thermal Transmittance	W/m ² K	5.2
Additional Values:					
Bullet Resistance	EN 1063	NPD	Burglar Resistance	EN 356	P4A
Explosion Resistance	ISO 16933	NPD	Pendulum Body Impact Resistance	EN 12600	1(B)1
Load Resistance (mm)		17.5	Resistance to Temperature Differentials (K)		40
Reaction to Fire	EN 13501	NPD	External Fire Performance		NPD
Resistance to Fire	EN 1364	NPD			
<p>* The values of some of the characteristics are stated as NPD which is for “No Performance Determined”.</p> <p>* Thermal and optical calculations as per EN 410 and 673/12898.</p> <p>* All data and values are subject to tolerances and ToughGlaze (UK) Ltd Terms & Conditions.</p> <p>* Acoustic calculations as per EN ISO 10140-3/EN ISO 10140-2.</p>					

Signed for and on behalf of manufacturer by:

Mr. Bhavik Varsani
(Managing director)



Location: London, UK

Date: Friday, 27 November 2020

ToughGlaze (UK) Ltd Unit 1, Badgers Rise, Ridgmont, Brogborough, Bedford, MK43 0YL