

# On/Off Test Instructions

Service - Maintenance - Repair  
994-2905



*\*Due to the nature of pool leaks, the measurement of time and water loss must be accurate and specific. Please be sure to record these precisely.*

- Check backwash line and equipment for any obvious leaks.
- Are there any visible tears in the liner? Is there a light in the pool? (lights are frequently culprits for leaks).
- Fill pool to the normal level.
- Mark the skimmer face plate with a pencil at the water level.
- Run the pump for 24 hours and mark the face plate a second time.
- Turn the pump off for 24 hours and mark it a third time.
- Measure the distance between the first mark and the second. Also between the second and the third. Accurate measurements are important. Use a ruler to be as specific as possible.

*Do not allow water level to drop below the skimmer at any point while the pool is running. Damage to the pump may occur if the water level drops too low while the pump is on.*

- This test will help us determine whether water is being lost from the pool itself, or possibly underground plumbing/equipment.

**Evaporation Test -** Place a bucket on the steps of the pool and fill with water. Mark water line. After 24 hours, check water level to determine evaporation rate.

## **Record Water Loss:**

Pump On: \_\_\_\_\_ " Pump Off: \_\_\_\_\_ " Evaporation: \_\_\_\_\_ "

Find us on 

Retail Store is Located at:  
4873 West Spencer Field Road  
Pace, FL 32571

[www.pacepoolandspa.com](http://www.pacepoolandspa.com)