GENERATOR TRANSFER SWITCH ENCLOSURETM RESIDENTIAL & SMALL FARM APPLICATIONS

Catalog# 1005656

100 & 200 Ampere • Single Phase 120/240 Volt

Units are manufactured from galvanized steel, painted gray for durability in harsh environments. The cover is secured with a positive latch, (No Screws Required). Knockouts supplied in the bottom $2\frac{1}{2}$ thru $1\frac{1}{4}$, 3 places.

Knife blade switch. Self cleaning action insures positive connection. Quick make, quick break switch with a positive off position.

HUB SELECTION CHART							
HUB OR TOP CONFIGURATION	CATALOG SUFFIX						
SMALL							
SOLID	Α						
FOR HUB (SM)	В						
HCP (SM)	С						
1 ¼" (SM)	L						
1 ½" (SM)	М						
2" (SM)	N						
2 ½" (SM)	Р						





CATALOG NUMBER	HUB OPENING	MAIN RATING	AUXILIARY RATING	WIRE SIZE CU-AL		AUXILIARY	DIMENSIONS			SHIPPING
				LINE	LOAD	CONNECT.	Н.	W.	D.	WEIGHT
1005773	SMALL	100	100	1/0	1/0	1/0	23	14	8 1/4	30
1005656	SMALL	200	200	250	250	250	27	14	8 1/4	40



Proudly Engineered, Designed, and Manufactured in the U.S.A.