

COMMERCIAL

BIG DOG[®]
— MOWER CO. —

DIABLO

SERIES



DIABLO

AVAILABLE DECK SIZES

52" - 72"



DIABLO ^{MP}

AVAILABLE DECK SIZES

60" - 72"

DIABLO

Heavy-Duty Frame

1.50" x 3" steel tubing frame making it one of the toughest and most durable in its class.

Welded Steel Deck

Durable 7 ga. welded fabricated steel.

Precision Steering

Precision control to help trim and maneuver easily around obstacles. Other brands have sensitive steering arms causing sudden and jerky movements.

Premium Seat

Custom Grammer full suspension seat with sliding adjustment reduces operator fatigue.

Commercial-Grade Power

Vanguard 810cc, KOHLER® Command Pro Engine options backed by 3 year warranty.

Foot Operated Deck Lift

Easily adjust the deck height between 1.5" - 5.5" with your foot.

Easy Serviceability

Flip-up seat pan and removable floor pan and toolless removable pulley covers make maintenance easy and simple.

24" BigBite™ Drive Tires

Provides a smooth ride and enhanced traction.

Commercial-Grade Torque

Power through with Parker unitized 12cc/rev pumps with 15.9ci wheel motors.

7 YEAR RESIDENTIAL WARRANTY
INDUSTRY LEADING LIMITED OR 1500 HOUR

2 YEAR COMMERCIAL WARRANTY
INDUSTRY LEADING LIMITED OR NO HOUR

UPGRADES FOUND ON THE DIABLO MP

DIABLO MP

- **Larger 26" Tires**
- **Larger Transmissions**
Hydro-Gear PY 21cc
- **Additional Horsepower**
Vanguard Big Block
- **Additional Speed**
14 mph vs. 10.5 mph



ACCESSORIES

- 3-Bag Powered Catcher
- BacVac Bagger
- Side Steel Catcher
(Diablo Only)
- Side Mesh Catcher
(Diablo Only)
- Mulch Kit
- Michelin X Tweel Turf Tire
- Michelin X Tweel Turf Caster
- Flex Forks
- Electronic Deck Lift
- Semi-Pneumatic Tire
(13 x 6.5)
- Rear Anti-Scalp Kit
- Light Kit
- Stripe Kit
- Sand Kit
(Diablo MP Only)

7 YEAR **INDUSTRY LEADING LIMITED WARRANTY** OR **1500** HOUR
RESIDENTIAL

2 YEAR **INDUSTRY LEADING LIMITED WARRANTY** OR **NO** HOUR
COMMERCIAL

DIABLO				DIABLO MP	
ENGINE					
Manufacturer	KOHLER® Command Pro / Vanguard 810cc			Vanguard Big Block	
HP	52", 60": 25HP - KOHLER Command Pro 52", 60", 72": 26HP - Vanguard 810cc (Per SAE J1995)			60", 72": 36HP - Vanguard Big Block (Per SAE J1995)	
Displacement	810cc Vanguard 747cc KOHLER			993cc	
Cooling	Air cooled				
Engine Warranty	3 year				
DRIVE SYSTEM					
Type	Dual hydrostatic				
Transmission	Parker unitized 12cc/rev pump and 15.9ci/rev wheel motors			Hydro-Gear® 21cc PY pumps with Parker TG310 wheel motor	
Speed	Up to 10.5 mph			Up to 14 mph	
Parking Brakes	Integrated with steering levers				
DECKS					
Cutting Width	52", 60", 72"			60", 72"	
Cutting Heights	1.5" - 5.5"				
Deck Lift	Foot operated				
Depth	5.5"				
Blades	3				
Blade Length	52": 17.86" 60": 20.5" 72": 23.86"			60": 20.5" 72": 24.5"	
Blade Tip Speed	52": 17,700	60": 18,800	72":18,500	60": 18,600	72":18,500
Spindles	Ductile cast iron with steel shafts and sealed ball bearings				
Drive	Electric PTO clutch				
Construction	7 ga. fabricated with 7 ga. wrappers			7 ga. fabricated 7 ga. wrappers	
Spindle Mounts	Reinforced 7 ga. stamped disc			7 ga. with 7 ga. doubler	
Impact/Trim Areas	11 ga. formed channel with rolled edge				
CONSTRUCTION					
Frame	1.5" x 3" Steel tubing				
Front Axle	Fabricated with tapered roller bearings				
Front Caster Wheels	Tapered wheel bearings and debris cap				
Front Caster Forks	Fabricated 1/2" steel				
GENERAL					
Seat	Custom Grammar full suspension seat, sliding adjustment				
Fuel Capacity	12 gallons				
Cupholder	Yes				
Front Tire	13 x 6.5 - 6				
Drive Tire	52": 24 x 9.5 - 12, BigBite™ 60", 72": 24 x 12 - 12 BigBite			26 x 12 - 12, BigBite	
DIMENSIONS					
Weight	52": 1255 lbs	60": 1306 lbs	72": 1465 lbs	60": 1460 lbs	72": 1590 lbs
Height	47" (72.5" with ROPS up)				
Length	52", 60": 80.2" 72": 84"			60": 89"	72": 93"
Width w/Chute	52": 54.4"	60": 62.4"	72": 75.7"	60": 65.3"	72": 75.3"
Tire Width	52": 51" 60", 72": 54.5"			57"	
Trim Side	52": 0.9"	60": 3.6"	72": 12"	60": 3.4"	72": 8.9"
PRODUCTIVITY*					
Acres Per Hour	52": 5.52	60": 6.36	72": 7.64	60": 6.78	72": 8.14

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

** Specifications are subject to change without notice.