

BX90
SERIES

The Kubota BX Series was built on a simple idea: your property doesn't have one need, so your tractor shouldn't have one purpose.

Kubota was instrumental in building the subcompact market with its first introduction of the BX in 2000. Diesel-powered, 4WD capable and sized to park in the garage, the BX series helps you accomplish chores and projects around your property with one machine.

Clear snow in the winter, till your garden in the spring and mow all summer long. With the right tools, the BX Series helps get the job done no matter the time of year.

The BX Series, brought to you by the #1 Selling Tractor Brand in the USA for 20 years running.*

Because You Can.

* Based on total U.S. unit sales from EDA/UCC equipment transaction data for all tractor classes (Utility Tractor, Utility Loader, Utility TLB and 4WD Ag Tractor) from 01/01/2005 through 12/31/2025.



ONE TRACTOR. EVERY JOB.

The BX Series lives where a riding mower taps out and a full-size tractor is more machine than the job needs. Sub-compact in footprint, serious in capability, it mows, lifts, digs and tills. Powered by Kubota's proven diesel engine and transmission, it's built to tackle a wide range of property maintenance tasks while keeping operator comfort top of mind.



	BX2190	BX2390 Deluxe	BX2690 Premium	BX2390S	BX2690S Premium
Engine Gross Horsepower	19.3	21.6	23.9	21.6	23.9
Power Take-Off Horsepower	15.7	17.2	18.7	17.6	18.7



FIVE MODELS. ONE THAT'S RIGHT FOR YOU.

FEATURES	BX2190	BX2390 Deluxe	BX2690 Premium	BX2390S	BX2690S Premium
Backhoe Equipped				●	●
Cruise Control	○	●	●	●	●
Electronically Controlled Engine			●		●
Engine Start Security			●		●
Foldable ROPS[1]	●	●	●	●	●
Four Wheel Drive	●	●	●	●	●
LCD Display & Jog Dial			●		●
LED Headlights	●	●	●	●	●
Signature LED Headlights			●		●
Loader Valve Equipped	○	●	●	●	●
Mid-PTO	●	●	●	●	●
One-Touch ROPS		●	●		●
Premium Joystick			●		●
Side-by-Side HST[2] Pedals	●	●	●	●	●
3-Point Hitch Position Control		●	●		●
PTO On/Off Switch		●	●		●
Telescopic Stabilizers		●	●		○

● Standard
○ Optional

[1] Roll-Over Protective Structure. [2] Hydrostatic Transmission.



BX BASICS

Features you can expect from every BX.



Side-by-Side HST Pedals

Forward and reverse are right under your toes, so changing direction is a quick motion that feels natural.

Kubota Engineered

With its 3-cylinder engine and HST transmission, the BX series is Kubota engineered from front to rear, making this a dependable sub-compact tractor.

Mid-PTO

Allows connection of mid-mount mowers, front snowblowers and sweepers.

Compact Size

Small enough to park in a standard garage without lowering ROPS. Narrow enough to fit through most garden gates.

Category I 3-Point Hitch

Standardized Category I hitch for universal fitment of rear implements.

LED Lights

Ready to work when you are. Enhanced visibility for long days that start at sunrise and last through sunset.







Above: BX2690 shown with signature LED headlights



THOUGHTFUL UPGRADES THROUGHOUT

Deluxe Models



PTO On/Off Switch

Easily engage and disengage PTO with the push of a button.



3-Point Hitch Position Control

Allows repeatable height and depth accuracy during 3-point operation.



Telescopic Stabilizers

Control implement sway with the pull of a pin and make attaching rear implements easier.

Premium Models *(Including Deluxe Upgrades)*



Electronically Controlled Engine

Provides more precise fuel control, improved emissions, and a more refined operating experience.



Premium Loader Joystick

Ergonomic joystick with three integrated buttons, which allows for an instant RPM boost via Throttle-Up as well as optional live 3rd function hydraulics.



LCD Display

Provides a clear view of machine information in direct sunlight and low light situations. Access engine speed presets, fuel consumption, engine vitals, maintenance information, engine start security and more with jog dial navigation.



DOESN'T CUT CORNERS. ONLY GRASS.

The BX Series mid-mount mower is engineered to perform like the machine it's attached to. It's precise, efficient and built for operators who expect professional results.

Fabricated Deck Design

54" and 60" options feature a fabricated welded deck design, built for long term durability.

Easy Adjustments

On deluxe and premium models, adjust the deck cutting height right from the operator platform with an improved left hand console adjustment.

Swift-Mount™ Drive Over Deck

The Swift-Mount™ system with its standard auto-coupling PTO driveline allows for quick and easy install and removal without the need for tools.

Cutting Width		48-in.	54-in.	60-in.
Tractor Compatibility		BX2190	BX2190, BX2390, BX2390S, BX2690, BX2690S	
Fabrication		Stamped	Fabricated	
Swift-Mount Drive Over Linkage		–	Optional	
Mulch Kit		Optional		
Grass Collector	*in*	Optional		
Deck Thickness	*ga*	11	10	9
Discharge		Side Discharge		
Number of Blades		3		
Cutting Height	*in*	1.0-4.0"		
Adjustment of Cutting Height	*in*	1/4" (BX2190/BX2390S), 1/2" (BX2390/BX2690/BX2690S)		
Transport Position Ground Clearance *with R4 tires*	*in*	5.5"		










LA405
Kubota





HEAVY WORK MADE LIGHT

Performance-matched to the BX90 Series, the LA355 and LA405 are the next generation of BX loaders. With increased lift capacity, robust design and dual bucket cylinders you can get more done no matter the job.

Dual Function Loader Valve

Helps you operate with more efficiency and control by giving you the ability to work the boom and bucket simultaneously.

2-Lever Quick Coupler

Simplifies the changing of loader attachments and standardized size to fit a variety of tools.

Live 3rd Function

Add more versatility to your machine with the optional live 3rd function loader valve, ideal for running grapples or snow blades that require independent hydraulic control.

Kubota Swift-Tach

Simplifies loader attachment and removal without stepping off the tractor. Optional Swift-Tach kits include one lever to remove hydraulic couplers and a dedicated lever to raise and lower parking stands from the operator station.

Mechanical Self-Leveling

Help keep the attachment level while raising and lowering the loader with optional mechanical self-leveling.

Grille/Brush Guard*

Shield the lights and hood from tree limbs, brush and debris to help protect the front of your tractor.

** Grille guard standard on LA405 and optional on LA355. Brush guard optional on LA355 and LA405.*

LOADER SPECIFICATIONS		LA355	LA405
Compatible Models		BX2190 / BX2390S	B2390 / BX2690 / BX2690S
Maximum Lift Height *(to pivot pin)*	*in (mm)*	72.3 (1837)	
Reach *with bucket on ground*	*in (mm)*	54.7 (1390)	
Maximum Rollback Angle	*deg*	40	40
Digging Depth	*in (mm)*	3.9 (100)	3.9 (100)
Overall Height in Carry Position	*in (mm)*	41.7 (1058)	41.7 (1058)
Lift Capacity *at max height (bucket pivot)*	*lbs (kg)*	639 (290)	811 (368)
Lift Capacity *at 1.5m (bucket pivot)*	*lbs (kg)*	721 (327)	904 (410)
Breakout Force *(pivot pin)*	*lbf (N)*	1281 (5700)	1559 (6933)




Kubota
SGC0554


Kubota



BUILT TO DIG

The BX2390S and BX2690S come with a fully integrated loader and backhoe – performance matched to the machine, ready to dig from day one.







Chassis Mounted Backhoe
Reinforces frame connection for durability, stability and strength.

Independent Backhoe Seat
Switch between tractor and backhoe operation quickly and easily without the need for rotating tractor seat adjustments.

Boom & Swing Cushion Valve
Reduces shock to operator and machine, making it easy to control for new and experienced operators.

Optional 3-Point Linkage Kit
Give your machine the ability to attach 3-point implements.

BACKHOE PERFORMANCE		BX2390S	BX2690S
Transport Height	*in (mm)*	68 (1719)	
Stabilizer Spread - *Operating*	*in (mm)*	73 (1862)	
Ground Clearance	*in (mm)*	9 (240)	
Digging Depth, *2 ft. Flat Bottom*	*in (mm)*	73 (1842)	
Operating Height Fully Raised	*in (mm)*	100 (2539)	
Reach from Swing Pivot	*in (mm)*	103 (2612)	
Lift Capacity *at 3 ft. (bucket pivot)*	*lbs*	454	535
Swing Pivot to Rear Axle Center Line	*in (mm)*	31 (778)	
Swing Arc	*deg*	140	
Digging Force *with Bucket Cylinder*	*lbf*	1936	2263
Digging Force *with Dipper Cylinder*	*lbf*	1171	1369

THE BX DOESN'T HIBERNATE

The optional BX90 cab keeps you in the seat and out of wintry conditions. Pair it with Kubota's snow attachments and the BX90 becomes the most capable piece of equipment on your property from the first frost to the last thaw.





Entry Cab

Heated cab for the BX2190 and BX2390S. Standard with cab heater, front LED lights and front wiper.

4 Post Cab

This heated cab maximizes operator space and visibility. Standard front LED lights, side mirrors and front wipers keep visibility high when light is low and snow is falling. An integrated switch panel allows quick control access with a modern look for deluxe and premium models.

K-Connect

Front hitch and PTO system makes it quick and easy to install and remove front attachments like a snowblower, blade or rotary sweeper. By keeping the attachment out front, K-Connect improves sightlines and operator comfort while helping the BX90 stay productive year-round.

BX SPECIFICATIONS		BX2190	BX2390 Deluxe	BX2690 Premium	BX2390S	BX2690S Premium
ENGINE						
Type		Liquid-Cooled, 4-Cycle Diesel				
Engine Gross HP (kw) at Rated RPM		19.3 (14.4) @ 3200	21.6 (16.1) @ 3200	23.9 (17.8) @ 3600	21.6 (16.1) @ 3200	23.9 (17.8) @ 3600
PTO Power HP (kw) at Rated RPM		15.7 (11.7) @ 3200	17.2 (12.8) @ 3200	18.7 (14.0) @ 3600	17.6 (13.1) @ 3200	18.7 (14.0) @ 3600
Displacement	*cc*	778	898			
Fuel Tank Capacity	*gal (L)*	6.6 (25)				
DRIVETRAIN						
Transmission		HST, High-Low Gear Shift				
Drive Method		4WD				
Brakes		Wet Disk				
PTO		Independent PTO with Hydraulic Clutch				
Rear PTO Engine Speed	*RPM*	540 / 3140	540 / 3140	540 / 3505	540 / 3140	540 / 3505
Mid-PTO Engine Speed	*RPM*	2629 / 3200	2629 / 3200	2651 / 3600	2629 / 3200	2651 / 3600
HYDRAULICS						
Pump Output at Rated RPM	*gpm (l/min)*	6.2 (23.6)	6.8 (25.8)	7.7 (29.0)	6.2 (23.6)	7.7 (29.0)
3-Point Hitch		SAE Category I			Optional	
Lift Capacity *at 24 in. Behind Pin*	*lbs (kg)*	950 (431)	892 (405)	898 (407)	950 (431)	898 (407)
Steering		Hydraulic Power Steering				
TIRE SIZE						
Front*		18×8.5-10				
Rear*		26×12-12				
TRAVELING SPEEDS AT RATED ENGINE RPM						
Forward	*mph (km/h)*	0-8.4 (0-13.5)	0-8.4 (0-13.5)	0-8.9 (0-14.3)	0-8.4 (0-13.5)	0-8.9 (0-14.3)
Reverse	*mph (km/h)*	0-6.5 (0-10.5)	0-6.5 (0-10.5)	0-6.9 (0-11.1)	0-6.5 (0-10.5)	0-6.9 (0-11.1)
DIMENSIONS						
Length with 3-Point Hitch	*in (mm)*	95.5 (2425)				
Width	*in (mm)*	44.5 (1130)				
Height with ROPS	*in (mm)*	83.0 (2111)	82.0 (2198)	86.5 (2083)		
Wheelbase	*in (mm)*	55.1 (1400)				
Ground clearance	*in (mm)*	8.4 (213)				
Tread - Front	*in (mm)*	36.6 (930)				
Tread - Rear	*in (mm)*	32.3 (820)	34.2 (870)	34.2 (870)	32.3 (820)	34.2 (870)
Turning Radius (w/o brake)	*ft (m)*	5.9 (1.8)	5.6 (1.7)	5.6 (1.7)	5.9 (1.8)	5.6 (1.7)
Tractor Weight with ROPS	*lb (kg)*	1433 (650)	1477 (670)		1598 (725)	1620 (735)

*Applicable to R3 turf, R4 industrial and R14 hybrid models.

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.







For more information, go to **kubotausa.com/equipment-series/bx-series**



kubotausa.com | Copyright © 2026 Kubota Tractor Corporation. All rights reserved. | KUB-BX90US | September 2026