

PRODUCT CHARACTERISTICS	TEST METHOD	UNIT	TYPICAL VALUES
Tensile Strength(CD)*	DTM001	N/25mm	Min: 40
Hook Shear in oven 38C* (1kg) (on mechanical frontal)	DTM004	minute/25mm	Min: 40
Roll Width	-	mm	300 ± 1
Roll Length**	-	m	2490± %1
Core Internal Diameter**	-	mm	152 ± 1
Basis Weight	DTM003	gr/m <sup>2</sup>	100 ± 10

Specifications can be changed without notice, as a result of our attention in improving our products quality.  
The values of the TDS refer to material stock under correct conditions (as specified in the MSDS) for a 12 month-old period from the date of the production.

## PRODUCT DESCRIPTION

- Nonwoven layer with hook.
- Used in diaper fastening systems.
- Compatible with adhesive and thermal bonding processes.
- Basis weight depends on product construction
- Standart widths: (single widths 46/50/61/65/100 mm)
- Custom options available

## PACKAGING

- Supplied in roll form with pancake and spool options
- Core diameter: 6 inches
- Spool format:
  - Width: 320 mm
  - Outer diameter: 700 mm
- Pancake format:
  - Outer diameter: 700 mm

## SHELF LIFE & DISPOSAL INFORMATION

- Shelf life: up to 12 months when stored in original packaging
- Store in a dry environment, protected from direct sunlight, humidity, and extreme temperatures
- Disposal should be carried out in accordance with local waste management regulations
- Product is recyclable

The information contained in this document is provided for informational purposes only and does not constitute a legally binding commitment, warranty, or specification.  
The manufacturer reserves the right to modify product specifications and information without prior notice.