

Whole of service life performance in every layer.

Supralon industrial filters truly are 'long-life'.

They enable operators to very quickly achieve and maintain the highest standards of cleanliness that will protect L&H systems against component failure and unscheduled downtime.

And here's the...

proof

Protection

4.2

Beta 2000 rating

Higher BetaX(C) $\geq$ 2000 rating for faster system clean-up.

Competitor A	5.7
Competitor B	6.3
Competitor C	9.3
Competitor D	9.5
Competitor E	9.6
Competitor F	9.9

Flow

0.34

Flow-dp bard/100l @ 30 cst

Well-balanced flow ratings are totally in-sync with other performance ratings.

Competitor A	0.45
Competitor B	0.32
Competitor C	0.32
Competitor D	0.33
Competitor E	0.28
Competitor F	0.22

Priority

12/08/<1

CST rating

CST (Cyclic Stabilization Test) ratings to ensure high performance consistency over the full element service life.

Competitor A	17/12/01
Competitor B	17/13/<1
Competitor C	18/15/<1
Competitor D	17/14/04
Competitor E	17/14/01
Competitor F	21/18/05

Longevity

X

Particles >6µm at 90% of life

Particle removal efficiency is twice as good when compared to BX(c)>1000 rated filters and ten-times better efficiency than the most common BX(c)>200 rated filters.

Competitor A	35
Competitor B	60
Competitor C	110
Competitor D	125
Competitor E	248
Competitor F	2000



Supralon. Keep your industry flowing

Want to know more?

Find out how Pall's Supralon can ipsum delorum text required for sign off and call to action copy.

Ipsum delorum endrium on ondiri - text required .

CTA - TBC