## DS SERIES - "B" RATE ROTARY AND FRONT LOADING

# AMSEC'S DS SERIES DEPOSITORY SAFES are

designed to provide immediate deposits and storage for cash, jewelry and miscellaneous valuables.

Deposits can be made to a locked compartment via a toploading rotary hopper, a reverse or a front-loading deposit door.







DSF2714K



DSF2014 WITH ESL10XL LOCK

### **STANDARD FEATURES**

#### **BODY:**

- Strong, formed "B" Rate construction made of A36 solid steel plate for improved security and appearance.
- Formed door jamb for increased resistance to sledgehammer attack.
- Four anchor bolt holes are standard.

# DOOR - MODEL NUMBERS: 2014, 2714 AND 3214

- ½" thick A36 solid steel plate, recessed ½" to increase resistance to pry attack.
- U.L. Group II combo lock (C), U.L. listed dual nose keylock (K).
- · Optional electronic locks available.
- . Three 1" diameter chromed steel locking bolts.

- Bolt detent system engages boltwork automatically.
- · Auxiliary spring-loaded relocking device.
- Lock and relock protected by large carburized hardplate.

#### **HOPPER:**

- 2014 is available w/reverse hopper.
- · Large package sizes:
- (Top Load Rotary): 4¾"D x 4¾"W x 10"L
- (Front/Reverse Load): 4"D x 2¾"W x 10½"L
- Recessed, heavy duty 3/16" construction (½" door).
- · Protected by dual "anti-fish" baffles.



DSF3214CC

Model †	Inside Dimension H x W x D	Outside Dim* H x W x D	Clear Door H x W	Cu. In. Capacity	Wt.
DST2014	11-½ x 13-¾ x 11	20-1/4 x 14 x 14	9- <sup>3</sup> / <sub>4</sub> x 9- <sup>3</sup> / <sub>4</sub>	1,739	90
DSF2014	10 x 13-¾ x 11	20-1/4 x 14 x 14	9-³/4 x 9-³/4	1513	79
DSC2014KC **	BT 10-1/4 x 13-3/4 x 11 TP 6-7/8 x 13-3/4 x 12-3/8	27-1/4 x 14 x 14	BOT 9-3/4 x 9-3/4 TOP 6 x 10-3/8	1513 1127	104
DST2714	18-½ x 13-¾ x 11	27-1/4 x 14 x 14	9-¾ x 9-¾	2798	101
DSF2714	17-½ x 13-¾ x 11	27-1/4 x 14 x 14	9-¾ x 9-¾	2609	93
DSF3214	TP 11-¼ x 13-¾ x 11 BT 12-½ x 13-¾ x 11	32-½ x 14 x 14	9- <sup>3</sup> / <sub>4</sub> x 9- <sup>3</sup> / <sub>4</sub>	1815 1702	144

#### **IMPORTANT:**

AMSEC depository safes are recommended for an operation that requires a non-returnable deposit such as armored car companies, convenience stores, restaurants, etc. The top locker is not meant for overnight storage of cash or valuables.

†Specify Prefix: T=Top Loading, F=Front Loading, R=Reverse Hopper, K=Key Lock, C=Combo Lock, E=Electronic Lock

\*Add 2" to outside depth for dial and handle projection.

<sup>\*\*</sup>Camlock on locker, combination on deposit safe.

## **DS SERIES TILL STORAGE DEPOSITORY SAFES**



#### BODY

- 1/8" solid steel plate
- Four anchor bolt holes

#### **DOOR**

- 1/2" solid steel plate
- ESL20XL, U.L. Type 1 High Security electronic lock
  - 1. Time Delay
  - 2. Multiple users
  - 3. Dual Control
  - 4. Armored car override.
- Three 1" dia. steel locking bolts.
- Auto lock bolt detent system
- Auxiliary relocking device.
- Large carburized hardplate

### **INTERIOR**

- · Receiving locker:
  - 1. <sup>1</sup>/<sub>4</sub>" solid steel plate
  - 2. Clear door: 6"H x 10"W
  - 3. ID: 5 <sup>7</sup>/<sub>8</sub>"H x 15 <sup>3</sup>/<sub>4</sub>"W x 13 <sup>3</sup>/<sub>4</sub>"D
  - 4. Cubic capacity: 1272 cu/in.

- · Till Storage Compartment
  - 1. Fit up to 4 till trays
  - 2. Clear door: 141/2" h x 12" w
  - 3. Inside Dimensions:  $9''h x 15^{3}/_{4}''w x 17''d$
  - 4. Cubic capacity: 2410 cu/in.

#### FRONT HOPPER

- Large package sizes: 4"D x 2<sup>3</sup>/<sub>4</sub>"W x 10<sup>1</sup>/<sub>2</sub>"L
- 1/4" solid steel plate
- · Dual "anti-fish" baffles.

#### **REVERSE HOPPER**

- Large package sizes: 4"D x 21/2"W x 91/2"L
- ½" solid steel plate
  - Protected by dual "anti-fish" baffles
- Thru the wall depository with adjustable chute.
- Wall Thickness: 6 <sup>7</sup>/<sub>8</sub>" to 13 <sup>7</sup>/<sub>8</sub>"
  Floor Height: 36 <sup>3</sup>/<sub>4</sub>" to 48 <sup>3</sup>/<sub>4</sub>"

Model	Inside Dimension H x W x D	Outside Dimension H x W x D	Clear Door H x W	Cubic Inches	Wt.
DSF2516E2	24-¾ x 15-¾ x 17	25 x 16 x 20	14-½ x 12	3,682	240
DSR2516E2	24-¾ x 15-¾ x 17	25 x 16 x 20	14-½ x 12	3,682	260


## **MONEY MANAGER SERIES**

AMSEC's "B" Rate Money Manager Series Undercounter Two Door Depository Safes are the most effective cash handling systems available. Engineered to help you achieve total cash control.

#### **STANDARD FEATURES:**

- ½" solid steel doors.
- ESL15 electronic lock.
- · Three 1" diameter locking bolts.
- · Auto lock bolt detent.
- · Auxiliary relock device.
- · Large carburized hardplate.
- · Coin racks.
- Front hopper: 161/4"W x 2"H x 31/2"D.
- Front hopper features "anti-fish" baffles.
- Four anchor bolts with hardware.
- 3 models: top, center or three drop.
- Three drop offers three color-coded drops and bins.
- Attractive Charcoal Gray textured finish.







MM2820E15 CENTER DROP



MM2820E15 THREE DROP

Model	Inside Dimension H x W x D	Outside Dimension H x W x D	Clear Door H x W	Cu. In. Capacity	Wt.
MM28203-Drop-E15	TOP 9½ x 20 x 17 BTM 11 x 20 x 17	28 x 20½ x 20	8½ x 16-¼ 8½ x 16-¼	3,230 3,740	247
MM2820Top-Drop-E15	TOP 9½ x 20 x 17 BTM 11 x 20 x 17	28 x 20½ x 20	8½ x 16-¼ 8½ x 16-¼	3,230 3,740	274
MM2820Ctr-Drop-E15	TOP 10-3% x 20 x 17 BTM 10-3% x 20 x 17	28 x 20½ x 20	8½ x 16-¼ 8½ x 16-¼	3,230 3,740	278