



The Corporation of The Village of Burk's Falls

# Asphalt Resurfacing

## Burk's Falls, ON

### Addendum # 3

Date Issued: August 20, 2025

To: All Bidders

---

The following information, amendments, and revisions shall form an integral part of the Bid Solicitation Documents and where applicable, shall supersede requirements of other Bid Solicitation Documents.

#### PROCEDURE

1. Add: Approximate depth of existing asphalt is 80 mm to section 5.14 Area 1: Ontario Street.
2. Change section 5.14 Area 2: Remove/mill existing asphalt/material for new asphalt 80 mm depth) to read: Remove/pulverize existing asphalt/material for new asphalt. The approximate depth of existing asphalt is 40 mm.
3. Add to Section 5.14 Area 1: Ontario Street  
Remove/mill existing asphalt/material for new asphalt (80mm depth) from outside white line on the west side to 6" on the outside of the white line east side of Ontario Street.
4. Remove from Section 5.14 Area 2: Victoria Street  
From outside white line on the west side to 6" on the outside of the white line east side of Ontario Street.
5. Change 5.13.1

#### Milling and Disposal of Milled Material

The successful bidder shall be responsible for the milling/removal of the existing asphalt surface for Area 1: Ontario Street to provide a smooth transition from the asphalt to the existing roadway and all areas in between the curb and gutter. All milling operations shall conform to OPSS 510.

The milling operations shall be carried out at Area 1. Milling depth is provided within Area 1 (approximately 80 mm). The contractor is responsible for disposing of millings. The disposal of the millings can be disposed of at the 140 Dimsdale Street in Burk's Falls if chosen by the contractor and arranged with Village of Burk's Falls by the contractor.

6. Change 5.13.2 PULVERIZING OF ASPHALT MATERIAL

The successful bidder shall be responsible for pulverizing the existing asphalt surface for Area 2: Victoria Street to provide a smooth transition from the new asphalt surface to the existing roadway. All pulverizing operations shall conform to OPSS.MUNI 330.

The pulverizing operations shall be carried out at the Area 2: Victoria Street location to the milling depth provided within Area 2 (Approximately 40mm). The total depth of pulverizing shall be to 250 mm below the existing asphalt surface. Pulverizing shall achieve a minimum of 50% blended asphalt/granular ratio, either by increasing or decreasing the depth of pulverization. Surplus pulverized material shall be used as fill for restorative site grading around existing gravel driveways and entrances (4 driveways, 1 street entrance (High St.)), to build up shoulder elevations and to grade out transition locations between existing asphalt surface elevations and the pulverized asphalt elevations). If more pulverized millings are needed to be removed they can be disposed of at the 140 Dimsdale Street in Burk's Falls if chosen by the contractor and arranged with Village of Burk's Falls by the contractor

Addendum Issued by:

Derek Smith

Village of Burk's Falls

Public Works, Foreman

705-382-1893

Cell 705-783-8255